



Hengesbach

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Hengesbach Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Hengesbach Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Ks070g8	Capac. Pressure transmitter KS070G8_50mbar_1,5m for gauge and absolute pressure with fixed measuring range Capacitive pressure sensor with ceramic membrane, Field housing made of material 1.4301 hygienic design Electronics potted Protection class IP 67 & IP 69K acc. EN 60529 Supply voltage 13 ... 36V DC Output signal 0 ... 20 mA, 3-wire SPAN $\pm 20\%$ adjustable Linearity $\leq \pm 0.2\%$ FS Overload protection ≥ 1.5 times the sensor measuring range Process connection: G8, internal thread G1 "B, according to ISO228, Wkst. 1.4404 Sensor measuring range: 0.05bar rel Electrical connection: ref cable 1.5m Measuring cell seal: Viton (O-ring) Set measuring range: 0.05bar r
A-CDT-MZ DIN11851 4733DN50PEEK-05	
A-CONDUTEC K M5 0000	
DMU RSCOe100 U 10bar MDM7310 DN32	
F-FESDFVLT	
F-MWU	
F-VOLUMTEC G AC 0D	
F-VOLUMTEC G DC 0D	
K M5 0000	
KS050DN3	
nm	
P-DMU RSCOe100 U MPRM02A 000	
P-PZM080DKRMT1	

P-PZM100CRKT1	
P-PZM100ERMT1	
P-RCKOe100 U 6bar M2 RDM7635,25	
P-TCF050DG7RAK 100ba	
P-TCSG6LRW	
P-TPF050DCSMRe1KT2	
P-TPF050DCSQRr4KT2	
P-TPF080DCSJr4KT2	
PZM101 0,35bar MT1	
RC100 U 10bar/psi MDM7310, DN40	
RCK0E100/U/6bar/M2 RDM7635	
T-06402409	
T-TP12/TW39 T039/T352 M BH90L099	
T-TP12/TW39 T039 B390L099	
T-TP12/TW39 T039 BH10L060	
T-TP51/TW68 CY90L050T516	
T-TP60/TW39 T500 BH90L050	
WTH TP12/TW39BH50L030T039	
WTH TP16/TW39BH05L040T397	
P-KS101N3ERK2	
WTH TP51/TW68CY90L040T504	<p>- Quicktemp version Compact resistance thermometer with screw-in thread G1/4" external thread, adjustable, for installation in a protective sleeve. Measuring range / version M12 connector: 0-100°C, 2-pin Installation length: 117mm (T504) Matching welding protection sleeves: T-06402400, T-06402387, T-06402427, T-06402455 Options: (none) --- Material Wkst. 1.4301 Hygienic Design, protection class IP 68 according to EN 60529. With transmitter TE62, programmable, or resistance output. Sensor type: 1xPt100, 4-L, class A Electrical connection: circular connector M12x1, 2-pin - different for resistance output: 4-pin According to data sheet 540_T-TP51-TW68-D-17-1-1.</p>
	<p>Pressure transmitter KS050DM5_1.3barA_K2 - capacitive - Ordering information Sensor measuring range / set measuring range: 2bar ab. / 1.3bar abs Electrical connection: cable connection, 5-9mm Seal pressure measuring cell (in contact with product): profiled EPDM, FDA-compliant Suitable for measuring relative or absolute</p>

P-KS050DM5FAe3K2	pressure. Capacitive pressure sensor with ceramic membrane, field housing made of material 1.4301 Hygienic Design. Electronics encapsulated. 2-button concept and multi-colored status LED for parameterization. Protection class IP 67 & IP 69K in accordance with EN 60529. Supply voltage 12...30V DC. Output signal 4...20 mA, 2-wire. TurnDown 4. Linearity $\pm 0.2\%$ FS Overload safety 1.5 times the sensor measuring range Process connection: M5, conical socket with grooved union nut according to DIN 11851 DN 50 / PN 25, material Wkst. 1.4404. According to data sheet PN-KS050D-D-14-1.
T-TP16/TW39 T392 BH90L040	WTH TP16/TW39BH90L040T392 Resistance thermometer Process connection G1/2B with elastomer-free sealing cone, d=6mm, tapered to D=4mm, made of CrNiSt 1.4571 Field housing made of CrNiSt 1.4301 Hygienic Design Protection class IP67 with neck tube l=120mm, d=12mm el. connection cable screw connection M16x1.5 with temperature transmitter TE42, 4...20mA, 2-wire, programmable or resistance output/ terminal block Ordering information Sensor type: 1xPt100, 3-L, Class AA Connection head: field housing Installation length: 160mm Output/measuring range: TE42 0-100°C according to data sheet: T-TP16-TP26... in the currently valid version
TPF080DCS_4bar_KT2	
TW39BH90L099T395	
TW39BH90L040T397	
TW39BH90L099T448	
TW39BH90L040T449	
Tcsg6_20bar_W	
7110001.07 H-1431	
Pzm100_350mbar_Kt1 Pressure Sensor	
Keradiff_150aoy7c11	
2-01-4-3-17	
Keradiff_140acy7d11	
Converter Pzm101_0-5bar_Mt1,	
Ks050g2	Hengesbach KS050G2_30mbar_K3 Range : 0...30 mbar Pmax : 4 bar Output : 4...20 mA 2-wire Supply : 13...36 VDC Drucksensor
Tp12/Tw39bh90l060t460 Sensor	
Tp12/Tw39bh90l099t352/M12-Te32*-10..+40	
Tcsg6_10bar_M	

Keradiff 1501oy7c11
Keramess 050 G2 0?0,40 K 2
00006970 Detail Dn 25mg,Ng: 100 For Dcp Sf-85,Serial
Ks050 M5 1,3bar Abs K2
F/G1i
Pzm080 10bar Mt1 Drucksensor
Wth Tp60/Tw39bh90I050t500
Keramess 050 G2 0...0,40 K 2
9mqo 389.10.2002
Tcsg6 25bar W
06402381
Pzm201
Tw39d39ok000to56
Manometer Typ Dmu, 0-10bar, 10-40vdc, 4-20ma, Splitter-Umgebungen Dn32
Pzm101 0,35bar Mt1 Intelligent Pressure Transmitter
Keradiff 150any7c11
06402409 Adaptertemperature Transmitter Adapter (Process)d12mm L=64mm Zeh/T516
Keradiff 140aby7d11
Tcs G1/2flo Drucksensor 20 Bar
Conduotec K V80000
1709931.02.003
Leveltec Sbm
A-Conduotec K Pzm_00h4 Conductivity Converter
Keradiff 1401cy7d11
T-Tp12/Tw39 T460 Bh90I060
Keradiff 140acy7c11
Keradiff 100acy7c11
Gã189;B 30mbar 4-20ma

Tp 12/Tw39bh90l060t460 Sensor
Ks050dn3 1bar K2 Capacitive Pressure Transmitter Keramess
Pzm100 -1/+1bar 1mt1
Tpf 080dcs 4 Bar Kt2 Sensor
1490001310214103
Pzm101 1bar Mt1
Keradiff 150aby7d11
Keradiff 1001cy7c11
P-Tpf050dcs
Keradiff 1001ny7c11
Kramess F/Mg50
Keradiff 100any7c11
Keradiff 100aoy7c11
Keradiff 140any7c11
Ks070g8 50mbar R053 <p>Capacitance pressure transmitter KS070G8_50mbar_R053 for relative and absolute pressure with fixed measuring range Capacitive pressure sensor with ceramic membrane, Field housing from Wkst. 1.4301 Hygienic Design Electronics shed Degree of protection IP 67 & IP 69K acc. EN 60529 Supply voltage 13 ... 36V DC Output signal 0 ... 20 mA, 3-wire Span ± 20% adjustable Linearity ≤ ± 0.2% FS Overload safety ≥ 1.5 times the sensor measuring range Process connection: G8, female thread G1 "B, according to ISO 228, Wkst. 1.4404 ordering information Sensor measuring range / set measuring range: 0.10 bar rel / 0.05 bar rel Electrical connection: Ref cable 1,5m Seal measuring cell: Viton (O-ring) Customs tariff number: 90262020 Country of origin: DE Weight: 1.2 kg</p>
Keradiff 1001by7d11
Keradiff 1001cy7d11
Keradiff 100any7d11
Volumtec G Ac Od
Ks050m5 10bar K2
Zfl / Drd-Flange D=65 Mm
G½b 30mbar 4-20ma
Dns6-201

18466011 0-160c 10w-18va
73541/6 Der Messumformer Des Durchflussmessers Type Volumtec G Dc Od
Keradiff 150acy7c11
Keradiff 1401cy7c11
??12/Tw39bh90I099t039
Ks070g8 50mbar R3(1,5m)
T-Tck100 U A6 0-120° I2
Dp 4522c2r244
Ks070 G8
2-01-4-3-17 Conductivity Transmitter
Ks101 N3 1bar K2
Ifferencial Pressure Gauge Ng 100
Pzm101
Keradiff 1501cy7d11
Keradiff 100aby7d11
Keradiff 1401by7d11
Liquitec Ybba
Ksf 101/N
Tp51/Tw68 CI0 50 T516 Temperatur- Sensor
Keradiff 150acy7d11
Keradiff 140aoy7c11
L Sbma
Keradiff 1001oy7c11
P-Tpf080dcsjre4kt2
Keradiff 1401oy7c11
Leveltec L Sbma
Wth Tp12/Tw39bh90I060t460
Rcg63
Keradiff 1501by7c11

Keradiff 1501ny7c11
Pzm101 2,5bar Mt1
P-Pzm050derkt1
En 837- 1.4576 1-9 Bar
Mdm7340
Keramess/F/G11 -Old Code, New Code - Ks070q8 50mbar R3(1,5m)
Keradiff 100acy7d11
Rck0e100/U/6bar/M2 Rdm7635 Inspektionswerkzeug Auf Manometer
4/2I Kd F 2wire
Keramess/F/G1/L
Keradiff 1401ny7c11
Din11851 Pressure Gauge With Diaphragm Seal Dn41
Zem / Vpm T (Pe1)
Tp60tw39bh90l040t500
Keradiff 1401by7c11
Keradiff 1501by7d11
Tw39bh90l040t392
Tp12/Tw39bh90l060t460
T-Tp12/ Tw39 T460 Bh90l060
N-Leveltec2 L Sbma
Tcsg2
P-Tpf050dcsre2kt2
094854212
Tp60/Tw39bh90l050t500
P-Tcf050dg7rak 100bar Drucksensor Tcf050dg7 100bar K
Tp/Tw39bh90l099t039 Temperatursensor
Keradiff 1501cy7c11
11228.01039

[Ks101 N3 250mbar K2](#)

[Rcg63/U/Fr](#)