



## Herborner Pumpenfabrik

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Herborner Pumpenfabrik** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Herborner Pumpenfabrik Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">A2G_103</a>	<p>Series: UNIPUMP Type: 5.5/QSH101-1-184-F-W1 WORKING CONDITIONS Flow rate (Q1): 100 m3/h discharge head (H1): 8 m ENGINE DATA Manufacturer: HOYER Size / Number of poles: 112 Type: IM B5/V1 Mains frequency: 60 Hz Voltage: D440 V Motor frequency: 60 Hz Engine speed: 1,750 rpm Engine power: 4.7 kW Rated current: 8.9 A Starting current: 56.59 A Cos phi: 0.84 Protection class: IP 55 ISO class: F/B Classification: Ship Max. ambient temperature: 45 °C Thermal motor protection: PTC thermistor Engine cooling: self-surface cooling Ball bearing A / Relubrication: Lifetime lubricated Ball bearing B / Relubrication: Lifetime lubricated BIKE Impeller type: open single-channel impeller with fiber cutting device Outer diameter: 184 mm Grain size: 80 mm DIMENSIONS Suction nozzle: DN 100 PN16 Pressure nozzle: DN 100 PN16 nozzle position: V Terminal box screw connection: 2xM20x1.5 MATERIAL TYPE: W1 Pump housing: Gray cast iron EN-GJL-250 Motor housing: AL Intermediate housing: gray cast iron EN-GJL-250 Suction cover: gray cast iron EN-GJL-250 Impeller: gray cast iron EN-GJL-250 Motor shaft: stainless steel X6CrNiMoTi17-12-2 (1.4571) Primary shaft seal: mechanical seal SiC/SiC/Viton Paint: RAL 5010 Gentian blue pump without accessories</p>

