



Herrblitz

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Herrblitz Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Herrblitz T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
A050T	
Herrblitz	
Herrblitz	
Herrblitz	
A050TER	herrblitz pneumatic feeder Control by mechanical valve Rear roller to optimize the strip positioning while entering the feeder Max. strip width 50 mm Max. feeding stroke 50 mm (it's the new version of your feeder A050, which is no longer produced)
KITABC+TER	kit repair for feeder ABCTER
C100TER	pneumatic feeders Control by mechanical valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 100 mm Max. feeding stroke 100 mm
model DX050	herrblitz pneumatic feeder Equipment and technical features: Control by mechanical valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 150

	mm Max. feeding stroke 50 mm
A100TER	pneumatic feeder Equipment and technical features: C0ntrol by mechanical valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 50 mm Max. feeding stroke 100 mm
C050TER	pneumatic feeders Control by mechanical valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 100 mm Max. feeding stroke 50 mm
A100TER/P	C0ntrol by pneumatic valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 50 mm Max. feeding stroke 100 mm
A100TERE	C0ntrol by electric valve in the voltage you need (choice among 24 VAC / 110 VAC / 220 VAC / 24 VDC) à Please confirm us the voltage needed at the order Rear roller to optimise the strip positioning while entering the feeder Max. strip width 50 mm Max. feeding stroke 100 mm
Pneumatic feeder, model A050TER	Equipment and technical features: Control by mechanical valve Rear roller to optimize the strip positioning while entering the feeder Max. strip width 50 mm Max. feeding stroke 50 mm
C100TER	pneumatic feeder Equipment and technical features: Control by mechanical valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 100 mm Max. feeding stroke 100 mm
Typ: B050 Pos. 66	
Typ: B050 Pos. 157	
Typ: B050 Pos. 102t	
Typ: B050 Pos. 65	
Sx150e	
Typ: B050 Pos.7t	
Typ: B050 Pos. 69	
Yb050r	
Db11/Abc/50 +68+69	
Typ: B050 Pos. 1 Hauptblock	
Part 11 For A250t	
C050ter	
Typ: B050 Pos. 207	
Bxd50p (Do19800)	
Multistroke Counter Box Ref 153	

A050ter
Typ: B050 Pos. 60t
Typ: B050 Pos. 12
Db12/Abc
Va/ Abcx
Vsabcxter
Typ: B050 Pos. 105
Typ: B050 Pos.63t
Typ: B050 Pos.62t
Typ: B050 Pos. 11
Typ: B050 Pos. 13
Typ: B050 Pos. 83
Typ: B050 Pos. 5t
Typ: B050 Pos. 9
Typ: B050 Pos. 14
Typ: B050 Pos. 64
9+10/Abc/50
Typ: B050 Pos.6t+8
Typ: B050 Pos. 104
Typ: B050 Pos. 109
Typ: B050 Pos. 15