

Hiat

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Hiat Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Hiat T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Purifier (Hyp40-831/2/60)	Active electrode area: 28 cm ² (ø 60 mm) number of cells: 2 pcs. H2 production: 831 Nml / min H2 production @ 70 ° C: 1045 ml / min O2 production: 415.5 Nml / min operating temperature: 65 - 80 ° C Current: 3 - 60 A (DC) Stack voltage BOL @ 40 bara / 70 ° C: 3 - 4.12 V Stack power BOL @ 40 bara / 70 ° C: 9 - 247.2 W H2 pressure: 40 bara O2 pressure: Ambient pressure H2 connections: 1/4 "H2O connections: 1/4" H2O inlet pressure: max. 2 bara Water quality: DIN ISO 3696 type 1
Customizer (Hyp40-1000/1/93)	Active electrode area: 68 cm ² (ø 93 mm) Number of cells: 1 pc. H2 production: 1,000 Nml / min H2 production @ 70 ° C: 1,256 ml / min O2 production: 500 Nml / min operating temperature: 65 - 80 ° C Current: 5 - 143 A (DC) Cell voltage BOL @ 40 bara / 70 ° C: 1.5 - 2.05 V Cell power BOL @ 40 bara / 70 ° C: 7.5 - 293.15 W H2 pressure: 40 bara O2 pressure: Ambient pressure H2 connections : 1/4 "H2O connections: 1/4" H2O inlet pressure: max. 2 bara Water quality: DIN ISO 3696 type 1