



Hidracar

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Hidracar** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Hidracar T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

| ¼r¼n | A¼ıklama |
|--------------------------------|----------|
| 004-AI | |
| 3.1 EN10204 | |
| ADAPT-S | |
| ADAPT-Y | |
| ADAPT-Z | |
| BT010A-AI | |
| BT025A-AI | |
| BV006A1TM | |
| BV010A1TM | |
| BV100A1ZM | |
| DN15 PN100 | |
| DRB.A/B | |
| F002T+HC2225-S | |

| |
|--|
| F003A0411-A1 |
| F007T+HC2234-S |
| F015A02T1-AI/PD |
| F015T+HC2239-S |
| F060A04T1-AI |
| F060T+HC2252-S |
| M002D-AI |
| M012D-AI |
| M030A03D1-AI |
| MF6A15N10/E |
| PMI |
| U001A20E1 AI - Po=106 barg |
| U001A20E1 AI - Po= 7 barg |
| U001A20E1 AI - Po=27 barg |
| U001A20E1-AI |
| U001A20V1-AI |
| U001E-AI |
| U001V-AI |
| U001V-PD |
| U002A01V1-PP |
| U002A18E1 |
| U002A18E1-AI |
| U002A18V1-AI |
| U002A25E1-AI |
| U002A27N1-AI 1/2 |
| U002A75E1-AI 1/4"NPT |
| U002E-AI |
| U002V-AI |
| U003A01B1-PC |
| U003A01E1- PC |
| U003A18N1-AI |
| U003A18V1-AI |
| U003A24N10/E |

| |
|---|
| U007A01E1-PC |
| U007A01E1-PP |
| U007A01V1-PC |
| U007A05E1-AI |
| U007A05N1-AI |
| U007E-AI |
| U007N-AC |
| U007N-AI |
| U010A01N1-PP |
| U010A04E1-AI |
| U010A04V1-AI |
| U010E-PC |
| U010V-AI/AP |
| U015A01E1-PC |
| U015A01V1-PP |
| U015A04E1-AI |
| U015A11E1-AI/NS |
| U015A11E1-AI/NS DN15 PN100 |
| U015A11E1-AI/NS+ DN15 PN100 |
| U015A17V1-A |
| U015A17V1-AI |
| U015A17V1-AI-AI |
| U015A39E1-AI |
| U030A01V1-PC |
| U030A03V1-AI |
| U030A11V1-AI |
| U030B01E1-PC |
| U030E-AI |
| U030E-AI/AP |
| U030V-AI |
| U030V-AI/AP |
| U040E-AI |
| U040E-PC |

| | |
|--|---|
| U040E-AI | |
| U060A01N1-PP | |
| U100E-PC | |
| M004D-AI | |
| U060A04N1-AI | PULSATION DAMPER Thread conneciton : 1 - 1/2" BSP Female Volume : 5,6Liters Deisgn pressure : 40 bar at 20C(PED) 28bar at 20C (ASME) Body : AISI 316L Bladder : NBR Deisgn tepmeretarues : -15 / 80C Precharge pressure: 32 barg NOTE: if this dampener is to be reexported by air, it could not be sent pre-charged, for security reasons during the transport |
| U060N-AI | BLADDER + INSERT |
| HC2255-N | O-RING |
| 004-AI | CHARGING VALVE |
| U002A18E1-AI | PULSATION DAMPER Thread connection: 1/2" BSP Female Volume: 0,18 litres Design pressure: 180 bar at 20°C Body: AISI 316L Bladder: EPDM Design temperature: -30 / +130°C DOCUMENTATION - Hydrotest & 2.2 certificate - Declaration of conformity with PED2014/68/EU (design code AD -2000) - GA drawing - Manuals of instructions - HIDRACAR standard sticker nameplate with dampener technical data |
| U010A01V1-PC | Thread connection: 1" BSP Female Volume: 0,95 litres Design pressure: 10 bar Body: PVC Bladder: FKM Design temperature: 0 / 60°C Po=0 barg |
| U001a20v1-Ai | PULSATION DAMPER Thread connection : 3/8" BSP female Volume : 0,09litres Design Pressure : 200 bar at 20C Body : AISI 316L Bladder :FKM Design Temperature : -20 / 200C Po = 0 brg |
| U001a20x1-Ai | |
| U001a01x1-Pp | |
| U001a01x1-Pd | |
| F015a03i1-Ai + Dn20 Pn16 + Btãa-Ai.E Bellows Type Pulsation Dampeners | |
| 1676058 Flask U015a11e1-Ans-Dn15-Dn100 | |
| U003a24x1-Ac + 3x4ã186; In 1500ã Rtj (Welded) | |
| U002a18e1-Ai | |
| U010a25x10 + 1 In 600ã Rf | |
| Bv600a1tm | |
| U030a36e1-Ai | |
| F060t+hc2252-S Bellows + O-Ringfor Ref. F060a02t1 | |
| Bv025a1tm | |
| U002a01x1-Pd | |

| |
|---|
| F015a03i1-Ai + Dn20 Pn16 + Bt#A-Ai.E Bellows Type Pulsation Dampeners |
| Bv006a1tm Filling Kit |
| Accumulator U001a20v1-Ai 0,075 (L) 200 Bar |
| F002t+hc2225-S Bellows + O-Ringfor Ref. F002a02t1 |
| U030a11v1-A1 Die Membran Des Akkus |
| Adacneu.5 |
| 004-Ai Charging Valvefor Ref. F007a02t1 |
| U003a26x1-Ai |
| Bv250a1tm |
| U002a75x1-Ai.E |
| U003b01x1-Pp |
| U040a01v1-Pc P-1374 A/B/C |
| U003a01v1-Pc |
| U007a05e1-Ai |
| U030v-Ai Bladder + Insert For Ref.U030a11v1-Ai |
| U010a60x1-Ac + 29x16ã186; In 10000ã Api (Welded) |
| U007a01x1-Pc |
| F007a05i1-Ai + 1 In 300# Rf (Integrated) Bellows Type Pulsation Dampeners |
| U003a30x1-Sa |
| U060n-Ai |
| U002a18x1-Ai + 2 In 300ã Rf |
| F002a02t1-Ai.Pd.Dr Bellows Type Pulsation Dampeners |
| U002a18v1-Ai Pulsation Damper |
| U002v-Ai Bladder+insert |
| U007a05x1-Ai |
| U030a23e1-Ac |
| U040a03e1-Ai |
| U010a47x1-Du.Ns + 1x2ã186; In 2500ã Rtj |
| F015a03i1-Ai Bellows Type Pulsation Dampeners |

| |
|---|
| Bv100a1tm |
| U003a24x10 |
| 004-Ai Charging Valvefor Ref. F060a02t1 |
| U003a01x1-Pc |
| F015a04t1-Ai Bellows Type Pulsation Dampeners |
| U003a13x1-Ai + 3x2ã186; In 1500ã Rf |
| U010a01e1-Pc |
| F007a05i1-Ai + 1 In 300ã Rf (Integrated) Bellows Type Pulsation Dampeners |
| U030a01e1-Pc |
| U003a01x1-Pd + Btãa-Ai |
| U007a01x1-Pp |
| F007a05i1-Ai 1/2"npt |
| U002a01x1-Pp |
| U002v-Ai Bladder-Insert U002v-Ai |
| U015a04e1-Ai Pulsation Damper |
| U040a36e1-Ai 1quot;Npt |
| Bv1000a1tm/E Filling Kit For Very High Pressure |
| Bv400a1tm |
| U001a01x1-Pc |
| 004-Ai Charging Valvefor Ref. F015a02t1 |
| 79745 U002a18e1-Ai + Adacneu.5 |
| U015a20n1-Ac |
| F015t+hc2239-S Bellows + O-Ringfor Ref. F015a02t1 |
| U001a01x1-Pc + 1x2ã186; In 150ã Rf |
| 97825. |
| F002a16t1-Ai.1x2° In Npt Bellows Type Pulsation Dampeners |
| U030v-Ai/Ap Bladder-Insert U030v-Ai/Ap |
| Bv300a1tm |
| U001a02x1-Pc |
| U030a36e1-Ai 1quot;Npt |
| |

| |
|---|
| U001a01x1-Pcc + Btãa-Ai |
| U007b01x1-Pp + Btãa-Pc.Pl |
| Bv160a1tm |
| U002a27x1-Ai.1x2ã186; In Npt |
| U010a04x1-Ai + 1x2ã186; In 150ã Rf (Welded) |
| U007a21x10 |
| U015a25n10 , By U015a20n1-Ac |
| U001a44x1-Ai.3x8ã186; In Npt |
| U 010 A02 V1 Ai Pulsation Damper Balloon V = 1 L, D = 110mm, L = 200mm, Rrasch = 2 Mpa. |
| U002a39x10 + 2 In 2500ã Rtj (Welded) + Btãa-Ai.Me |
| 004-Ai Charging Valve |
| F007a01t1-Pc Bellows Type Pulsation Dampeners |
| U001a01v1-Pc |
| Bv060a1tm |
| U010a04e1-Ai Pulsation Damper |
| F003a0411-A1 1/2 - Obsolete, Replaced By F007a05i1-Ai 1/2"npt Dampener |
| U002a18x1-Ai |
| U002a01x1-Pc |
| 004-Ai Charging Valvefor Ref. F002a02t1 |
| U003a41x1-Ai + 3 In 2500ã Rtj (Welded) |
| U002a18v1-Ai |
| F007t+hc2234-S Bellows + O-Ringfor Ref. F007a02t1 |
| U001a80x1-Ai.3ã215;8 In Npt |
| U030a03v1-Ai Die Membran Des Akkus |
| Bv016a1tm |
| U002a18v1-A1 |
| U030v-Ai/Ap Bladder + Insert High Pressure |
| U030a01x1-Pp |