



Hoffmann

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Hoffmann** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Hoffmann Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
21101705 3u Emc Ss Gasket 10 Pcs	EMC stainless steel seal 3U (10 pieces) *** Stat. Product number: 73201090 Country of origin: DE *** <<< RoHS compliant >>>
A808chfl	nVent, J Box, Type 12, Turn Latch, 203x203x102mm
A8p8g	nVent, Panel, J Box / 6.75x6.88
74-41210015204	Plastic endless belt for HSF 100 - replaces our item no. 74-41510065 -
111700 19W11	
74-41810016131	Plastic endless belt CM series for HSF 150 SE
D4/4-St--S-DC-363-158-A	Float switch 01-12258-S2
74-45842769	Filter bag SENTINEL NMO-250-P01Z-60L
79-50245115220	Differential pressure indicator type deltaP
203 ECH100	Heater 100W <<< RoHS-konform >>>
203 ECHT100	Heater 100W <<< RoHS-konform >>>
558855	Dimensions: 125 mm x 50 mm x 20 mm It will be used on both sides. One side must have a grit number of 500 and the other 180.
A90XM3EW24FTC	
ADSCPA	

AFK1224SS	
PGS2K	
DAH2001A	
ABBSC	
ADP2	
CDSC483812	
CMFKSS	
CP4836	
PGS2K	
CMFKSS	
CP3030G	
CSD303010	
APMT 180508 SR HB 7520	
74-41210017131	Plastic endless belt for HSF 200 Replacement for item 74-41520070
74-41210016147	Plastic endless belt for HSF 150 - Replacement for item 74-41515070 -
74-41210014144	Plastic endless belt for HSF 60 - Replacement for item 74-41506065 -
74-41210015204	Plastic endless belt for HSF 100 2,127.00 2,127.00 - Replacement for item 74-41510070 -
741000 180	
sliding bar wide 91 67 601	h33-4/2019/ 12-0000108
side panel wide right 91 67 596	
side panel wide left 91 67 595	
HM element 87. 591. 67 598	
gate valve 9163 184	
compressor oil filter 505008	
pump drive gear	
three-section hydraulic pump 636000121	
Plastic endless belt for HSF 150	- Replacement for 74-41515070 - Article no. 74-41210016147
Twist drill HSS-E-PM TiAlN	114610 5 Fabrikat: GARANT
354773 50/V25	Reduction SK50 VDI Make: GARANT
354773 50/V30	Reduction SK50 VDI Make: GARANT
354773 50/V40	Reduction SK50 VDI Make.: Garant
354771 50/40	Reduction SK50 SK
338400 10	Tap Extension Make: HOLEX use For thread cutting in inaccessible places, such as deep recesses, shoulders, projecting edges Devices, extremely deep internal threads or directly on cast walls. execution • Long or extra-long version. • The front end of the extension is designed as a collet. By hand-tightening the knurled The collet is clamped with

	the tap using the clamping nut. • The torque is transmitted via the square. • The rear end of the extension conforms to DIN, so the extension can be used in quick-change tapping bits or tap ER collets with square.
74-41210016147	Plastic endless belt for HSF 150 - Replacement for 74-41515070 -
558855 125X50	Denomination: Bench stone for steel, special carborundum medium / very fine LengthXWidth (mm): 125X50
3WAY BALL VALVE	C674D901/002 Pos.7-28 38M-MNT
Plastic endless belt for HSF 100	(Replacement item for 74-41510070) Article no. 74-41210015204
Plastic endless belt CM series HSF 150	Article no. 74-41810016131
371600 18x200	
375300 1816160	
085726 20	
085725 150	
A-EK115NDH	
483910 / Ø15	
483900 02	Ø15, Ø18
483914 0	Ø30,Ø35
483910 02 / Ø18	
483900 02 / Ø15	
483900 02 / Ø18	
483914 0 / Ø30	
483914 0 / Ø35	
838350	Universal deburrer with 1 blade S 150
839678	HSS blade (rear deburring) for 83930
L51050 788	POLINOX fleece grinding point PNL Ø 30x25 m PFERD No. 4007220087831 / 86,000x63,000x1
L51100 184	POLINOX fleece grinding point PNL Ø 40x20mm PFERD No. 4007220157077 / 86,000x63,000x1
418802 500	digital depth caliper Brand: HOLEX execution Easy-to-read digital display. Optimum sliding properties thanks to double prism guide. Measuring bridge made of hard-coated aluminum with two 90° offset holes (M2.5) to accommodate the measuring inserts. scope of delivery Including measuring probe no. 434900 size 2, 3 measuring bridges no. 418803 sizes 150, 300 and 450 mm, 1 battery no. 081560 size. LR44 and factory test report.
432210 10/58	dial gauge waterproof Brand: GARANT execution Precision dial gauges with shock protection, protected against splash water, oil and dirt. Measuring bolt on the shaft with Rubber bellows, sealed at the top by a protective sleeve. Back wall sealed, watch glass and outer ring sealed screwed. Clamping shaft Ø 8 mm h6.
	Polishing abrasive coarse (gray) Brand: GARANT use For fine grinding and polishing of steel, rust- and acid-resistant steel, high-temperature resistant materials and Non-ferrous metals. Polishing grinding pins do not clog even with smearing materials. For matt polishing or attaching optical effects on stainless steel containers, etc. The elastic integration

551850 6X10	of the abrasive grain results in a very fine polish achieved. Not suitable for edges and rough surfaces. execution Polishing pins with normal corundum (A) in rubber-elastic bond. GARANT polishing pens are characterized by a long service life for quickly achieving a fine, even surface Depending on the version, even fine polishing up to a gloss polish can be achieved. GARANT polishing pens can be profiled with dressing tools
551850 8X10	Polishing abrasive coarse (gray) use For fine grinding and polishing of steel, rust- and acid-resistant steel, high-temperature resistant materials and Non-ferrous metals. Polishing grinding pins do not clog even with smearing materials. For matt polishing or attaching optical effects on stainless steel containers, etc. The elastic integration of the abrasive grain results in a very fine polish achieved. Not suitable for edges and rough surfaces. execution Polishing pins with normal corundum (A) in rubber-elastic bond. GARANT polishing pens are characterized by a long service life for quickly achieving a fine, even surface Depending on the version, even fine polishing up to a gloss polish can be achieved. GARANT polishing pens can be profiled using dressing tools.
551900 6X10	polishing abrasive medium (red) use For fine grinding and polishing of steel, rust- and acid-resistant steel, high-temperature resistant materials and Non-ferrous metals. Polishing grinding pins do not clog even with smearing materials. For matt polishing or attaching optical effects on stainless steel containers, etc. The elastic integration of the abrasive grain results in a very fine polish achieved. Not suitable for edges and rough surfaces. execution Polishing pins with normal corundum (A) in rubber-elastic bond. GARANT polishing pens are characterized by a long service life for quickly achieving a fine, even surface Depending on the version, even fine polishing up to a gloss polish can be achieved. GARANT polishing pens can be profiled using dressing tools.
551900 8X10	polishing abrasive medium (red) use For fine grinding and polishing of steel, rust- and acid-resistant steel, high-temperature resistant materials and Non-ferrous metals. Polishing grinding pins do not clog even with smearing materials. For matt polishing or attaching optical effects on stainless steel containers, etc. The elastic integration of the abrasive grain results in a very fine polish achieved. Not suitable for edges and rough surfaces. execution Polishing pins with normal corundum (A) in rubber-elastic bond. GARANT polishing pens are characterized by a long service life for quickly achieving a fine, even surface Depending on the version, even fine polishing up to a gloss polish can be achieved. GARANT polishing pens can be profiled using dressing tools.
551920 6X10	polishing abrasive fine (brown) use For fine grinding and polishing of steel, rust- and acid-resistant steel, high-temperature resistant materials and Non-ferrous metals. Polishing grinding pins do not clog even with smearing materials. For matt polishing or attaching optical effects on stainless steel containers, etc. The elastic integration of the abrasive grain results in a very fine polish achieved. Not suitable for edges and rough surfaces. execution Polishing pins with normal corundum (A) in rubber-elastic bond. GARANT polishing pens are characterized by a long service life for quickly achieving a fine, even surface Depending on the version, even fine polishing up to a gloss polish can be achieved. GARANT polishing pens can be profiled using dressing tools.
551920 8X10	polishing abrasive fine (brown) use For fine grinding and polishing of steel, rust- and acid-resistant steel, high-temperature resistant materials and Non-ferrous metals. Polishing grinding pins do not clog even with smearing materials. For matt polishing or attaching optical effects on stainless steel containers, etc. The elastic integration of the abrasive grain results in a very fine polish achieved. Not suitable for edges and rough surfaces. execution Polishing pins with normal corundum (A) in rubber-elastic bond. GARANT polishing pens are characterized by a long service life for quickly achieving a fine, even

	surface Depending on the version, even fine polishing up to a gloss polish can be achieved. GARANT polishing pens can be profiled using dressing tools.
551922 6x10	Polishing abrasive grain 280 (green) use For fine grinding and polishing of steel, rust- and acid-resistant steel, high-temperature resistant materials and Non-ferrous metals. Polishing grinding pins do not clog even with smearing materials. For matt polishing or attaching optical effects on stainless steel containers, etc. The elastic integration of the abrasive grain results in a very fine polish achieved. Not suitable for edges and rough surfaces. execution Polishing pins with normal corundum (A) in rubber-elastic bond. GARANT polishing pens are characterized by a long service life for quickly achieving a fine, even surface Depending on the version, even fine polishing up to a gloss polish can be achieved. GARANT polishing pens can be profiled using dressing tools.
551922 8X10	Polishing abrasive grain 280 (green) use For fine grinding and polishing of steel, rust- and acid-resistant steel, high-temperature resistant materials and Non-ferrous metals. Polishing grinding pins do not clog even with smearing materials. For matt polishing or attaching optical effects on stainless steel containers, etc. The elastic integration of the abrasive grain results in a very fine polish achieved. Not suitable for edges and rough surfaces. execution Polishing pins with normal corundum (A) in rubber-elastic bond. GARANT polishing pens are characterized by a long service life for quickly achieving a fine, even surface Depending on the version, even fine polishing up to a gloss polish can be achieved. GARANT polishing pens can be profiled using dressing tools.
554971 40X20	Flap grinder fleece coarse SIC use For removing dirt and oxide layers on metals, as well as for matting Cr-Ni and other stainless steels as also of non-ferrous metals. execution Fan-shaped arrangement of the fleece lamellae around the axis of the tool. Shaft diameter 6 mm. The sharp-edged silicon carbide grain (SiC) ensures aggressive grinding behavior and a slightly shiny finish.
554972 40X20	Flap Sander Fleece Medium SIC use For removing dirt and oxide layers on metals, as well as for matting Cr-Ni and other stainless steels as also of non-ferrous metals. execution Fan-shaped arrangement of the fleece lamellae around the axis of the tool. Shaft diameter 6 mm. The sharp-edged silicon carbide grain (SiC) ensures aggressive grinding behavior and a slightly shiny finish.
566486 80	Fiber disc Cubitron II 987C 125mm use On angle grinders with a maximum peripheral speed of 80 m/s with grinding wheels No. 566690 / 566692. The sleek Abrasive grain enables comfortable, ergonomic work with low contact pressure. With the high removal rate 3M™ fiber discs are also a real alternative to grinding and flap discs. For processing stainless steel, aluminum, titanium and nickel alloys. execution The precision-shaped high-performance abrasive grain in 3M™ products consists of defined, ceramic triangles that optimally aligned on the grinding base. Greatly increased removal rate with very long service life and uniform surface finish. Extremely tear-resistant, but very flexible vulcanized fiber. Bore 22.23 mm and cross slots. Tip type Cubitron™ II. Highest removal rate. The additional grinding aid ensures a cool grinding without tarnishing and reduces clogging on lubricating materials.
657277 200	Torque wrench basic unit with scale standard Tested according to DIN EN ISO 6789. use For small to medium series. execution Robust, one-arm torque wrench, adjustable via micrometer scale, with safety device against unintentional Adjustment. Basic device with square drive (without insert tool). Suitable insert tools no. 657582 – 657950. Units of measurement: Nm, lbfft. Notice The guaranteed measurement accuracy of the torque only occurs from the calibrated torque range according to DIN EN ISO 6789.
	insert ring spanner execution Drop forged; all tools with plug connection = rectangular shaft with spring-loaded retaining pin. This creates a

657892 2-24	ensures that the insert tools fit firmly and securely in the torque wrench. Notice Please note the pitch of the insert tools and compare them with those of the adjustment tool (see Test report/operating instructions of the torque wrench used). If there is a deviation Make gauge correction!
495003 A	
Fp940155 Cs/K	
2423527	
2423550	
447110	
552200 (170)	
30 2 110 50 000/0	
A8pa	
2423407	
453800 150	
Ptdhw482424g	
434920 10	
Mi 2100	
A2-01812	
12423110	
630002 46	
Erc4u4843	
Ts120	
Bm 5004 6704740	
Ercfh3u	
Star 021/51	
568732 / 568731	
Pns20810	
568730 / 568731	
6513060	
2423526	
174025 27x0,9	
Emv-B/4,5 24v	
A-10pa	
2423547	
A1412nfss	
20 00040 00040m	
966110	

552500 (8)
W 3900005
478100 32
090/54
2423419
12423422
12423532
6511942
432000 10/58
Type 071/53
N 5965
Fp940255 Cs/K
Monty 3300-24 2
(59381) 491515 175 Halex
568731 (152x25x25)
981370
Bm0015
Dvu-100/32/0,4
A6axfn (4593595)
Hk500
Erc3u4837
30210020594135
478100 20
Ercfp4u48
079202 7739
2423412
3021001254105
74-41510070
2423542
C-C58sj
Ercfp3u48
079710 P2505
88-Lsgqr
12421421
66-Lsgqr

086120-8 / 8 X 50mm
457100_300
39d647/21
12423406
6510941
12423436
Vml 16 Handtufting
2423539
Ercfh4u
2423548
2423533
085480 5
A-Spbg
Diaphragm For M803213c