



Hp Teknik

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Hp Teknik Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Hp Teknik Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Drv 18 El For Light Oil 2 - 18 Bar	Pressure regulator valve m. Plunger u. Roll ^ Connection G 3/8 " Material: GGG 40 Flow range: 300 - 600 l / h Pressure level: 2 adjustable: 2 - 18 bar V.no. : # HS Code: 84811019 Origin: CE (DE) Net weight (kg): 1,500
Drv 18 El For Light Oil 6 - 25 Bar	DRV 18 EL for light oil Pressure regulator valve m. Plunger u. Roll ^ Connection G 3/8 " Material: GGG 40 Flow range: 300 - 600 l / h Pressure level: 3 adjustable: 6 - 25 bar V.no. : # HS Code: 84811019 Origin: CE (DE) Net weight (kg): 1,500
B-GHG-E/4	h p - Overflow valve threaded version Connection G 1 " Material: GGG 40 DIN tested: DIN 12514-2 Flow range: 300 - 6000 l / h Pressure level: 4 adjustable:: 15 - 40 bar V. no. : # HS Code: 84811019 Origin: CE (DE)
SMG 1552-I-2-10-H1	h p - motor pump group with industrial pump series VB and overflow valve tested according to: DIN / EN 12514-1 Pump type: VBHG M-I-2-10-H1 Flow rate: 4500 l / h Pressure level: 2 bar adjustable: 2 - 9 bar Medium: # Three-phase standard motor: B3 / B14 Motor power: 2.2 KW Speed: 1400 min-1 Voltage: 230 V / 400 V Frequency: 50 Hz Degree of protection: IP 55 Efficiency class: IE3 HS Code: 84136020 Origin: CE (DE)
MMG 1847-I-2-90-BH1	motor pump group with industrial pump Series VB Type : VBGG-I-2-90-m-BH1 Flow rate : 400 l/h Pressure level: 2 adjustable : 2 - 9 bar with magnetic clutch: for pinion 38 Media : # Standard three-phase motor : B35 Motor power : 0.37 kW Voltage : 230/400 V Frequency : 50Hz P. no. : # F. no. : # M. no. : # Type :
Oil,Pump,Exproof,2000L/hr,070H1063,Clayt	OIL PUMP CAPACITY:2000 L/HR ROTATION:CLOCKWISE REFERENCE NO:070H1063 MODEL:KSN2000 R MANUFACTURER:HP TECHNIK Please find the label attached!
NVBHRM-D-4-15-BH1	4120041 hp - industrial pump Flow rate : 1000 l/h Pressure level: 4 adjustable : 15 - 40 bar at speed : 1400 min-1

FDR 25-E/2	2270003 h p - relief valve flange design Flange DN 25, PN 40 Material : GGG 40 DIN tested: DIN 12514-2 Flow range : 300 - 6000 l/h Pressure level: 2 adjustable : 2 - 9 bar
BIK 5211-FL	0520396 h p - double unit series BIK flanged version with integrated overflow valve 2 x pump type : VBHGRP-I-4-10 Flow rate : 2200 l/h Pressure level: 4 adjustable : 15 - 30 bar Connections : DN 32 Media : # Three-phase standard motor: B3 / B14 Engine power: 4.0 KW Speed : 1400 min-1 Voltage : 400/690 V Frequency : 50Hz Degree of protection: IP 55 Efficiency class : IE3 2 x filters : DN 32 Filter insert : 100µm Oil pan : 800x700x80mm Vacuum gauge : -1..+5 bar Pressure gauge : 0 - 40 bar P. no. : # F. no. : # M. no. : # Type : #
SMG 1631 VBHGRP	2200 lt /h 30 bar 4kw 1400 rpm
B-GHG-E/4	4210005 Connection G 1" Material : GGG 40 DIN tested: DIN 12514-2 Flow range : 300 - 6000 l/h Pressure level: 4 adjustable: : 15 - 40 bar
A X - Piston B-GHG 1"	900-6000 l/h
4380047	hp - Motor pump group SMG 1868-I-4-90 with industrial pump series VB Pump type : VBHP-I-4-90 Flow rate : 470 l/h Pressure level: 4 adjustable : 15 - 30 bar Media : # Three-phase standard motor: B3 / B14 Motor power : 1.5 kW Speed : 950 min-1 Voltage : 230/400 V Frequency : 50Hz Degree of protection : IP 55 Efficiency class : IE
3210005	hp overflow valve threaded version B-GHG-E/3-AX with heavy oil pistons connection G 1" Material: GGG 40 DIN tested: DIN 12514-2 Flow range: 300 - 6000 l/h Pressure level: 3 adjustable: : 6 - 25 bar
B - Gh - E / 4 - V101532	
Uhe-A5-Gz-I-4-20	h p - I n d ustriepumpe Flow rate: 1050 l / h at 40 bar Pressure level: 4 adjustable: 15 - 40 bar at speed: 2800 min-1 P.-Nr. : # HS code: 84136020 Origin: CE (DE) Net weight (kg): 5.186
4110035	
L67776	