

Hp Valves

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Hp Valves Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Hp Valves Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
GATE DN50 CL2700 F91	
GATE DN25 CL2700 F91	
GLOBE DN80 PN160	
DN40 CL2700 BLOWOFF	
SHP1 Outlet Drain Isolation Valve (HAH70AA451)	SHP1 Outlet Drain Inching Valve (HAH70AA452) As a valve type, globe valve type (current type) or ball valve can be considered. Even the fluid used is vapor phase. The design pressures of the existing valves can be exceeded by 204.5 bar, and the design temperatures are 449.4 degrees, and can be exceeded even more. The material can also be SA182 F92 or F91. It should be welded. The data we receive as operating data is; 427.12 degrees working temperature and 170.11 bar working pressure.
SHP4 Inlet Drain Isolation Valve	SHP4 Inlet Drain Inching Valve (HAH72AA452) As a valve type, globe valve type (current type) or ball valve can be considered. Even the fluid used is vapor phase. The design pressures of the existing valves can be increased to 204.5 bar and even higher, and the design temperatures are 581.5

[\(HAH72AA451\)](#)

degrees and even higher. The material can also be SA182 F92 or F91. It should be welded. The data we receive as operating data is; 554 degrees working temperature and 177 bar working pressure.

[Item 101](#)

[A105n,Cl1500,Dn50](#)

[Mv 11 Lae50aa080](#)

[Asme B16.34 En 12516](#)

[Dwg/N 2s10855](#)

[1.500/2.500lbs.](#)

[40-50hah44aa002](#)

[96+726+11](#)