



Hsb Automation

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Hsb Automation Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiřime ge¼iniz.

Firmamız Hsb Automation T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
110-OSS	
140-C-ZSS	
50-C-ZRS-20AT5-E-110-2010-2300-AK-AZ2-GX -8BL1-1	
80-SOS-M-2550-2296-2720-4SA-1	
Beta 110-OSS-9960-10650-AK-32BL-1	
Beta 50-C-ZRS-20AT5-E-110-2010-2300-AK-AZ2-S -8BL1-1	
Beta 80-SGV-M-2525-1490-1930-2SA -8BL2-1	
Beta 80-SSS-M-2005-250-630-2EO2 -4BL2-0	
Beta-140-C-Z.. M6BZ-Z90-TK108-RD120-d32x70-M8-90G-140-1	

[BETA180-ZSS-50AT10E-180-2830-3498-AK-AZ](#)

[BETA80-ZSS-32AT5](#)

[SN 38550](#)

[URT2-4BS-Z80.0-TK100.00-VK88.0-d14.00x30.00-D7-45G-i=1.0 \(Beta 60-S\)](#)

[Beta 80-SSS-M-2005-150-530](#)

-2EO2-4BL2-0 with Star rail guide S20 with ball screw and single nut 2005 max. travel: 150mm, total length: 530mm with standard carriage L=210mm Lubrication side: C+D, grease nipple design: funnel with masking tape: blue Wiper: felt + sheet metal 1.Limit switch: EO2, side C, pos. A, cable A - Adjustment range: 10mm 2.Limit switch: EO2, side C, pos. B, cable A - Adjustment range: 10mm Permissible spindle speed: 3000 1/min Permissible drive torque: 4.0 Nm rotate. Moment of inertia JR=0.000049 Kgm² (with slide) the total sled mass is: 1.90 kg with the following attached accessories: - Coupling, mounting side: fixed bearing side - Motor/gear bell, mounting side: fixed bearing side see the following position(s) Engine/gearbox bell MGK (Bgr.) Type: Beta-80-S.. M5BS-Z110-TK130-VK116-d24x50-D9-45G-109-3 with Rotex coupling: - Rotex GS 24 98 ShA-GS2.6-d16H7/6.0-d24H7 - Clutch nominal torque: 60.0 Nm - Clutch maximum torque: 120.0 Nm for attachment to SEW CMPZ71S

[Compact linear unit](#)

Delta 145-C-ZSS-60AT5-E-150-1540-1930-AK-AZ2-S -2EO10-8BL2-1 Replacement for serial no.: 102840 / AB 51181/110 Customer part no.: 3843.CA2.215 with Star rail guide S20 and toothed belt drive 60AT5-E, 150 mm/rev max. travel: 1540 mm, total length: 1930 mm with standard slide L=180 mm total height H=88mm side lubrication: C+D, design grease nipple: funnel with cover tape: blue scraper: felt + sheet metal (sheet metal/felt/sheet metal) drive shaft connection: key 1st limit switch: EO10, side C, item A, cable A 2.Limit switch: EO10, side C, item B, cable A with limit switch bar(s) side C Timing belt pre-tension: 1260N corresponds to 170Hz with a measuring length of 200mm or a pre-tension path of 4.5mm Mass moment of inertia JR=0.00318020Kgm² (with carriage) The total carriage mass is: 4.50 kg permissible drive torque: 50.7 Nm 1 = special version: special version/wet room with special drive shaft A AZ2-S, d18x162lg.without keyway special processing profile: - 1. sealing air connection G1/8 connection side C, item A at 50mm - 2. sealing air connection G1/8 connection side C, item B at 50mm !!! Screw-in depth of sealing air connection max. 4mm !!! Special lubrication, grease nipple: funnel with lubrication attachment with 4x attachment lubrication system size 20 rust-free components: - external/visible parts rust-free - drive shaft rust-free (all steel parts outside made of VA) - all open synchronous bearing points mech. closed with vernier version, enclosed loose, (ID no. 26449 / 26455) with fastening thread for energy chain holder;

Beta 100-D-ASS-40AT10-E-240-300-770-AZ2-S -2EMB-1 Customer part number: 3843.CA3.794 Replacement for serial number: 102839 / AB 51181/70 with Star rail guide S15 and

[Mechanical linear unit](#)

toothed belt drive 40AT10-E, 240 mm/rev max. travel: 300 mm, total length: 770 mm with standard slide L=260 mm
Lubrication side: C+D, grease nipple design: funnel Drive shaft connection: key 1st limit switch: EMB, side C, item A, cable - adjustment range: 10 mm 2nd limit switch: EMB, side C, item B, cable - adjustment range: 10 mm Toothed belt pre-tension: 1688N corresponds to 175Hz with a measuring length of 200mm or a preload path of 0.8mm Mass moment of inertia JR=0.01483172Kgm² (with slide) The total carriage mass is: 8.60 kg permissible drive torque: 86.5 Nm 1 = special version: special version/damp room mounting of mechanical limit switch side C with special drive shaft A AZ2-S, d20x131.5lg.without keyway special processing profile: - 1. sealing air connection G1/8 connection side D, Pos. A at 30.00mm - with special drilling pattern - 4 positioning fitting holes d12H7x3 deep, on side E at B slot nut(s)/strip(s) in special version 2xNL140, 30/2x40/30, 3x thread M8, material VA special lubrication, grease nipple: funnel with lubrication attachment (4x attachment lubrication systems size 15) rust-proof components: - External/visible parts rust-proof - drive shaft rust-proof - all open synchronous bearings mechanically closed with vernier version, enclosed loose, (ID no. 26449 / 26455)

[Beta80-Sos-M2550-2100-2720-45sa-1](#)

[80-Sos-M-2250-834-1200-2sa-1](#)

[54138](#)

[180-Sss-M-2505-600-1012-2eo2-1es2-4ns6-1](#)

[180-Sss-M-2505-600-1012-2eno](#)
[Obsolete Replaced By 180-Sss-M-2505-600-1012-2eo2-1es2-4ns6-1](#)

[Beta80-Sos-M-2550-1600-2215-4sa-1](#)

[Beta 80-Ss-M-2020-300-680-8ns3-1](#)

[Beta-80sos-M-2550-1600-2115-4sa-1](#)

[Beta100-D-Sss](#)

[Beta180-Zss-50at10e-180-3500-4168-Ak-Az6-1](#)

[Kgm 2550](#)

[115204](#)

[80-Sos-M-2250-2296-2720-4sa-1](#)

[Beta 50-C-Zrs-20at5-E-110-2360-2650-Ak-Az2-10bl-0](#)

[Beta-80-Sos-M-2550-2100-2720-4sa-1](#)

[54137](#)

[80-Sos-M-2250-1494-1860-2sa-1](#)