



## Hydrokomp

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Hydrokomp** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Hydrokomp T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">KMP-5-03-014</a>	Coupling mechanism plate, 3-fold for compressed air max. 20 bar NW 5, can be coupled without pressure, O-ring flange connection Positioning tolerance to the counterpart: radial +/- 0.2 mm, axial +0.5 mm Fastening screws, cylindrical pin u. O-rings included. Customs tariff number 84122120
<a href="#">KNP-5-03-007</a>	Coupling nipple plate, 3-fold for compressed air max. 20 bar NW 5, can be coupled without pressure, O-ring flange connection Positioning tolerance to the counterpart: radial +/- 0.2 mm, axial +0.5 mm Fastening screws, cylindrical pins u. O-rings included. Installation dimensions according to E-KMP-5-03-007 Customs tariff number 84812010
<a href="#">KN-460-5-S007k</a>	Coupling nipple, UD, hardened pmax = 300 bar, NW 5, Installation element, short, under pressure detachable Coupling elements must be approx. 2-3 mm before touching the sealing surfaces within the positioning tolerance be guided. Positioning tolerance: radial +/- 0.2 mm, axial + 0.5 mm Installation dimensions according to Data sheet 3-100 Housing plasma nitrided. Customs tariff number 84812010
	I need price and delivery on (2) KN-160-5-S001K Fittings,

<a href="#">KN-160-5-S001K</a>	that mate with to a KM-460-5-N001 port. I need the part number verified and the dimensions of the fitting. Thank you.
<a href="#">Hydrokomp</a>	
<a href="#">Hydrokomp</a>	
<a href="#">Hydrokomp</a>	
<a href="#">Hydrokomp</a>	
<a href="#">KN-460-5-EG002</a>	Coupling nipple, M24x1.5 ,UD pmax = 400 bar, NW 5, Screw-in element, under pressure detachable Installation dimensions according to drawing E-KN-460-5-EG002 External thread M24x1.5
<a href="#">6011-001-N001</a>	
<a href="#">Kn-460-5-Eg_003</a>	
<a href="#">Kmp-460-5-K015</a>	
<a href="#">Ase-016-08-03-001</a>	
<a href="#">Ab03006/1-B-Nr-160003</a>	
<a href="#">Kmp-460-5-K013</a>	
<a href="#">Km-460-5-Eg_008</a>	
<a href="#">Kn-460-5-Eg001</a>	Coupling nipple, M28x1, AND pmax = 350 bar, NW 5 Insertion element, under pressure coupled Installation dimensions according to drawing E-KN-460-5-EG001 or catalog sheet 3-100 Customs tariff number 84812010
<a href="#">Kmp5-Ko_52</a>	
<a href="#">Kmp-460-5-K004</a>	
<a href="#">Km-460-5-N001</a>	
<a href="#">Kds-5-06-002</a>	
<a href="#">Duhh-70-5-002</a>	
<a href="#">Dhsp-Dhs-020-001</a>	
<a href="#">Kn-460-5-S001l</a>	
<a href="#">Kn-460-5-Eg002</a>	
<a href="#">Kn-460-5-S001k</a>	
<a href="#">Kmp-460-5-K-024</a>	