

Igema

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Igema Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Igema T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Typ Af410	Indicator valve type AF410 to the remote display Datasheet: D-09-D-16362-0 PS = 180 bar, TS = 5 to 40 ° C Material: stainless steel Process connection: Welding nipple Ø 17.2 x 2.3 mm
Elektrode Typ EI60	Electrode type EL60 for Sensor type PE1- / PE2 permissible pressure 210 bar, permissible temperature 370 ° C
10016	
10205	
11121 + 15-13050	
14326	
14356	
14696	
14833	
15-00113	

15-00114	
15-00115	
15-04090	
15-04308	
15-06233	
15-06366	
15-10970	
15-13065	
15-13069	
15-13070	
15-13073	
15-13088	
15-15036	
15-7400065	
20-00011	
20-00156	
20-10020	
40-00042	
40-00117	
40-00200	
70-00002	
70-00005 (Beleuchtungseinrichtung fur den Zwerfarbenanzeiger)	
70-00007	
A120-CS	
D-07-D-16324-1	
KAV1 R1-N	
40-00989	Mica package Ø 42x0.8 mm PN250-320
MODEL: EL23, TS:298C / 80BAR, DN: 6 ½	
	data sheet: D-03-D-38755-DE-00 size: 5/8-2, left-hand model PS = 73 bar, TS = 288 °C center distance A = 620 mm

transparent level gauge glass mica TG120	sight length EN = 0 mm, E = 470 mm measure H = 75.0 mm, J = 75.0 mm 0 x dead space 0 mm, 1 x overlap 25 mm lwl-mark: yes shut off valve type A180, barrier single with handlever with self-closing ball for automatic shut off quick closing spindle: yes data sheet: D-09-D-16356-1 process connection: flange, nominal size: PN160 DN25 to DIN EN 1092-1 drain valve type: AV250 end of drain valve type: cutting ring connection Ø 12 mm nach DIN 2353 data sheet: D-09-D-34162-EN-01 norm: DIN mounØng- and operaØng instrucØons: D-03-B 38755-0 Illumination device LEDSecure Slim Size 5 for E = 200 mm data sheet: D-A1-D-51865-EN-02 Illumination device LEDSecure Slim Size 8 for E = 300 mm data sheet: D-A1-D-51865-EN-02 mounting bracket for LEDSecure Slim for TG32/TG120
15-11035	Measuring probe EC8, capacitive Data sheet: D-08-D-50949-DE-01 PS = 32 bar, TS = 239 °C Dimension Y =1500 mm Process connection: external thread G 1/2" Standard: DIN Operating instructions D-08-B-51050-DE-01
20-10020	Continuous level transmitter DLT2 Data sheet: D-08-D-51253-DEOperating data 230Vac, 50 Hz Protection class IP 40 Current interface 4 – 20 mA
20-10027	Conductivity controller FARB2 with limiter function Mains connection: 110-240 V +10/-15% 50-60Hz Power consumption: approx. 4.5 VA Protection class: IP40 Electrical conductivity of the liquid: 0.5 µS/cm - 10,000 µS/cm Data sheet: D-08-D-50096-DE-0 Operating instructions: D-08-B-50032-DE-0
15-00858	Conductivity electrode type EL22, Data sheet D-08-D-50372-DE-02, PS = 32 bar, TS = 239 °C, Protection class IP 65, connection G 1/2, Dimension Y= see below Y=500mm
15-13073 Die Gimmerplatte	
40-00006	
?220 Schnell Wirkendes Absperrventil Eckform	
24x400x10x380x0,5 Mm	
40-00136	
40-00099	
Igema-70-00005-Beleuchtungseinrichtung-F3;R-Den-Zwefarbanzeiger-Istanbul-Turkiye	
15-06360 (Datenblatt: D-A1-D-18931-0)	
40-00989 Satz Von Glimmer Platten	
Dlr1	
Ersatzteile-Set Zum Ventil	

15-15835
40-00053
40-04463
- Die Kugel
40-00079
D-03-D-07395-0 (3-Af 910 03/04) Zylinder Glas
9-V 510-Gb O-Ring
Smlc1 Limiter Levelsmlc1
15-00115 Sockel
?220 Schnell Wirkendes Absperrventil Eckform
15-00114 Kegelgarnitur Und Sitz A120, A200-240 Material: Niro
15-01122
40-00010 Din7081 Klarglas Pos. 9
Flb1 Begrenzer
Dir1 Controller-Level
4-Eaf 110-R
042014 Obsolete, No Replacement
Gasket / Glass / Shield Assembly; For Local Level Display; Igema; Tp: Igema 15-13070
40-00988
40-00205 Dichtung
20-00110
20-00034
4-Eaf 110-R Paket Glimmer
40-00155 Ring Graphit
40-00042 Borosilikatglas
Dir1 Level-Regler Igema
40-00117 Dichtung
15-13070 Joint Gasket / Glass / Shield

For Local Level Display	
20-00006	
Typ El23	Conductivity electrode type EL23, PS 80 bar, TS 296 ° C, Protection class IP 65, connection G 1/2, with electrode mounting flange DN 50, PN160 according to DIN and Electrode housing, but without screws, nuts and flange sealing ring, Dimension Y = 500 mm, Component number TÜV ID. 0000006175 Data Sheet D-08-D-16345-0, Operating Instructions 8-BAS 513
20-00116	
Typ El21-2	Level electrode type EL21-2, Data sheet D-08-D-16331-0, PS 200 bar, TS 367 ° C Degree of protection IP65, connection G1 / 2, Conductivity 0.5 - 2,000 µS / cm, Certificate No .: TÜV ID: see controller Dimension Y = 1,000 mm Operating instructions D-08-B-16645-0
40-00979	
Reflex Level Gauge Lg40	
A2t-160,D-03-D09875-1	
40-00205 Schutz	
0920000060019 Niveauschalter Igema Dri 20-00006	
40-00988 Glimmer	
Ds1 Level-Regler	
40-00283	
Die Kugel Pos. 12	
15-7400065 Magnetgesteuerter Grenzschalter M740065	
20-00007	
Dri 20-00006 Niveauschalter Serial 0920000060019	
Lg40	
Kav1 R1-N	
10178	
40-00077	
40-01845	
20-00101	
Skqws Relais	

400x24x1 Mm
40-00136 Dichtung
40-00042 Klarglas
40-00420
Kav2 R1-N
Reflex Level Gauge Lg40-X2
40-00205
20-00109
15-06233 Reedkette Typ Mrk110-S
15-00318
10177
15-00790
40-01536
Tds Flb1 Begrenzer
20-00035
15-00115 Sockel Pos. 2
40-00283 Dichtung
Set Verschluss Ohne Achsen Pos. 13
D-07-D-16324-1 Magnetsperrschalter M130-Kganschlusskabel: Ptfe 200 Mm
15-00113 Packungsgarnitur A110-150 A200-220material: Stahl / Graphit
40-00136 O-Ring
40-00117 O-Ring
40-01803
15-00114 Sockel Pos. 2
20-00015
15-13085
M130-Kg (15-01122)
13574
EI19-2

40-00979 Glimmer-Platten
70-00005
M130-Kg
Ds1 Controller-Level
40-00042 Borsilikatglas
20-00102
20-00-102 Limiter Level Smlc1
15-11604
Art.No. 15-01122 Model M130-Kg Magnetic Switch
Ds1 Regler Wasserstand
Smlc1
M130-Ks Replaced By M130-Kg
043031 Obsolete, No Replacement
4-Eaf 110-R O-Ring
Lg40 Water Level Reflector, Ps 32bar, Ts 239 0c, For Steam Boiler, Flanges Dn20
Dichtung Lg40,7 40-00088
Lg40 Water Level Reflector, Ps 32bar, Ts 239 0c, For Steam Boiler, Flanges Dn25
70-00005 (D-04-D-19466-1)
40-00957
15-01122 Magnetsperschalter M130- Kgtypenblatt: D-07-D-16324- 1anschlusskabel: Ptfe 200 Mm
40-00155
EI913
40-00155 Schutzdichtung
Ts 239 0c Lg40 Wasserstandsanzeigeps 32 Bardn20
15-13062
Dichtungposition 4, Im 11 12had10&Mpb103-

00 Transparentanzeiger
40-00081
D-03-D-09871-0
10237
Ts 239 0c Reflex Wasserstandsanzeige Lg40 Ps 32 Bardn25
40-00207 Wellendichtung
M130-Kgd-07-D-16324-1 Schalter
15-00115 Kegelnarnitur ,Sitz Und Kugel A200-240 Material: Niro
40-00010
40-00109
Dhr1
12-202525-2-1 Lg40 Ps 32 Bar Ts 239 C Dn 25
M130-Kgd-07-D-16324-1
Relais Igema Skgwsj
20-00014
70-00005 (D-04-D-16289-1)
15-00177
4-Eaf 110-R Glas