

Innovatek

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Innovatek Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Innovatek T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
501812	Cartridge for particle filter type F20 - 100 µm
801074	Cooling system type D24 direct cooling system 24V 0.35bar (PES tank) Compact cooling system 24V= (24V 0.5A) with PES tank Cooling capacity: 850W (at Delta T 38K / 22°C environment to 60°C water) Thermal resistance of the system ~ 0.045 K/W Pump max. 0.35 bar 5l/min Level monitoring with signal output and visual display Tank volume approx. 1.2 liters Hydraulic connection: CPC NS2 couplings (female) Volume approx. 39 db(A) Size: approx. 290x235x240mm (lxwxh) Weight (ready for use) approx. 8.8kg Scope of delivery: cooling system, manual DE WITHOUT accessories, WITHOUT power plug Requires electrical: Connector (cable socket/socket) Hirschmann CA series Rated current: 10 A/AC/DC Poles: 6 + PE - e.g. innovatek Item number: 801195 Alternatively: 501826 power supply 24VDC/2.71A C14 on socket 6+PE with on/off switch Requires hydraulic: 2x CPC NS2 plug (male) e.g. innovatek Item number: 501718 CPC-NS2 plug (m) (inline) grommet SØ6.4 for hose 8x1)
	Cooling system D24-2 direct cooling system 24V 0.35bar (2.5

[501913](#)

liter tank) Compact cooling system 24VDC (30W) 2.5l tank volume (approx.) Pump 350 mbar 4l/min Supply air filter 8x M8 mounting points Warning level with potential-free switching output Error detector with potential-free switching output Cooling capacity: 850W (at Delta T 38K / 22°C environment to 60°C water) Thermal resistance of the system ~ 0.045 K/W Hydraulic connection: CPC NS2 couplings (female) Volume approx. 39 db(A) Size: approx. 290x235x280mm (lxwxh) Weight (ready for use) approx. 8kg Scope of delivery: cooling system, manual DE WITHOUT accessories, WITHOUT power plug Requires electrical: Connector (cable socket/socket) Hirschmann CA series Rated current: 10 A/AC/DC Poles: 6 + PE - e.g. innovatek Item number: 801195 Alternatively: 501826 power supply 24VDC/2.71A C14 on socket 6+PE with on/off switch Requires hydraulic: 2x CPC NS2 plug (male) e.g. innovatek Item number: 501718 CPC-NS2 plug (m) (inline) grommet SØ6.4 for hose 8x1)