

Intorq



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Intorq Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Intorq Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Intorq Bfk458-10	Magnet part complete INTORQ BFK458-10 Material nr : 00521307 Size 10 Type E, with adjusting ring Nominal voltage 180 V. Rated power 32 W. Cable length 400 mm Characteristic torque 16 Nm Armature disk nitrided Nomenclature number 85059029 Country of origin DE (Germany) Weight / unit 2.510 KG
Intorq 14.105.06.10	Complete rotor Type INTORQ 14.105.06.10 Bore diameter 14 mm Bore tolerance H7 according to DIN 6885/1-P9 Nomenclature number 85059090 Country of origin DE (Germany) Weight / unit 0.210 KG
53100478 Intorq Bfk457-06 Compact 190v	art nr. 13320929 Spring-applied brake Type INTORQ BFK457-06 Compact Nominal voltage 190 V. Rated power 20 W. Cable length 600 mm Characteristic torque 6.8 Nm Armature disk noise-dampened Aluminum rotor Version silenced Flange mounted Customer designation 53100478 Weight / unit 1.155 KG
Bfk464-25s	
14.105	
14.115	
BEG-561-255-030	13053794 Electronic brake rectifier Type BEG-561-255-030 Bridge / half-wave rectifier version 6-pin connection Lying design Max. Connection voltage 255 V AC
BFK458-12N 103V 32NM	Magnet part KPL BFK458-12N 103V 32NM Size 12 Type N, without setting ring Nominal voltage 103 V Rated power 40 W. Cable length 400 mm Characteristic torque 32 Nm Armature disk nitrided Intermediate pane yes Hand release installed as standard Lever length 74 mm Nomenclature number 85059029 Country of origin DE (Germany) Weight / unit 3.700 KG
	Magnetic part Size 12 Type N, without setting ring Nominal voltage 205 V Rated power 40 W Cable length 400 mm

KPL BFK458-12N 205V 32NM	Characteristic torque 32 Nm Armature disk nitrided Nomenclature number 85059029 Country of origin DE (Germany) Weight / unit 3,900 KG
INTORQ BFK457-04 Compact	Nominal voltage 24 V. Rated power 11.5 W. Cable length 400 mm Characteristic torque 2 Nm Rotor plastic Flange mounted
BEG-261-460	
BFK458-06E	Size 06 Tooth addition, noise-dampened Material aluminum Low-wear friction lining material
BFK458-10N	
14.800.06.11.1 24V DC	
(00519524) BFK458-08	
00011294	
00011298	
00024105	
00032898	
00034593	
00035877	
00035879	
00036823	
00045801	
00076264	
00103904	
0011295	
00120592	
00181062	
00376078	
00396186	
00396200 (BFK458)	
00396202	Rotor complete Type INTORQ BFK458 Size 10 Material aluminium Friction material standard
00396252	
00396280	
00397383	

00397683	
00398426	
00399507	set of screws Designation cylinder screw Allen drive Dimensions M6x55 Material 8.8 Surface A2F Pack size 3 pieces
00399517	
00405194	
00405202	
00406946	
00410929	
00423189	
00426428	INTORQ BFK458-18
00480964	
00519500	
00519501	
00519522	(BFK458-08)
00520174	
00520177	
00520178	
00521306	
00521371	
00521423	
00521427	
00540074	
00566272	
00575536	
045801	
11295	
11296	
11299	
13018257	

13046388
13046434
13053794
13053795
13059769
13062307
13169183
13208995
13328214
14.105.06
14.105.06.10(00032840)
14.115.20.10
14.198.00.04
14.800.06.12.3 24V 11,5W 7,5NM 14MM K6 NACH DIN 748/3 160MM
14.800.10.11.1 (00109039)
14.800.10.20.3
14.800.12.10.1
1480006103
15001038
15060939
15191617
155-1 E318895
32893
33001328
34419
35000294
35877
376077
396186
396200

396202
397383
397398
397514
397683
398361
399507
401282
423189
480967
50000039
50000039 BFK458-06
50000039 BFK458-08/10
50000039 BFK458-16
519518
520182
520874
520880
5PK457-08
60 NM BFK 458-14 E
76260
96186
BEG-142-270
BEG-162-270
BEG473270 (not a valid)
BEG-561-250-130
BFK 457-08
BFK 458-16E,NR.13018637 .
BFK 460 - 18
BFK452-20
BFK457-08 (13222795) Basic

BFK458	
BFK458 - 08, 24V 25W	
BFK458 - 10, 24V 30W	
BFK458 (00011299)	
BFK458 (00396214)	
BFK458 (15061328)	
BFK458 00396200	
BFK458 00397734	
BFK458 -14E 60 NM 110 VDC	
BFK458 20 00396280	
BFK458 SIZE 12	
BFK458 SIZE 12E	
BFK458/Nabe	
BFK458-06	
BFK458-06 (00519501)	
BFK458-06 (0396186)	
BFK458-06E (519508)	
BFK458-06E 00460697	
No.: 010195	Magnetic part for BFK458-06N 205VDC Manufacturer: Intorq / Kendrion Size: 06 Design: N-without adjustment ring Coil voltage 205 VDC Rated power: 20W Cable length: 400mm Rated torque: 4Nm Armature disk: nitrided
BFK458-06N 24V 20W	
BFK458-08	
BFK458-08/10 50000039	
BFK458-10	
BFK458-10 32W 180V DC	
BFK458-12 00520884	
BFK458-14	
BFK458-14 00521375	
BFK458-14 50000039	
BFK458-16 E 205 V, 56 W	

BFK458-16E 103V 80Nm	
BFK458-16E 103V 80Nm 35MM Bore	
BFK458-18	
Magnetic part for BFK458-20E 180VDC (So)	Part Nr: 011364 Size 20 Design E-with adjustment ring Coil voltage 180 VDC Rated power 100W Cable length 800mm (special length) Rated torque 80 - 260 Nm Galvanized anchor plate NOTE***: Compared to the standard magnetic part, the requested product has an extended cable (800mm instead of 600mm).
BFK458-25 (00521385)	
BFK458-25E	
bfk458-80e	
BFK466-55	
BFK468-31N	
BKF457-03	
BKF457-04	
BKF458-06N	
BKF458-12E	
BRB-238-000-M000200-000	
BUSH FOR INTORQ BFK457-03	
BUSH FOR INTORQ BFK457-04	
DOPPELFEDERKRAFTBREMSE INTORQ BFK458-25N	
FBGR-E400/175-GS	
Hub BFK458-16	
INTORQ BFK458/00399516	
INTORQ BFK458-06	
INTORQ BFK458-16E	
INTORQQ BFK457-08	
KBK 14.800.06.12.4	
L260GH	
L400GH	
LENC0152	

LENCS0292	
LENCS0627	
Nabe BFK458	
Nabe BFK458-16	
SEW 826 763 4	
Typ 14.115.10.10 Nr. 00032882	
BFK458-10E 180V 16NM	Magnet part KPL BFK458-10E 180V 16NM country of origin Germany Statistical goods number 85059029
00423191	Rotor complete Type INTORQ BFK458 Size 10 Material aluminium Low-wear friction lining material
00024043	Hub type INTORQ BFK458 Size 08/10 Bore diameter 10 mm Tolerance class J7 Keyway standard without keyway Hub length 20 mm External teeth db x m x z W35X1.25X26
00076260	friction plate Type INTORQ BFK458 Size 10 Electrolyte surface coating. galvanized
Shaft Ø : 20 mm	The brake coil connection has three holes and the hole spacing is 114 mm.
BFK458-08E 00519521 8NM	
BFK458-08E	pos.3
010209	Magnetic part for BFK458-16E 205VDC Manufacturer Intorq / Kendrion Size: 16 Design: E-with adjustment ring Coil voltage 205 VDC Rated power: 56W Cable length: 600mm Rated torque: 80Nm Galvanized anchor plate Country of origin: DE stat. Commodity number: 85059020 Weight: 8.60kg
010215	Rotor for Intorq BFK458-16 (standard) Manufacturer Intorq / Kendrion Size: 16 Support material: aluminum Friction lining: standard stat. goods no. 85059090 Country of origin: DE-Germany Weight: 0.44kg Item no.: (without item no.) We offer you the following hub as an example. Standard diameters are 25 / 30 / 35 / 38 mm H7 Please specify this dimension.
010786	Hub for BFK458-16, 30mm Manufacturer Intorq / Kendrion Bore diameter: 30mm Tolerance class: H7 Groove according to standard: DIN6885/3 Hub length: 30mm Outside toothing: W55 x m2.00 x z 26 Statistical goods number 85059090 Country of origin: DK-Denmark Weight per piece: 0.3 kg
BFK457-08	4011221 compact 24VDC spring-loaded brake Manufacturer: Intorq / Kendrion Material no. of the manufacturer 00451815 Type BFK457-08 Nominal voltage 24 V Rated power 28.0 W Cable length 130mm Rated torque 16.00 Nm Aluminum rotor Hub bore 15,000mm Tolerance / design H7 according to DIN 6885/1-P9 Flange mounted Special features with AMP connector Special signature BT 210462 Version special

	friction lining
14.800.08.11.1	072925 KBK 14mm 14mm clutch-brake combination Manufacturer: Intorq/Kendrion Type 14.800.08.11.1 Output side brake Nominal voltage 24 V Power at 20°C 16.0 W Rated torque 15.00 Nm Shaft diameter 14.00mm Shaft tolerance K6 according to DIN 748/3 Drive side clutch Nominal voltage 24 V Power at 20°C 20.0 W Rated torque 15.00 Nm Shaft diameter 14.00mm Shaft tolerance K6 according to DIN 748/3 Foot height 71.00 mm Maximum speed 3,000 rpm Terminal box position 1
BFK458-14E	
BFK 458-08N	
Spring-applied brake BFK458-16E	Article no.: 011242 Manufacturer Intorq / Kendrion Rated torque 100Nm Magnetic part adjustable Rated voltage 205VDC Rated power 56.0 W Cable length 600mm Aluminum rotor Screw set M8X80 included Customer designation AH 132/2LM8 Siemens engine
Hub for BFK458-16	Manufacturer Intorq / Kendrion Bore diameter: 25 / 30 / 35 / 38 mm optionally Please specify!! Tolerance class: H7 Groove according to standard: DIN6885/3 Hub length: 30mm Outside toothing: W55 x m2.00 x z 26
Magnetic part BFK458-10E 24VDC (increased torque)	Manufacturer: Intorq / Kendrion Size: 10 Design: E-Adjustable Coil voltage 24 VDC Rated power: 30W Cable length: 400mm Rated torque: 20Nm Anchor disk nitrided
Rotor for Intorq BFK458-10 (standard)	Manufacturer: Intorq / Kendrion Size: 10 Support material: aluminum Friction Material: Standard
Hub for BFK458-08 and BFK458-10, Ø20mm	Manufacturer: Intorq / Kendrion Material no. i.e. Manufacturer: 00011295 Bore diameter: 20mm H7 Groove standard: according to DIN 6885/1-P9 Hub length: 20mm Serration: W35 x 1.25 x 26
Model No: BFL458-18N	85W, 250 VDC, 150 NM
Model No: BFK458-20N	100W, 180 VDC, 260 NM
011273	14.105.10.30 (magnetic part for clutch) Manufacturer INTORQ Type 14.105.10.30 Nominal voltage 24 V Power at 20°C 28 W Cable length 400mm Rated torque 30 Nm Commodity number 85059020 Country of origin DE (Germany) Weight / piece 1.1 kg
010582	Magnetic part for BFK458-12E 180VDC Manufacturer Intorq / Kendrion Size: 12 Design: E-adjustable Coil voltage 180 VDC Rated power: 40W Cable length: 400mm Rated torque: 32Nm Anchor disk nitrided stat. goods no. 85059020 Country of origin: DE-Germany Weight per piece: 7.8 kg
010524	Rotor for Intorq BFK458-12 ST Manufacturer Intorq / Kendrion Size: 12 Support material: aluminum Friction Material: Standard Statistical goods number: 85030099 Country of origin: DE-Germany Weight per piece: 0.26 kg

010518	Hub for BFK458-12, 25mm Manufacturer Intorq / Kendrion Bore diameter: 25mm Tolerance class: H7 Groove according to standard: DIN6885/1-P9 Statistical goods number 85059090 Country of origin: DK-Denmark Weight per piece: 0.35 kg
Magnnet part CPL BFK458-06E 205V 4.0Nm	00519508 Large size 06 Construction E, with setting ring Nominal voltage 205 V Rated performance 20 W Cable length 400 mm Identonary moment 4.0 nm Anchor disk nitrates
BFK458-08E-180VDC	Article no.: 010700 Manufacturer: Intorq / Kendrion Size: 08 Design: E-with adjustment ring Coil voltage 180VDC Rated power 25W Cable length: 400mm Rated torque: 8Nm Anchor disk nitrated Country of origin: DE
Rotor for Intorq BFK458-08	Article no.: 010558 Support material: aluminum Friction lining: standard
Hub for BFK458-08/10, Ø12mm<	Article no.: 010839 Manufacturer: Intorq / Kendrion Bore diameter: 12mmH7 Hub length: 20mm External teeth: W 35 x 1.25 x 26
BFK457-08	4011221
183540004	
bfk457-08 basic	
BEG-561-255-130	
BFK457-05 Compact	00475686 Rated Voltage 205V Rated power 13 W Cable length 400mm Rated torque 4 Nm Rotor plastic Flange mounted
BEG-561-440-130	Bridge/half-wave rectifier design 6-pin connection design lying Max. connection voltage 440 V AC Max. direct current 3.0 A / 1.5 A at 60°C Overexcitation time 1,300 ms
BEG-561-255-130	Bridge/half-wave rectifier design 6-pin connection design lying Max. connection voltage 255 V AC Max. direct current 3.0 A / 1.5 A at 60°C Overexcitation time 1,300 ms OEM part number 10167674
KPL BFK458-18N 24V 150NM	00520230 Size 18 Type N, without adjustment ring Nominal voltage 24 V Rated power 85 W Cable length 600mm Rated torque 150 Nm Rear holes in the housing Galvanized anchor plate
KPL BFK458-10N 24V 16NM	00520879 Size 10 Type N, without adjustment ring Nominal voltage 24 V Rated power 30 W Cable length 400mm Rated torque 16 Nm Anchor disk nitrated
KPL BFK458-12E 180V 32NM	00743258, Size 12 Type E, with adjustment ring Rated Voltage 180V Rated power 40 W Cable length 500mm Rated torque 32 Nm Anchor disk nitrated
00520879	Magnetic part KPL BFK458-10N 24V 16NM Size 10 Type N, without adjustment ring Nominal voltage 24 V Rated power 30 W Cable length 400mm Rated torque 16 Nm Anchor disk nitrated

BFK458-16	
00032873	Type INTORQ 14.105.10.10 Rated voltage 24 V Power at 20°C 28 W Cable length 400 mm Rated torque 30 Nm
00102428	INTORQ 14.800.10.040
00079120	Rotor complete Type INTORQ 14.137.10.10 Bore diameter 25 mm Bore tolerance H7 according to DIN 6885/1-P9
BEG-561-255-130	Bridge/half-wave rectifier version 6-pin connection Lying design Max. connection voltage 255 V AC Max. DC current 3.0 A / 1.5 A at 60°C Overexcitation time 1,300 ms OEM part number 10167674
BFK464-19S	
BFK458-12N	
BFK466-55	
00396252	Rotor complete Type INTORQ BFK458 Size 16 Material aluminum Friction lining material standard
00464977	hub Type INTORQ BFK458 Size 16 Bore diameter 40 mm Tolerance class U7 Groove standard without groove Hub length 30 mm External toothing db x m x z W55X2.00X26
BFK458-06N	
00416240	Spring brake Type INTORQ BFK457-08 Compact Rated voltage 24 V Rated power 25 W Cable length 400 mm Rated torque 12 Nm Rotor aluminum
13018012	Spring brake Type INTORQ BFK457-08 Compact Rated voltage 205 V Rated power 25 W Cable length 250 mm Rated torque 6 Nm Rotor aluminum Low-wear friction lining Hub bore 17 mm Tolerance / version H7 according to DIN 6885/1-P9 Screw set M5X16 Flange mounted
16211991	Magnet part complete INTORQ BFK458 Size 06 Design E, with adjustment ring Rated voltage 24 V Rated power 20 W Cable length 1250 mm Rated torque 6.0 Nm Armature disk nitrided
17012829	Magnet part complete INTORQ BFK458 Size 08 Design E, with adjustment ring Rated voltage 24 V Rated power 25 W Cable length 1250 mm Rated torque 7.0 Nm Armature disk nitrided
17012830	Magnet part complete INTORQ BFK458 Size 08 Design E, with adjustment ring Rated voltage 24 V Rated power 25 W Cable length 1250 mm Rated torque 10 Nm Armature disk nitrided
	Spring-applied brake INTORQ BFK458 Brake for MOT G50BS166MHCR2C00 Code MFEMABI090-32C1C ID 16209568 S/N: 10000179144769 00537935 1 ST Magnet part cpl BFK458-10N 24V 23NM Size 10 Design N, without setting ring Nominal voltage 24 V Rated power 30 W Cable length 400 mm Nominal torque 23 Nm 00426424 Rotor complete Type

16257733	INTORQ BFK458 Size 10 Tothing addition noise-damped Material aluminum Friction lining material low-wear 00011295 Hub Type INTORQ BFK458 Size 08 / 10 Bore diameter 20 mm Tolerance class H7 Groove standard according to DIN 6885/1-P9 Hub length 20 mm External tothing db x m x z W35X1.25X26 00076260 Friction plate Type INTORQ BFK458 Size 10 Surface coating electrolytically galvanized 00399507 Screw set Designation cylinder head screw Drive hexagon socket Dimensions M6x55 Material 8.8 Surface A2F Pack size 3 pieces
00537935	Magnetic part cpl BFK458-10N 24V 23NM Size 10 Type N, without setting ring Nominal voltage 24 V Rated power 30 W Cable length 400 mm Nominal torque 23 Nm
15642208	Brake BE32B/300Nm/400AC
00406544	Type INTORQ BFK458-16E Nominal voltage 190 V Rated power 60 W Cable length 600 mm Nominal torque 80 Nm Rotor aluminum Screw set M8X80 Special marking NM34007ANR2
E318895	155-1 BRAKE
155-1 E318895	Intorq Engine Brake Model: 155-1 E318895 1LE1002-DEB42-2FA4-ZD22+F01+F11 for PAD
BFK464-25/1	
11298	
00519524 Magnetteil Komplett Intorq Bfk458-08	
015350	
00520878 Intorq Bfk458	
14.115.06.10	
00397513	
Bfk458-10e 20mm	
Bfk458-18n-205vdc	BRAKE COIL NON ADJUSTABLE 150NM SIZE 18 205VDC
00112610	
Bfk457 16 Basic	
Bfk458-08n	
Bfk458-08n 205v 8nm	
14.105.08.02	
15007178, 14.105.06.13	
396202 Rotor	

00519523 Bfk458-08	
Bfk458 18e	
520872	
Intorq Bfk457-12 Compact	Spring-loaded brake Type INTORQ BFK457-12 Compact Rated voltage 24V Rated power 40 W Cable length 350 mm Characteristic torque 23 Nm Rotor aluminum Version noise-damped Hub bore 20 mm Tolerance / execution H7 according to DIN 6885/1-P9 Integrated screw set Flange mounted Special features with Molex connector
00526082	
00396253 Rotor Bfk458-18b Aluminium	
13053795 Beg-561-255-130	
Bfk457-08	
Bfk458-16e 205v 80nm	
00544422 Bfk458-12	
00581905	
Beg-243-555	Brakes Electronics Rectifiers Type BEG-243-555 Execution one-way rectifier 4-pin connection Design lying with snap hooks Max. Supply voltage 555 V AC Max. Direct current 1 A at 60 ° C Nomenclature number 85044082 Country of origin CN (China) Weight / unit 0.020 KG
Bfk458-10n, 7nm Alternative Bfk458-10e 20mm	
00581871 Bfk458-20	
00519514 Intorq Bfk458-08	
76264	
00396288	
Bfk458-16n	
397683 Flansch	
00519518	
00743258	
13046432	
Bfk45825e1303489	BRAKE
00109043	
00111287	
13046439	

00396215	
13053795(Beg-561-225-130)	
Bfk457 - 05- 205vdc	00475684 Spring-loaded brake Type INTORQ BFK457-05 Compact Rated voltage 205V Rated power 13 W Cable length 400 mm Characteristic torque 2 Nm Rotor plastic Flange mounted Statistical commodity code 85052000 Country of origin HK (Hong Kong) Weight / unit 0.700 KG
Intorq Bfk458 (00423193)	
14.800.10.10.4	
13046 439 Replaced By Beg-161-270	
00521349	
00520245	BRAKE COIL NON ADJUSTABLE 150NM SIZE 18 205VDC
519508	
00105984 14.800.08.10.3	
Beg-561-255-130 - Fren Mod¼l¼	
00105985 14.800.08.10.3	
Bfk458-12-E Ersatzteil	
Bfk457 05 Nr 13123058	
Beg-262-460-01	
E318895	
00111286/ 14.800.06.12.8	
00396252 Bfk458-16	
13017598	
13046388 Bremsenelektronikgleichrichter Typ Beg- 142-270	
Bfk 457 - 16 / 00455254	
00109042	
Beg242-555-01	
14.800.12.10.1 Elektromagnetische Kupplungwellen-Durchmesser 28 24 V Dc 60/60 Nm 28/35w	
Bfk460-14e	
Intorq-13046-437-	

[Bremsenelektronikgleichrichter-Typ-Beg-161-270-Ausf3;Hrung-Br3;Ckengleichrichter-Anschluss-6-Polig-Bauform-Liegend-Max-Anschlussspannung-270-V-Ac-Max-Gleichstrom-075-A-Bei-60;C-Statistische-Warennummer-85044082-Istanbul-Turkiye](#)

[13046438](#)

[13046390](#)

[Bfk458-20-E](#)

[Bfk458-80e Bremsen-Spule](#)

[Beg 261 460](#)

[00034418](#)

[00521306 Magnetteil Komplett Intorg Bfk458-10](#)

[Bfk458-20e Bremsen-Spule](#)

[Beg-242-555](#)

[Bfk458-25 \(00396288\)](#)

[00401238](#)

[396215](#)

[00416212](#)

[00520878](#)

[398361 Magnetischer Teil](#)

[13046-388](#)

[399507 Schraube](#)

[14.800.08.12.4](#)

[398426](#)

[13339984](#)

[Bfk458-16e](#)

[14.115.12.10](#)

[00035596](#)

[25353](#)

[14.800.06.11.1](#)

CLUTCH BRAKE 24VDC

00406946 Ring Bfk458-16 Da=68 Di=52 S=14	
INTORQ BFK457-08 Basic	Spring-applied brake Nominal voltage 20 V Rated power 25 W. Cable length 1,210 mm Characteristic torque 12 Nm Rotor aluminum Friction lining increased characteristic torque Hub bore 20 mm Tolerance / design H7 according to DIN 6885/1-P9 Screw set M5X55 Friction plate enclosed Special features with AMP connector Special signature FL11525047001
396214	
Beg-261-460	
Disc For Bfk458-16e	
00034416	Type INTORQ 14.115.10.10 Rated voltage 24 V Power at 20°C 21 W Cable length 400 mm Rated torque 30 Nm
Bfk45818e	BRAKE
14.105.08.30	
396288	
00576340	
14.105.08.01 00000210	
00396214 Intorq Bfk458-12 Aluminium	
00571278kit	KIT
00521307	
Bfk458-10e	
Stator Intorq 14.105.08.30	
Intorq Bfk457-05 Compact	Type INTORQ BFK457-05 Compact Rated voltage 205V Rated power 13 W Cable length 400 mm Characteristic torque 4 Nm Rotor plastic Flange mounted Statistical commodity code 85052000 Country of origin HK (Hong Kong) Weight / unit 0.700 KG
14.115.08.10	
Intorq 14.800.06.12.8	Clutch-brake combination Type INTORQ 14.800.06.12.8 Output brake Rated voltage 24V Power at 20 ° C 11.5 W Rated torque 7.5 Nm Shaft diameter 11 mm Shaft tolerance K6 according to DIN 748/3 Flange diameter 140 mm Drive coupling Rated voltage 24V Power at 20 ° C 15 W Rated torque 7.5 Nm Hollow shaft diameter 11 mm Bore tolerance G7 Flange diameter 140 mm Speed max. 3,000 r / min Anchor part torsional play free
00033626	
00396200 Rotor Typ Intorq Bfk458-08	

Bfk458 Size 16e 103v	
Intorq Bfk458 (00011294)	
00396200	
Beg-262-555	
00520179 Bfk458	
Bfk45818n	STARTER
Beg-561-255-130	Type BEG-561-255-130 Design of bridge / half-wave rectifier Connection 6-pin Design lying Max. Connection voltage 255 V AC Max. DC 3.0 A / 1.5 A at 60 ° C Overexcitation time 1,300 ms Statistical commodity number 85044082 Country of origin QU (No EC country) Weight / unit 0,050 KG
396252	
13046437	
00396214	
00396202 Bfk458-10 (Rotor Typ Intorq Bfk458-10 Werkstoff Aluminium Statistische Warennummer 85059090)	
480964	
00397755	
00520250 Magnetteil Komplett Bfk458 18 E 205v 85w 66mm 150nm Verzinkt	
Bfk458-08n Der Motor Mit Diesem Getriebe Und Separat Bremsen24 V Dc	
Bremse	
00521376	
Beg-242-555-01	
520177	
Bfk457 - 03	
Beg-561-250-130 Gleichrichter	
Intorq Bfk457-06 Comp	Spring-loaded brake Type INTORQ BFK457-06 comp Rated voltage 24V Rated power 20 W Cable length 400 mm Characteristic torque 6 Nm Rotor aluminum Statistical commodity code 85052000 Country of origin CN (China) Weight / unit 1,100 KG
00570262 (Bfk458-16)	
Beg-242-555 (13046432)	
14.105.08.03	

13046388 270v 2a	
13146168	
Bfk468-31n Elektromagnetische Bremse2400 Nm, D=80mm	
Intorq Bfk458 (00043717)	
Bfk458-12e 24v 32nm	Magnetteil komplett INTORQ BFK458 Magnet t eil KPL BFK458-12E 24V 32NM Statistische Warennummer 85059029 Ursprungsland DE (Deutschland) Gewicht / Einheit 3,900 KG
Intorq Bfk458 20	
14.105.08.30 Kupplung	
14.115.08.10 0034107	
Bfk458-12	
Bfk458-10n - Cns Makina Balatasi	
00520879 Bfk458-10	
13053794 The Brake Rectifier Typ Beg- 561-255-030 255 V V 3.0/1.5a Tu=0.30s	
401238	
00396202 Rotor Kompletttyp Intorq Bfk458	
1007000000722	
00011294 Nabetyyp Intorq Bfk458nabetyyp Intorq Bfk458	
Bfk458-20e 205 V D	
Beg-561-255-030-255v 3.0/1.5a	
010582	Magnetic part for BFK458-12E 180VDC Manufacturer Intorq / Kendron Size: 12 Design: E-adjustable Coil voltage 180 VDC Rated power: 40W Cable length: 400mm Rated torque: 32Nm Anchor disk nitrided stat. goods no. 85059020 Country of origin: DE-Germany Weight per piece: 7.8 kg
13046388/Beg 142-270	
35879	
13046434 Beg-243-555	
00519514 Magnetteil Komplett Bfk458- 08	
00076260 Bfk458-10	

[00520880 Bfk458](#)

[00520174 Magnetteil Komplett Bfk458-16](#)

[00520874 Bfk458-10](#)

[Rme - 400 - S 2a / 400 V](#)

[Bfk458-10n Bremse](#)

[405202](#)