

Intronics

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Intronics Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Intronics T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
2b34j	(PRICE/EA) STRAIN GAUGE/RTD CONDITIONER, 72-DIP, IC FUNCTION:RTD / STRAIN GAUGE CONDITIONER, SUPPLY VOLTAGE MIN:14.25V, SUPPLY VOLTAGE MAX:15.75V, IC
751n	IC
2b23j	IC ISOLATED VOLTAGE TO CURRENT CONVERTER, INPUT VOLTAGE:10V, NO. OF OUTPUTS:2, SUPPLY VOLTAGE RANGE:14V TO 28V, NO. OF PINS:12, OPERATING TEMPERATURE
Rti1226	COMPUTERS, DATA ACQUISITION INTERFACE CARDS
Dac1136k	IC, DAC, 16BIT, MODULE-72, RESOLUTION (BITS):16BIT, INPUT CHANNEL TYPE:PARALLEL, DATA INTERFACE:PARALLEL, SUPPLY CURRENT:30MA, DIGITAL IC CASE STYLE:M
277a	IC, ISOLATION AMPLIFIER, 2.5KHZ, NO. OF AMPLIFIERS:1, INPUT OFFSET VOLTAGE:1.5MV, BANDWIDTH:2.5KHZ, ISOLATION VOLTAGE:3500VRMS, GAIN NON-LINEARITY MAX
	COMPUTERS, DATA ACQUISITION INTERFACE CARDS,

Rti1262	CONNECTOR TYPE:3M#3429,26PIN, OPERATING TEMPERATURE RANGE:0 C TO +70 C
Das1152	IC, ADC, 14BIT, 25KHZ, METAL CASE, RESOLUTION (BITS):14BIT, SAMPLING RATE:25KSPS, DATA INTERFACE:PARALLEL, SUPPLY CURRENT:80MA, DIGITAL IC CASE STYLE:
Rti1280	COMPUTERS, DATA ACQUISITION INTERFACE CARDS
Adc1131j	IC, ADC, 14BIT, MODULE-72, RESOLUTION (BITS):14BIT, DATA INTERFACE:PARALLEL, SERIAL, SUPPLY CURRENT:250MA, DIGITAL IC CASE STYLE:MODULE, NO. OF PINS:7
2b56a	SIGNAL CONDITIONING, SIGNAL CONDITIONER INPUT:THERMOCOUPLE, SIGNAL CONDITIONER OUTPUT:VOLTAGE, NO. OF OUTPUT CHANNELS:4, NO. OF CHANNELS:4, TYPE:DIGIT
Das1153	IC, ADC, 15BIT, 20KHZ, METAL CASE, RESOLUTION (BITS):15BIT, SAMPLING RATE:20KSPS, DATA INTERFACE:PARALLEL, SUPPLY CURRENT:80MA, DIGITAL IC CASE STYLE:
2b55a	IC, THERMOCOUPLE/MV CONDITIONER, 72-DIP, IC FUNCTION:FOUR-CHANNEL, ISOLATED THERMOCOUPLE / MV CONDITIONERS, SUPPLY VOLTAGE RANGE:12V TO 18V, OPERATING
755n	(PRICE/EA) LOGARITHMIC AMPLIFIER, 400 UV, 100 US, NO. OF AMPLIFIERS:1 AMPLIFIER, DYNAMIC RANGE:6 DECADES, SCALE FACTOR:2V / DECADE, RESPONSE TIME:100
2b31l	(PRICE/EA) STRAIN GAUGE/RTD CONDITIONER, 29-DIP, IC FUNCTION:STRAIN GAUGE / RTD CONDITIONER, SUPPLY VOLTAGE MIN:12V, SUPPLY VOLTAGE MAX:18V, IC PACKAG
2b24a	SIGNAL CONDITIONING, ISOLATION AMPLIFIERS, SIGNAL CONDITIONER INPUT:TEMPERATURE, SIGNAL CONDITIONER OUTPUT:CURRENT, NO. OF OUTPUT CHANNELS:2, NO. OF C
451k	(PRICE/EA) F/V CONVERTER, 10KHZ, 0.015%, 9-DIP, FREQUENCY:20KHZ, FULL SCALE RANGE:0HZ TO 10KHZ, LINEARITY %:0.015%, SUPPLY VOLTAGE RANGE:12V TO 18V, D