

## Italvalvole

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Italvalvole** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Italvalvole T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">Ø160 X 13 X 23 Valve Cuff</a>	
<a href="#">5402 (G: 400 - P: 1.020 )</a>	SERVOCONTROL SPARE PARTS SBS D.360
<a href="#">11839</a>	
<a href="#">12495</a>	
<a href="#">12496</a>	
<a href="#">12833</a>	
<a href="#">12834</a>	
<a href="#">17605</a>	
<a href="#">17800</a>	
<a href="#">LOT2017000005225</a>	membrane rubber gasket
<a href="#">DN 15/25/40//50/80</a>	repair kit set
<a href="#">SBS B77 T360-STD 6-18</a>	DN20 GJL PN16 PK L C20 2VNC PN¼MATİK VALF DN20

<a href="#">SBS B77 T360-STD 6-18</a>	DN25 GJL PN16 PK L C20 2VNC PNMATİK VALF DN25
<a href="#">SBS B77 T360-STD 6-18</a>	DN50 GJL PN16 PK L C20 2VNC PNMATİK VALF DN50
<a href="#">SBS B77 T360-STD 6-18</a>	DN65 GJL PN16 PK L C20 2VNC PNMATİK VALF DN65
<a href="#">SBS B77 T360-STD 6-18</a>	DN80 GJL PN16 PK L C20 2VNC PNMATİK VALF DN80
<a href="#">DN65 Proportional Burah Valve</a>	
<a href="#">DN80 Proportional Steam Valve</a>	
<a href="#">19079 (G: 120 - P: 837 )</a>	SBS A63 H360-STD 03#15 DN050 GJL PN16 PK L S20 2WNC DN 50 Seat diameter [mm] 48 Actuator [mm] 360 Actuator Material Standard Signal [psi] 3÷15 Packing PTFE / PTFE-Gr Body GJL Rating PN16 Connections EN1092-2 PN16 Face-to-Face EN558-1 Series 1 Trim 316/304 Seal PEEK Leakage Class VI Characteristic Linear Kv [m3/h] 42,4 Max Dp [bar] 7,2 Max Temperature [°C]+200° Stroke [mm] 20 Function 2 way Normally Close/Open NC
<a href="#">DIAPHRAGM D.360</a>	1714 (G: 584 - P: 40 )
<a href="#">SERVOCONTROL SPARE PARTS SBS/10 D360</a>	5402 (G: 400 - P: 1.020 )
<a href="#">13587/20</a>	SBS C77 T360-STD 06#30 DN065 GJL PN16 PK L S20 2WNO ♦ DN 65 Seat diameter [mm] 63 Actuator [mm] 360 Actuator Material Standard Signal [psi] 6÷30 Packing PTFE / PTFE-Gr Body GJL Rating PN16 Connections EN1092-1/2 PN16 Face-to-Face EN558-1 Series 1 Trim 316/304 Seal PEEK Leakage Class VI Characteristic Linear Kv [m3/h] 74,8 Max Dp [bar] 8,5 Max Temperature [°C]+200°C Stroke [mm] 20 Function 2 way Normally Close/Open NO
<a href="#">From the attached flanged on-off valves</a>	DN20 3 pieces DN25 3 pieces DN32 3 pieces
<a href="#">16861</a>	VALF PNMATİK FFF/P DN15 D:63 EPDM 6-8BAR MATR:2016/24800 SVP CODICE:16861
<a href="#">16859</a>	VALF PNMATİK FFF/P DN50 D:80 EPDM 6-8BAR MATR:2016/24847 SVP CODICE:16859
<a href="#">16853</a>	VALF PNMATİK FFF/P DN32 D:80 EPDM 6-8BAR MATR:2016/24743 SVP CODICE:16853
<a href="#">12816</a>	SUITABLE AND THE PIPE DIAMETER MUST BE 1 1/4 Please look at the attachment