



Jm Concept

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Jm Concept Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Jm Concept T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
GK3000D1	DIGITAL CONVERTER Settable with keyboards on front plate (22.5 mm width) Display 99999 Counts 2 Process inputs 4-20mA 2 AON input isolated of process input 4-20mA and supply. 1 isolated analogue output 4-20mA Input/output insulation 2500V Power supply 20Vdc to 370Vdc and 80Vac to 256Vac Delivered WITHOUT wiring base
XALIS 9000U0	UNIVERSAL INDICATOR FRONT FACE OR PC PROGRAMMATION - Alphanumerical two-coloured display - Front face programmable with 4 buttons - 1 USB plug on rear face for easy PC programming AVAILABLE INPUT - Process Input mV/V/mA - RTD input (Pt100/Pt1000...) - Potentiometre input - Thermocouple input - Resistor input
BL09DRV	
EOLIS0030A2	
EOLIS0030A2 (Isolator 2-2)	
JK 3303	
JK0030A1-F	
JK3000A-2I	
JK3002	
JK3002-AA1	
TELIS 9200U2	

TELIS9000U1	
TELIS9150U1	
XALIS 9200U1	UNIVERSAL INDICATOR 1 255.00 255.00 FRONT FACE OR PC PROGRAMMATION - Alphanumerical two-coloured display - Front face programmable with 4 buttons - 1 USB plug on rear face for easy PC programming AVAILABLE INPUT - Process Input mV/V/mA - RTD input (Pt100/Pt1000...) - Potentiometre input - Thermocouple input - Resistor input - Sensor power supply AVAILABLE OUTPUTS - 1 digital output RS485 MODBUS - 2 Relays 1 C/O - 1 Analogue output current or voltage OTHER CHARACTERISTICS - Input / Outputs / Power supply insulation - Universal power supply : 20Vdc/370Vdc & 80Vac/256Vac - Case 48 x 96 mm with unpluggable terminals
ULCOS 920D2 (Sans option)	Universal input digital Transmitter, 2 analog outputs, 2 relays, with display, DIN Rail Mounting Box
TELIS 9150U1	
JK9200N2	
Jk3000a-2i	
Jk20a2	
BI02alv	
Telis 9200u2	
Telis9000u1	
Jk6010a1	
Jk3000a2	
Eolis6000p2-Aek	
Jmconcept3400p	
Xalis 9400u1	
Jk7000a1	
Gk3000d1	DIGITAL CONVERTER Settable with keyboards on front plate (22.5 mm width) Display 99999 Counts 2 Process inputs 4-20mA 2 AON input isolated of process input 4-20mA and supply. 1 isolated analogue output 4-20mA Input/output insulation 2500V Power supply 20Vdc to 370Vdc and 80Vac to 256Vac Delivered WITHOUT wiring base
9000u2	
Jk2001	
Jk3000a2i	
Telis 9400u1	
Ulc920d2	UNIVERSAL TRANSMITTER FRONT FACE PROGRAMMATION - LCD graphic display - Programmation joystick AVAILABLE INPUTS - 1 universal input and 1 sensor supply AVAILABLE OUTPUTS - 2 Analogue output current or voltage - 2 Relays outputs 1 C/O OTHER CHARACTERISTICS - Triple Isolation Input / Outputs / Auxiliary supply : 2500Vac - Universal auxiliary supply 20Vdc/370Vdc & 80Vac/256Vac - 17.5mm width DIN RAIL mounted case with unpluggable terminals
Telis 9400u2	
Xalis3400p1	

Telis 9000u2	
Jk3000a1	
Xal3400p1	
Jk2002	
BI02alv Wiring Base	
Telis 9250t0	
B25655-A2507-A000	
Jk 9400n2 Obsolete, Replaced By Telis9400u2+ BI02alv	
Xalis 9000u1	
Jk 9400n1 Obsolete, Replaced By Telis 9400u1+ BI02alv	
Xg2714	
BI01alv For Telis9000u1	
Xalis 9000u0	UNIVERSAL INDICATOR FRONT FACE OR PC PROGRAMMATION - Alphanumerical two-coloured display - Front face programmable with 4 buttons - 1 USB plug on rear face for easy PC programming AVAILABLE INPUT - Process Input mV/V/mA - RTD input (Pt100/Pt1000...) - Potentiometre input - Thermocouple input - Resistor input AVAILABLE OUTPUTS - 1 digital output RS485 MODBUS OTHER CHARACTERISTICS - Input / Outputs / Power supply insulation - Universal power supply : 20Vdc/370Vdc & 80Vac/256Vac - Case 48 x 96 mm with unpluggable terminals
W k6000tu-Ann	
Xalis1000u1	
W k6000tu	
Jk3000a21	
Xalis 9200u1	
Jk0030a-1	
BI01alv	WIRING BASE FOR ONE TRANSMITTER 22,5mm
Ulcos600v1	
Jk 3002	Please see attached Photo
Telis6020u1 Is No More Manufactured It Can Be Replaced With Ulcos600v1	
9250t0	
Ulcos62010	