



## Jm Concept

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Jm Concept** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Jm Concept Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">GK3000D1</a>	DIGITAL CONVERTER Settable with keyboards on front plate (22.5 mm width) Display 99999 Counts 2 Process inputs 4-20mA 2 AON input isolated of process input 4-20mA and supply. 1 isolated analogue output 4-20mA Input/output insulation 2500V Power supply 20Vdc to 370Vdc and 80Vac to 256Vac Delivered WITHOUT wiring base
<a href="#">XALIS 9000U0</a>	UNIVERSAL INDICATOR FRONT FACE OR PC PROGRAMMATION - Alphanumerical two-coloured display - Front face programmable with 4 buttons - 1 USB plug on rear face for easy PC programming AVAILABLE INPUT - Process Input mV/V/mA - RTD input (Pt100/Pt1000...) - Potentiometre input - Thermocouple input - Resistor input
<a href="#">BL09DRV</a>	
<a href="#">EOLIS0030A2</a>	
<a href="#">EOLIS0030A2 (Isolator 2-2)</a>	
<a href="#">JK 3303</a>	
<a href="#">JK0030A1-F</a>	
<a href="#">JK3000A-2I</a>	
<a href="#">JK3002</a>	
<a href="#">JK3002-AA1</a>	
<a href="#">TELIS 9200U2</a>	

<a href="#">TELIS9000U1</a>	
<a href="#">TELIS9150U1</a>	
<a href="#">XALIS 9200U1</a>	UNIVERSAL INDICATOR 1 255.00 255.00 FRONT FACE OR PC PROGRAMMATION - Alphanumerical two-coloured display - Front face programmable with 4 buttons - 1 USB plug on rear face for easy PC programming AVAILABLE INPUT - Process Input mV/V/mA - RTD input (Pt100/Pt1000...) - Potentiometre input - Thermocouple input - Resistor input - Sensor power supply AVAILABLE OUTPUTS - 1 digital output RS485 MODBUS - 2 Relays 1 C/O - 1 Analogue output current or voltage OTHER CHARACTERISTICS - Input / Outputs / Power supply insulation - Universal power supply : 20Vdc/370Vdc & 80Vac/256Vac - Case 48 x 96 mm with unpluggable terminals
<a href="#">ULCOS 920D2 (Sans option)</a>	Universal input digital Transmitter, 2 analog outputs, 2 relays, with display, DIN Rail Mounting Box
<a href="#">TELIS 9150U1</a>	
<a href="#">JK9200N2</a>	
<a href="#">XALIS 9200U1 (Without option)</a>	Universal input indicator, 1 analog output, 2 relays, RS485/USB, DUALCOLOR LCD display and USB rear side
<a href="#">Jk3000a-2i</a>	
<a href="#">Jk20a2</a>	
<a href="#">BI02alv</a>	
<a href="#">Telis 9200u2</a>	
<a href="#">Telis9000u1</a>	
<a href="#">Jk6010a1</a>	
<a href="#">Jk3000a2</a>	
<a href="#">Eolis6000p2-Aek</a>	
<a href="#">Jmconcept3400p</a>	
<a href="#">Xalis 9400u1</a>	
<a href="#">Jk7000a1</a>	
<a href="#">Gk3000d1</a>	DIGITAL CONVERTER Settable with keyboards on front plate (22.5 mm width) Display 99999 Counts 2 Process inputs 4-20mA 2 AON input isolated of process input 4-20mA and supply. 1 isolated analogue output 4-20mA Input/output insulation 2500V Power supply 20Vdc to 370Vdc and 80Vac to 256Vac Delivered WITHOUT wiring base
<a href="#">9000u2</a>	
<a href="#">Jk2001</a>	
<a href="#">Jk3000a2i</a>	
<a href="#">Telis 9400u1</a>	
<a href="#">Ulc920d2</a>	UNIVERSAL TRANSMITTER FRONT FACE PROGRAMMATION - LCD graphic display - Programmation joystick AVAILABLE INPUTS - 1 universal input and 1 sensor supply AVAILABLE OUTPUTS - 2 Analogue output current or voltage - 2 Relays outputs 1 C/O OTHER CHARACTERISTICS - Triple Isolation Input / Outputs / Auxiliary supply : 2500Vac - Universal auxiliary supply 20Vdc/370Vdc & 80Vac/256Vac - 17.5mm width DIN RAIL mounted case with unplugable terminals

<a href="#">Telis 9400u2</a> <a href="#">Xalis3400p1</a>	
<a href="#">Telis 9000u2</a>	
<a href="#">Jk3000a1</a>	
<a href="#">Xal3400p1</a>	
<a href="#">Jk2002</a>	
<a href="#">BI02alv Wiring Base</a>	
<a href="#">Telis 9250t0</a>	
<a href="#">B25655-A2507-A000</a>	
<a href="#">Jk 9400n2 Obsolete, Replaced By Telis9400u2+</a> <a href="#">BI02alv</a>	
<a href="#">Xalis 9000u1</a>	
<a href="#">Jk 9400n1 Obsolete, Replaced By Telis</a> <a href="#">9400u1+ BI02alv</a>	
<a href="#">Xg2714</a>	
<a href="#">BI01alv For Telis9000u1</a>	
<a href="#">Xalis 9000u0</a>	UNIVERSAL INDICATOR FRONT FACE OR PC PROGRAMMATION - Alphanumerical two-coloured display - Front face programmable with 4 buttons - 1 USB plug on rear face for easy PC programming AVAILABLE INPUT - Process Input mV/V/mA - RTD input (Pt100/Pt1000...) - Potentiometre input - Thermocouple input - Resistor input AVAILABLE OUTPUTS - 1 digital output RS485 MODBUS OTHER CHARACTERISTICS - Input / Outputs / Power supply insulation - Universal power supply : 20Vdc/370Vdc & 80Vac/256Vac - Case 48 x 96 mm with unpluggable terminals
<a href="#">Wk6000tu-Ann</a>	
<a href="#">Xalis1000u1</a>	
<a href="#">Wk6000tu</a>	
<a href="#">Jk3000a21</a>	
<a href="#">Xalis 9200u1</a>	
<a href="#">Jk0030a-1</a>	
<a href="#">BI01alv</a>	WIRING BASE FOR ONE TRANSMITTER 22,5mm
<a href="#">Ulcos600v1</a>	
<a href="#">Jk 3002</a>	Please see attached Photo
<a href="#">Telis6020u1 Is No More Manufactured It Can Be</a> <a href="#">Replaced With Ulcos600v1</a>	
<a href="#">9250t0</a>	
<a href="#">Ulcos62010</a>	