



Kbr Kompensationsanlagenbau

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Kbr Kompensationsanlagenbau Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Kbr Kompensationsanlagenbau Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
multimess F96 23426	Mains measuring instrument for panel mounting, TFT display Colors freely adjustable by user Design: 2-TFT-ESMS-2RO1DO-US1 Dimensions: HxWxD 96mm x 96mm x 67mm Power supply Us: 100-240 V +/-10% AC/DC, 50/60 Hz, 8 VA Measuring voltage Um: 3 x 5...600 V AC, measuring current Im: 3 x 0.01...6 A AC Interface(s): KBR eBus RS485, Modbus RS485 Load profile storage for 366 days 2 signaling relays, 1 work pulse output S0 Degree of protection: front IP 40 / insulation class I Software requirement for integration into "visual energy 4" is the SW version 4.7 Release 1
F96-2-TFT-ESMS-2RO1DO-US1	
F144-2-LED-ESMS-2RO1DO-US1	
F144-3ph	
14084 - Multimess F144	
multicond-premium UHPC-33.4-480-3P	10371 Three-phase power capacitor in SF6-free dry technology Capacitor Rated Voltage: 480V Capacitor rated frequency: 50/60 Hz Power: 23.2 kvar at 400 V / 50 Hz Power: 33.4 kvar at 480 V / 50 Hz Capacitance: 3 x 153.82µF Ampacity: 2.0 x In Degree of protection: IP 20 with discharge resistor Dimensions: H x D 246.5mm x 136mm plus grounding bolt M12. l=16.5mm Life expectancy at temperature class: D (-40/55 °C) > 250,000 h
multiind-light 400-50-50.0-7-Cu-RK-S	10065 Three-phase filter circuit choke Rated Voltage: 400V/50Hz Power: 50 kvar Inductance: 0.767mH Choking factor: 7% (189 Hz) Linearity constancy: 1.6 x In Inductance matching: +/- 3% to In Degree of protection: IP 00 Ambient temperature Tu : 40 °C Temperature class: B (135 °C) Thermal switch: normally closed at 125 °C in the middle coil Execution: copper, standing, with tubular cable lug, vacuum impregnated Dimensions: HxWxD 250mm x 240mm x 145mm
Multimess F96 model	Mains measuring instrument for panel mounting, TFT display Colors freely adjustable by user Design: 2-TFT-ESMS-2RO1DO-US1 Dimensions: HxWxD 96mm x 96mm x 67mm Power supply Us: 100-240 V +/-10% AC/DC, 50/60 Hz, 8 VA Measuring voltage Um: 3 x 5...600 V AC, measuring current Im: 3 x 0.01...6 A AC Interface(s): KBR eBus RS485, Modbus RS485 Load profile storage for 366 days 2 signaling relays, 1 work pulse output S0 Degree of protection: front IP 40 / insulation class I Software requirement for integration into "visual energy" is the SW version 4.7 Release 1 Deviating from the terms and conditions, "General Terms of Delivery" applies to the

aforementioned Position a warranty period of 5 years from delivery.

multicomp D6	26715 Consisting of: ID: 24140 Power factor controller for standard rail mounting, dimensions: 6TE Version: ESBSDS-1V1C6RO Power supply Us: 100-240 V +/-10% AC/DC, 50/60 Hz, 22 VA Measuring voltage Um: 1 x 50...500...600 V AC CAT III:300V 1 x 10...172.5...207 V AC CAT III:300V 1 x 50...690...828VAC CAT II: 400V Measuring current Im: 1 x 0.05...5... 6 A AC CAT III: 300V 1 x 0.01...1...1.2 A AC CAT III: 300V Interface(s): KBR eBus RS485 / Modbus RS485 4 x relay outputs, 1 x temperature input PT1000, 2 x auxiliary relay outputs Degree of protection: front IP 20 / insulation class I ID: 26635 multicomp F96-TFT, operating unit for control panel installation, TFT display Version: DS, dimensions: HxWxD 96 mm x 96 mm x 45 mm Degree of protection: front IP 51 / insulation class I Operating language: German/English/French
multisio D6-ESBSDS-5DI6RO1DO-6	
F96-2-TFT-ESMS-2RO1DO-US1-5	
Multisio D6-1-ESBSDS-5DI6RO1DO-US1	
Multisio D2-4TI-10105	
3 meter 2-wire Pt100 Temperature Sensor	
UHPC-33.4-480-3P	Heavy-Duty
UHPC-17.9-480-3P	Heavy-Duty
Multicomp F96	
40kVAR COMPANIZATION CONTRACTOR	
20kVAR 440V CONDANSATOR	
F96-2-TFT-ESMS-2RO1DO-US1-eBus	
D6-ESBSDS-5DI6RO1DO-6 14181	
L0844803 ELECTRICAL MOTOR P0769010 I.15	
L0844804 ELECTRICAL MOTOR P0769010 I.59	
L5783700 ZONE LEVER CPL	
L0843338 MOTOR GEAR 10000N	
L0861071 MOTOR SHEER GUIDE.	
L08447402 SENSOR WANISH	
Multimes F144	14088 multimes F144 Network instrument for panel mounting, LED display Version: 2-LED-ESMS-US1 Dimensions: HxWxD 144 mm x 144 mm x 60 mm Power supply Us: 85-265 V AC / DC, 50/60 Hz, 15 VA Measuring voltage Um: 3 x 5 ... 600 V AC, measuring current Im: 3 x 0.01 ... 6 A AC Interface (s): KBR eBus RS485, Modbus RS485 Load profile storage for 365 days 1 synchronous, 1 tariff switching input 2 signaling relays, 1 working pulse output S0, 3 analogue outputs Type of protection: Front IP 51 / SK I Customs tariff number: 90303200 Country of origin: Germany Total weight: 1.38 kg
4f96-1lcd-Esms-2ro-US1 / Energieanalyser - Multimes 96 Lcd	
Multimes F96	Network measuring instrument for panel mounting, TFT display Colors freely adjustable by the user Version: 2-TFT-ESMS-2RO1DO-US1 Dimensions: HxWxD 96 mm x 96 mm x 67 mm Power supply Us: 100-240 V +/- 10% AC / DC, 50/60 Hz, 8 VA Measuring voltage Um: 3 x 5 ... 600 V AC, measuring current Im: 3 x 0.01 ... 6 A AC Interface (s): KBR eBus RS485, Modbus RS485 Load profile memory for 366 days 2 signaling relays, 1 working pulse output S0 Degree of protection: Front IP 40 / SK I The software version for integration into "visual energy 4" is the SW version 4.7

Release 1 Customs tariff number: 90303200 Country of origin: Germany

[Multisio D6](#)

Central storage module for multisio acquisition system Version: ESBSDS-5DI6RO1DO, dimensions: 6TE Power supply Us: 100-240 V +/- 10% AC / DC, 50/60 Hz, 18 VA Interface (s): KBR eBus RS485, KBR module bus expandable with up to 5 expansion modules via KBR module bus, parameterizable via software 5 x digital in, 1 x digital out, 6 x relay out The software version for integration into "visual energy 4" is the SW version 4.7.1 Release 12518 Customs tariff number: 84714100 Country of origin: Germany