

Keb

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Keb** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Keb T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Keb Driver 7,5 Kw 14f5q1d-Yp10	
02 91 020 Ce07	
14 F4 F1G-4100	
KEB K4.3 BSHT2DA100LX4 3.0KW MOTOR	
12.F4.C3D-3420	KEB / ISA frequency converter type F4.C Packing and shipping (UPS)
12F5C1B-350A	KEB COMBIVERT F5-COMPACT controlled frequency converter Furnishing: Braking transistor: GTR7 Heatsink Type: Air Cooler Technical specifications: Power: 6.6kVA Motor: 4.0kW 2/4P 50/60Hz Input voltage range: 400V AC 3 PH Output voltage: 0...Uin Rated output current: 9.5A Max. short-term current limit: 17.0A Max output frequency: 599Hz Switching frequency: 4kHz Protection class: IP20 Dimensions (WxHxD): 90 x 220 x 160 mm
08P1320-0057	KEB COMBIPERM Torque M2N (Nm): 36 Power P2O (W): 26 Voltage (V): 24 Bore hub ø : 30 H7 Groove hub : 8 P9 According to drawing 08.P1.320-0057
06.10.042	24V to 205 V DC 6 to 130Nm
08P1320-0057-0C-24VDC-26W	
09G6CDA-39B0	KEB COMBIVERT G6-C controlled frequency converter Analogue/Digital (default) Furnishing: Safety functions: STO LCD display with keyboard integrated filter - low leakage current Braking transistor: GTR7 Technical specifications: Power: 2.8kVA Motor: 1.5kW 2/4P 50/60Hz Input voltage

	range: 400V AC 3 PH Output voltage: 0...Uin Rated output current: 4.1A Max output frequency: 400Hz Switching frequency: 4kHz Protection class: IP20 Commodity number: 85044084 Single net weight: 1,670 KG
10.F5.HBD.Y00F	
00.F5.060-2000	
9098200-CE09	POWER BOX Input voltage 180 - 300 V AC \pm 0% Overexcitation time 350ms \pm 10% Cable length max. 100 m to the brake coil Rated current (45°C) 1.2 A continuously, 2.4 A for 350 ms Rated current (85°C) 0.5 A continuously, 1.4 A for 350 ms Continuous operation only permissible at 45°C
09F5M1D-3AGA	KEB COMBIVERT F5-MULTI controlled servo converter Furnishing: Encoder interface 1: input incr. TTL Encoder interface 2: input incr. TTL Braking transistor: GTR7 Heatsink Type: Air Cooler Technical specifications: Power: 2.8kVA Motor: 1.5kW 2/4P 50/60Hz Input voltage range: 305...528V AC 3 PH Output voltage: 0...Uin Rated output current: 4.1A Max. short-term current limit: 7.4A Max output frequency: 800Hz Switching frequency: 8kHz Protection class: IP20 Dimensions (WxHxD): 90 x 250 x 181 mm
0058060-0040	K E B USB-serial service cable HSP5, DIN66019 Data line USB => HSP5 / RS 232 for direct connection of KEB Combivert and PC bypassing the operator at F5 and B6 (HSP5) or with interface operator at F5 and F4 or directly at G6 (DIN 66019) Length 2.0m
12F5C1B-350A	KEB COMBIVERT F5-COMPACT controlled frequency converter Braking transistor: GTR7 Heatsink Type: Air Cooler Technical specifications: Power: 6.6kVA Motor: 4.0kW 2/4P 50/60Hz Input voltage range: 400V AC 3 PH Output voltage: 0...Uin Rated output current: 9.5A Max. short- term current limit: 17.0A Max output frequency: 599Hz Switching frequency: 4kHz , IP20 Product Status: NRND - Not recommended for new design
14F5C1D-380A	KEB COMBIVERT F5-COMPACT controlled frequency converter Furnishing: Brake transistor: GTR7 Heatsink Type: Air Cooler Technical data: Power: 11kVA Motor: 7.5kW 2/4P 50/60Hz Input voltage range: 305...528V AC 3 PH Output voltage: 0...Uin Rated output current: 16.5A max. short-term limit current: 29.7A Max. output frequency: 599Hz Switching frequency: 2kHz Protection class: IP20
03.33.004.1051	spring magnetic brake
NMS40HU-10/1-63L/4A-IE2-TB-ST05	uniGear worm gear motor 0.25 kW, 1400 rpm 3x230 V, 50 Hz, IP 55, insulated Cl. F with plug ST05, without mating connector Engine IE2 *Incl. Output flange NMS40 FC
06 15 100 0047 24V 13 W	24DC FOR TYP T4F4BR0017 MOTOR
Permanent magnet brake	Type 08.02.130-24VDC 30 Nm, 20 watts Anchor hole \varnothing ? Groove according to DIN 6885/1 When ordering, please specify the desired hole!
Power operated brake	Type 09.03.110-24VDC 65 Nm, 35 watts Rotor bore \varnothing ? Groove according to DIN 6885/1 When ordering, please specify the desired hole!
MAGNETİC BRAKE 09.03.100-0241 24V DC	
MAGNETİC BRAKE 08.02.332-0009 24V DC	
00.C6.BD1-ECB0	Combicontrol C6 Compact II HSP5/485 4 Dig-in 4Dig-out Profinet Softmotion
09S6K12-1100	KEB COMBIVERT S6 COMPACT Drive controller for real-time communication Technical characteristics: Fieldbus: EtherCAT/CAN Device profile: CiA 402 Inputs: 8 digital/2 analog Outputs: 4 digital/ 1 analog/ 1 relay Two-channel multi encoder interface Brake control 24V/2A Motor temperature sensor: KTY/ PTC/ PT1000 Power section version: with internal filter Brake transistor: integrated Safety function: STO Heat sink

	type: air cooler, built-in version IP20 Technical data: Type. Rated motor power: 1.5kW 2/4P 50/60Hz Rated output power: 2.8kVA Rated input voltage: 400V / AC 3 PH / 50/60Hz Rated output current: 4.1A Short-term limit current: 3s/250%, 60s/200% Max. output frequency: 599Hz Rated switching frequency: 8kHz Protection class: IP20 Dimensions (WxHxD): 50 x 310 x 220 mm
00S6ZC0-0000	S6-K connector and shield set STO Case 2 - Size 07, 09, 10
C2SMHF0-54I0	KEB Dynamic Line DL3 Three-phase synchronous servo motor Furnishing: Encoder type: RESOLVER-2P resolver Angle flange sockets: rotatable Temperature sensor: KTY84 UR/ cUR approval: E471175 Technical data: Standstill torque: 4.00Nm Standstill current: 4.10A Rated speed: 5000rpm. Rated torque: 3.70Nm Rated current: 3.80A Protection class: IP54 Design: IM B5 Edge length: 87mm Hole circle diameter (output): 100mm Recess diameter (output): 80mm Shaft diameter: 19x 40mm Shaft: with feather key
0090396-1720	FERRITE RING CORE PERM. UI = 6000 AL: 13240NH +/-25% DIMENSIONS: 26X14.5X20MM CORE POLIAMIDE GRAY PACKAGING:
14DRB08-1451	THROTTLE 3PH / 400VAC MAINS/MOTOR IN = 20.0A UK = 4% L = 1.47 MH F=50/60HZ FS=2-8KHZ DIMENSIONS: 178X95X165MM WEIGHT: 5.4KG PV = 54W
0008110-4005	KEB COMBISTOP Torque M2N (Nm): 1 Power P2O (W): 11 Voltage (V): 24 Bore hub ø: 8 H8 Nut hub: 2 P9
0710510-4015	KEB COMBIBOX Brake M2N (Nm): 15 Brake P2O (W): 16 Coupling M2N (Nm): 15 Clutch P2O (W): 20 Voltage (V): 24 Bore A ø: 19 G7 Flange A ø: 120 B14 Bore from ø: 19 G7 Flange made of ø: 140 B5 Terminal box location: B2 Terminal box IP65 M16 x 1.5
TA2M V40 ER TW	Rated power: 1.04kW S1 Motor speed: 0 - 4500 1/min System voltage: 400V Torque M0/Mn/Mmax: 2.4/2.2/7.2Nm Rated current I0/In/Imax: 2.15/1.96/6.4A Insulation class: 155 Protection class: IP54 Flange 75x75/Ø75-4xØ5.5/Ø60 Output shaft with key Ø11x23 ER - resolver, without mating connector Motor protection: PTC thermistor temperature sensor Motor connection: Right-angled, rotatable M23 connector, position 0B UL version (C+US), file E342804 Color: normal, RAL9005 jet black Installation position: B5 Weight: ~3.3 kg
Typ 08.P1.130-24VDC	Permanent magnet brake
Typ 09.03.130-24VDC	Electromagnetic clutch
7606912-4fyc	
303 0100.16	
16f5c1d-390a	
15f5c1e-350a	
14f5gbd-Ym00, 10594113 (*)	
12.Dr.B08-2851	
28f5hbp-900d	
27f5hau-Yvm0	
Hsp5/485 No 00f5025-0080	
Gvme600sc-B	PC BOARD
14f5c1e-Y00a	
0710670-4006	
12f5ebd-Ya00	3 Phase AC Drive

Sku 12010986292	
1009010-0009	
09f5cbb3aoa	DRIVE
00f50c00020 P.O4500306825	
3hac023195-003	TEACH PENDANT CABLE SET 10M
00.F4.010-2009	
19p6h2g	
00f5060-2100 Interface-Operator Mit Potentialgetrennter Serieller Schnittstelle Rs 232/485 Auf Submin-D-9-Stecker Statistische Warennummer: 85049099 Einzelnettogewicht: 0,160 Kg	
10 09 370 4000	
E-7-Temp/7	PC BOARD
00f5060-5018 Can	
00f5060-1100	
00f5060-5000	
07f5c1b-3b0a	
20f4c0k2441	
0810670-4043	
Rs-091	POWER MODULE
09094404033	
10 04 000 0402	
09.F4.C1d.4a01-1.4 Oem	
10 F4 S1d-5d02/ 1 2	
Ls70ms	
12f5c3b-Yq1a	AC Drive
Do321/16	OUTPUT CARD 16 FOR ENGEL PRESS
4 Kw - 12f5c3b-Yq1a 380 V	
05.B6.A2a-6a00(Ex.05f4soc1220)	
10.09.370-4000	
D3268308-10-570	
F4 S 4kw	inverter
23z1b04-1000 Line Choke	
Ht4-1684617731	HANDHELD TEACH PANEL TERMINAL
13.Dr.B08-1851	
10.F4-F1d-3440 V3.9	

Ketop-C100rw2/65693/18	TEACH PENDANT CONTROL MODULE 0.3AMP 24VDC
12e5t60-1001	Line Filter KEB 12.E5.T60-1001
0810370-4001	
03292626/0476815_07.F4.S1d-3420/1.2 (Obsolete)	
07.10.440	
023811n-4017	
00f5060-H000	
10for110000	DRIVE
303 0080.16	
15f5c1e-Y50a	
05.F4.019-0048 V.1.0 Not Available	
18f4c0h3440	
023800n-1051	
15f5c1e150a3514	INVERTER
00f50c0-0020	
07105704000	
16.Dr.B08-7341	
14.F4.C1e-4a01/1.4	DRIVE 7.5KW 305-440V 3PHASE
7.5 Kw - 14f5g1e-Yq1a 380 V	
08.38.13n.4002	
07f5c1b-2b0a	DRIVE 4.4AMP 200-230V/208-240V 3PH 50/60HZ
09f5c1d-3a0a	
0610370-4000	
07.F5.B1a.Z000	MOTOR CONTROL 4.1AMP 240VAC 1600HZ
18f4c0h-3441	DRIVE 50AMP 480V 3PH 30HP INTERBUS
13.F5.A1d-390a	DRIVE INVERTER 5.5KW 400-480VAC
15f4c1e3420	
073813n-0000	
18u400hbm00	
14.F5.C1e-3a0a	
0910580-2hgu	
00f50c0-4100 450032728	
B5-Zg1bprcr80g8-4	
Ht2/Ss/20677	ROBOT CONTROL TEACH PENDANT .1AMP 24VDC
17.F5.M1g-350a (18,5 Kw) Inverter	

11bp-99093n	
2.2 Kw - 10f5c3b-Yq1a 380 V	
10.F4-F1d-3440	
Ht401-222/Nco-4/O/21049	TEACH PENDANT MODULE 24V LCD DISPLAY
14f5c1e-3a0a	
08.10.370-4000	
Ps-242	POWER SUPPLY
09f5c3b-0b0a	
07.Dr.B08-4951	
10-F4-C1d-3460/1.4	DRIVE 4KVA 2.2KW 440/480V
Ms	
15f5abe-Yh01	11 KW KEB DRIVER 15F5ABE-YH01 F¼R: LIEBHERR EC 154 H6 MODEL: 2010 MOTOR NR: WN No: 49895 S/N: 32649895
17f5c1g-350d	
18.F5.Abq-34wf	DRIVE INVERTER 22KW 400VAC 3PHASE
09fo2001228	
13.F5.H1d-L90a	AC DRIVE
Zg4bprcr132m8-4	
0610670-4009	
00f40102009	
00f50c0-0010	
0108210	
16.F4.F1g-M440	
10u400dbm00	
09f5b1b-3a0a	KEB COMBIVERT F5-BASIC controlled frequency converter Domestic equipments: Braking transistor: GTR7 Type of heat sink: Air cooler surface-mounted version Technical specifications: Power: 2.8kVA Motor: 1.5kW 2 / 4P 50 / 60Hz Input voltage range: 400V AC 3 PH Output voltage: 0 ... Uin Output rated current: 4.1A Max. Short-time current limit: 7,4A Max. Output frequency: 400Hz Switching frequency: 8kHz Protection class: IP20 Dimensions (WxHxD): 90 x 220 x 160 mm Statistical commodity code: 85044084 Single net weight: 1,900 KG This lot needs an export license according to item list 3A225 Annex I of the Dual Use Regulation.
15.F5.M1e.35g0	DRIVE INVERTER 23.1-26.5AMP 3PH 305-500VAC 50/60HZ
07f5a1d-2bya	
1004000-0402	
12.F5.B1d-3a00 (4.0 Kw) Inverter	
0291010-Ce07	
07.F4.C3d-3420	
07.06.68047578	

0058060-0040	
12.F5.A1d-Laea	DRIVE 5HP CLOSED LOOP
Aa0120	CONTROL BOARD
16f4-Cog-M441	FREQUENCY INVERTER 33A 420-720VDC 15KW
G02c Dm71g4 Ts	
21f5m0r-55ga	
07.F4.S1d-3420	DRIVE 1HP 0.75KW 2.6AMP 380-480VAC 3PHASE
Zg1bprcr80g8-4	
0605800-0377	
F00f40101009	
07f5b1b-3b0a (0.75kw)	KEB COMBIVERT F5-BASIC controlled frequency converter Equipment: Braking transistor: GTR7 Type of heat sink: Air cooler surface-mounted version Technical specifications: Power: 1.8kVA Motor: 0.75kW 2 / 4P 50 / 60Hz Input voltage range: 400V AC 3 PH Output voltage: 0 ... Uin Output rated current: 2.6A Max. Short-time current limit: 4.7A Max. Output frequency: 400Hz Switching frequency: 16kHz Protection class: IP20 Dimensions (WxHxD): 90 x 220 x 160 mm Statistical commodity code: 85044084 Single net weight: 1,800 KG This lot needs an export license according to item list 3A225 Annex I of the Dual Use Regulation.
07.03.100-0244	
Kemro-8gt	RACK 8SLOT
02.38.11n-So	
09-F4-S1d-1220/1.2	DRIVE INVERTER 12-14AMP 2.8KVA 1PH 200-264VAC
B5-Zg4bprcr132m8-4	
10f4c1d3460	
10.04.000-0402	
13f5c1d-390a	
22.F5.A1r.954a	
Ms-Repeater	
10.03.100-0241	
00f5060-200f	
12560804008	
07.F5.B1b-3900 (0.75kw)	
15.F4.C1g-M441/2.2	DRIVE INVERTOR 23.1A 3PH 305-440VAC 50/60HZ 11KW
12f5h1d-3a0a	
14.F5.A1e-3a0a	DRIVE INVERTER 23/19.6A 3PH 400/480VAC 7.5KW 11KVA
07.F0.220-1278	DRIVE 1PH 200/240V 50/60HZ
10f4f1d4r01	
15f4cog2441	

18.F5.A1b-364f	
16f4f1g4r01	
07.F4.C1d-3420	.75KW AC DRIVE
07.F5.G1d-3b0a	DRIVE AC MOTOR CONTROL 3PHASE 440VAC
09fo2001229	
09f5b3a-Ya10	INVERTER DRIVE 3PH 5.7A 400V 50/60HZ
10.09.010.0009	
03.S4.D2a-3012	SERVO CONTROLLER OUTPUT 2.6AMP 3PH 1.0KVA 190V
00.00.000-0890	
07.F4-C1d-3420/1.4	
10.16.370	
18f4f1h4r01	
05.F4.Soc-1220	INVERTER DRIVE 400VAC 0.37KW
18e5t60-1001	
18.5 Kw - 17f5g1g-Yq1a 380 V	
07gtg240001	GEAR MOTOR
09f5b3a-390a	
15f5b1e-350a (11 Kw)	KEB COMBIVERT F5-BASIC controlled frequency converter Equipment: Braking transistor: GTR7 Heat sink type: air cooler Technical specifications: Power: 17kVA Motor: 11kW 2 / 4P 50 / 60Hz Input voltage range: 400V AC 3 PH Output voltage: 0 ... Uin Output rated current: 24A Max. Short-time current limit: 36.0A Max. Output frequency: 400Hz Switching frequency: 4kHz Dimensions (WxHxD): 130 x 290 x 208 mm Statistical commodity code: 85044088 Single net weight: 5,040 KG
09.F5.Bib.2b00	
13.F5.M1d-3a00 (5,5 Kw) Inverter	
09f5m3d-3aga Keb Combivert F5-Multi	
K33av Dm100la4 Ts	Bevel gear motor K33AV DM100LA4 TS Output speed: 83 1 / min Torque: 255Nm -- Transmission value: 1.60 Transmission: -- Translation: 17.57 Foot-mounted Output shaft with key Ø30x60 vent valve -- Connection side: R Lubricant: 1.9 l CLP VG220 mineral oil Motor: three-phase motor IE3 Rated power: 2.2kW -- Engine speed: 1460 1 / min Voltage / Frequency: ? / Y 230 / 400V 50Hz Rated current: 7.7 / 4.45A cos?: 0.81 - - Insulation class: 155 Protection class: IP65 Motor protection: Temperature switch (normally closed) Dust and water protection Motor connection: Terminal box 2xM25, position 0A Coloring: normal, RAL9005 deep black Installation position: M4 (vertical installation) Weight: ~ 51 kg -- made in Germany
00.F5.Bib.2b00	
10.F0.R01-4b09	DRIVE 3PHASE 240VAC
14f5l1d-Y8sa	
14f5m1e-3aea11kva	
10p1-130-0000	
04.F5.F3a-Ye01	

07f5a1a-3e2f	
00.B0.0bk-K001	KEB Interbus Remote Bus KEB 00.B0.0BK-K001
303 0040.16	
D25ls70ms	
14.Dr.B08-1451	
0610570-4006 Combibox	
F5-Compact	
09f5b1b13a0a	DRIVE
10f5m3dlbda	MODULE
303 0050.16	
23f5har-Yvm0	
06 10 042	
01102044/0414745	
09.F5.B1b-3900	INVERTER DRIVE AC 3PHASE 1.5KW 440-480VAC 50/60HZ
14.F4.F1e-4019	7.5KW AC DRIVE
Aw14243	SERVO CONTROL
14e5t60-0001	
07f5b3a-390a	
16.F5.A1g-360a	DRIVE INVERTER 3PHASE 42.9AMP 23KVA 400VAC 50/60HZ
10.F0.R11-3429	DRIVE INVERTER 3HP
12f5b1d-3a0a (4.0 Kw)	KEB COMBIVERT F5-BASIC controlled frequency converter Equipment: Braking transistor: GTR7 Heat sink type: air cooler Technical specifications: Power: 6,6kVA Motor: 4.0kW 2 / 4P 50 / 60Hz Input voltage range: 400V AC 3 PH Output voltage: 0 ... Uin Rated output current: 9.5 A Max. Short-time current limit: 17,0A Max. Output frequency: 400Hz Switching frequency: 8kHz Protection class: IP20 Dimensions (WxHxD): 90 x 250 x 181 mm Statistical commodity code: 85044084 Single net weight: 2,840 KG
1mf5280-0029	
05f4socm220	DRIVE AC COMBIVERT 0.37K/W
10 06 670-0037	
Ft101661a	DRIVE AC 12AMP 370VOLT 50/60HZ F0 SERIES
0491010-Ce07	
12.Sm.000-3400	SERVO MOTOR 40IN/LB/4.5NM 3000RPM 330V TNOM
17f5g1g-350a	KEB COMBIVERT F5 GENERAL controlled frequency converter Domestic equipments: Braking transistor: GTR7 Type of heat sink: Air cooler surface-mounted version Technical specifications: Power: 29kVA Motor: 18.5kW 2 / 4P 50 / 60Hz Input voltage range: 305 ... 528V AC 3 PH Output voltage: 0 ... Uin Rated output current: 42A Max. Short-time current limit: 63.0A Max. Output frequency: 400Hz Switching frequency: 4kHz Protection class: IP20 Dimensions (WxHxD): 170 x 340 x 255 mm Statistical commodity code: 85044088 Single net weight: 9,600 KG This lot needs an export license according to item list 3A225 Annex I of the

Dual Use Regulation.	
09f5h1d-3a0a	
0909440-4006	
1009370-4000	
07.31.230-0000	
2mf5280-1019 Encoder Karti	
07.08.230-0000	
12.F4.C1e-1240	INVERTER DRIVE AC 3PH 16.5A 240VAC 50/60HZ
0291020-Ce07	
Ht4-20656	HAND TERMINAL 0.2AMP 24V
27z1b04-1000 Line Choke	
07.F5.M1d-Lbta	DRIVE 1HP CLOSED LOOP
07.F5b1b-R001	DRIVE CONTROLLER 2.5AMP 500V IN/1.8AMP 480V OUT
10 F5 C3b-Yq1a	
12f5c1dla0a	DRIVE
16.F4.C1g-2441/2.2	DRIVE INVERTOR 33AMP 2/4POLE 500V 50/60HZ 15KW
0810370-4000	
M6871	TOOL
09.F5.B1b-3a0a	INVERTER DRIVE AC 5.7AMP 3PHASE 440VAC 50/60HZ
00f5060-6000	
18.F5.B1g-3400	DRIVE AC 3PH 400V 35KVA
13e5t60a071	INVERTER
00-F5-060-5000	
Ft011241a	DRIVE AC 12AMP 50/60HZ F0 SERIES
10.F4.C1d-5a01/1.4	AC DRIVE 1PH 200-264V 20A 50-60HZ
15.F4.C1g-3441/2.2	DRIVE INVERTOR 26.5AMP 2/4POLE 480V 50/60HZ 11KW
00580290049	CONTROL BOARD
13.G6.C3b-3910	DRIVE INVERTER 8.3KVA AC3 PHASE 50/60HZ
1003100-0241	
0d.56.180-0029	LOGIC BOARD
10f4f1d344012	DRIVE
15.F4.C1e-3420/1.4	DRIVE INVERTER 26.5AMP 3PH 305-440VAC 17KVA 11KW
14.F5.G1e-3a0a	DRIVE INVERTER 7.5KW 2PHASE 50/60HZ
05.F4.S2c-1220	DRIVE INVERTER 0.37KW 1PHASE 200/240V 50/60HZ