



Keith & Koep

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Keith & Koep Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Keith & Koep T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
2306-Us	BATTERY / CHARGER SIMULATOR, 15V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2, OUTPUT VOLTAGE:15V, OUTPUT VOLTAGE 2:15V, OUTPUT CURRENT:5A
7035	9 BANK 1X4 MULTIPLEXER SWITCHING CARD FOR 7001, 7002. (MATING CONNECTOR INCLUDED)
248/E	5KV POWER SUPPLY @220V
2002-Us	8.5D DMM W/8K MEMORY
2651a	SOURCE METER, DC VOLTAGE CURRENT, 200W, SOURCE METER FUNCTION:CURRENT/VOLTAGE SOURCE, DMM, ELECTRONIC LOAD, POWER SUPPLY, WAVEFORM GENERATOR, SOURCE
6220/2182a-Us	SOURCE METER, DC CURRENT, 11W, SOURCE METER FUNCTION:CURRENT SOURCE, SOURCE VOLTAGE RANGE:-, OUTPUT POWER:11W, SOURCE CURRENT RANGE:2NA TO 100MA, RESI
2790.	SOURCEMETER SWITCH SYSTEM MAINFRAME

7073	8X12 COAX MATRIX CARD FOR 707
3723	MULTIPLEXER CARD, ACCESSORY TYPE:MULTIPLEXER CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:DUAL 1 30, HIGH SP
2000-Scan-20	20 CHANNEL SCANNER BOARD
708b	(PRICE/EA) 1 SLOT SEMICONDUCTOR SWITCHING MAINFRAME
2015/E-Nok	THD DIGITAL MULTIMETER @220V WITH CAL LA
2001-Uş	HIGH PERFORMANCE 7-1/2 DIGIT DMM WITH 8K MEMORY, DMM FUNCTIONS:AC/DC CURRENT, AC/DC VOLTAGE, FREQUENCY, RESISTANCE, TEMPERATURE, CURRENT MEASURE AC MA
6220	SOURCE METER, DC CURRENT, 11W, SOURCE METER FUNCTION:CURRENT SOURCE, OUTPUT POWER:11W, SOURCE CURRENT RANGE: 2NA TO 100MA, I-V ACCURACY MIN.:0.4% +
62212182a	SOURCE METER, AC DC CURRENT, 11W, SOURCE METER FUNCTION:CURRENT SOURCE, OUTPUT POWER:11W, SOURCE CURRENT RANGE:2NA TO 100MA, RESISTANCE MEASUREMENT
2400-C	SOURCEMETER
7706	I/O MODULE, ACCESSORY TYPE:INPUT / OUTPUT MODULE, FOR USE WITH:KEITHLEY MODEL 2700, 2701, 2750 DMM DATA ACQUISITION DATALOGGING SYSTEMS, ROHS COMPLI
4200-Scs-Pk1	4200-SCS BUNDLE WITH (2) 4200-SMU, (1) 4200-PA, (1) 8101-PIV
2500int-2-Ge	INTEGRATING SPHERE, ACCESSORY TYPE:INTEGRATING SPHERE, FOR USE WITH:KEITHLEY MODEL 2502 DUAL PHOTODIODE METER, FEATURES:GERMANIUM DETECTOR, 2, ROHS C
2303	HIGH SPEED PRECISION READBACK POWER SUPPLY, 45W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:15V, OUTPUT CURRENT:5A, POWER R
2400-C-Uş	SOURCE METER, VOLTAGE CURRENT, 20W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:200MV TO
2016-P	AUDIO ANALYZING DMM W/9V SRC
7168	NANOVOLT SCANNER CARD
2001/Mem1	HIGH PERFORMANCE DMM W/32K MEM
	ELECTROMETER / HIGH RESISTANCE METER, DMM

6517b	TYPE:BENCH, VOLTAGE MEASURING RANGE DC:2V TO 200V, VOLTAGE MEASURING RANGE AC:2V TO 200V, CURRENT MEASURING
2602b	SOURCE METER, VOLTAGE CURRENT, 40.4W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE: 100MV
8010	TEST FIXTURE, 2675A SOURCE METER, ACCESSORY TYPE:TEST FIXTURE, FOR USE WITH:KEITHLEY 2657A SOURCE METERS
2401	SOURCE METER, DC VOLTAGE CURRENT, 22W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE: 200M
2502-U_s	AC/DC PICOAMMETER, BENCH, 2NA TO 20MA, AMMETER FUNCTION:AC / DC CURRENT, CURRENT MEASURING RANGE AC:2NA TO 20MA, CURRENT MEASURING RANGE DC:2NA TO 20M
2601b	SOURCE METER, VOLTAGE CURRENT, 40.4W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:100MV T
2220j-30-1	PROGRAMMABLE DUAL CHANNEL DC POWER SUPPLY FOR JAPAN
2636b	SOURCE METER, VOLTAGE CURRENT, 30.3W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:200MV T
2657a-Lim-3	LOW INTERCONNECT MODULE
2430cald	2430 CALIBRATED W/ DATA
26600-2	PICOAMMETER LOGARITHMIC 10 TO THE 12TH
6221	SOURCE METER, AC DC CURRENT, 11W, SOURCE METER FUNCTION:CURRENT SOURCE, OUTPUT POWER:11W, SOURCE CURRENT RANGE: 2NA TO 100MA, I-V ACCURACY MIN.:0
707b	6 SLOT SEMICONDUCTOR SWITCHING MAINFRAME
2410-C-U_s	HIGH VOLTAGE SOURCEMETER W/CONTACT CHECK
2304a	HIGH SPEED PRECISION READBACK POWER SUPPLY, 100W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:20V, OUTPUT CURRENT:5A, POWER
S46-Sp4t-Kit	SP4T RELAY AND CABLE ASSEMBLY
Ucpdisco-8	SCALE INTERFACE CARD

Kusb-3108	HIGH GAIN USB DAQ MODULE
2001/Mem2-Us	NON-SALEABLE, NON-CONFIGURED ASSEMBLED PRODUCT NOMENCLATURE, FOR MFG. USE ONLY, -2001/MEM2-US
Rsa6106b	REAL TIME SIGNAL ANALYZER, 9KHZ-6.2 GHZ, 40 MHZ ACQ. BW.
6167	GUARDED INPUT ADAPTER FOR MODEL 220
6485-Us	PICOAMMETER
6487/E	PICOAMMETER/VOLTAGE SOURCE @220V
2200-30-5	POWER SUPPLY, AC-DC, PROG, 0-30V, 5A, 150W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:30V, OUTPUT CURRENT:5A, POWER RATING
7712	RF SWITCHING MODULE, ACCESSORY TYPE:RF SWITCHING MODULE, FOR USE WITH:KEITHLEY MODEL 2700, 2701, 2750 DMM DATA ACQUISITION DATALOGGING SYSTEMS, FEAT
7020-D	DIGITAL I/O CARD, SWITCH MAINFRAME, ACCESSORY TYPE:DIGITAL I/O CARD WITH D SUB CONNECTORS, FOR USE WITH:KEITHLEY 7001 7002 SWITCH MAINFRAMES, ROHS C
7158	LOW CURRENT SCANNER CARD
2410-C	SOURCE METER
Pc9172	I/O DA DIGITAL ANALOG OUTPUT PC CARD
2430	SOURCE METER, DC VOLTAGE CURRENT, 1.1KW, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE: 20
7002	SWITCH MAINFRAME, 400-CH, 100MHZ, NO. OF CHANNELS:400, SAMPLING RATE:-, INPUT VOLTAGE MAX:250V, INPUT CURRENT MAX:1A, BANDWIDTH:100MHZ, EXTERNAL HEIGH
2701	DMM, DATA ACQ, DATALOGGING SYSTEM W/ 2 SLOTS, DMM TYPE:BENCH, VOLTAGE MEASURING RANGE DC:100MV TO 1000V, VOLTAGE MEASURING RANGE AC:100MV TO 750V, CUR
3706a	DMM, 7-1/2 DIGIT, DMM TYPE:BENCH, VOLTAGE MEASURING RANGE DC:100MV TO 300V, VOLTAGE MEASURING RANGE AC:100MV TO 300V, CURRENT MEASURING RANGE DC:10 A
2425	100 WATT SOURCEMETER
2611b	SOURCE METER, VOLTAGE CURRENT, 30.3W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:200MV T
	DMM, DATA ACQ, DATALOGGING SYSTEM W/ 2 SLOTS, DMM

2700	TYPE:BENCH, VOLTAGE MEASURING RANGE DC:100MV TO 1000V, VOLTAGE MEASURING RANGE AC:100MV TO 750V, CUR
7013-S	20 CHANNEL RELAY SWITCH CARD
2701/E	DMM/DATA ACQUISITION SYSTEM @ 220V
2001/Mem2	DMM WITH 128K MEMORY