



Keithley

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Keithley** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Keithley T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
2400 DIGITAL SOURCEMETER	
2400 Sourcemeter	
DAQ6510/7700+40 Channel Kart	DAQ6510/7700
KUSB-488B	
2410	
2450	
2612b-3y-Ew(Optiononly)	
2002/Mem1	
2001/Mem2-Us	
Pdma32	
6487-5y-Ew-Std	
8101-4trx	
3390	
C/7751-5y-Std	
2430caldu	2430 CALIBRATED W/ DATA + UNCERT

4288-7	
7012-S	4X10 MATRIX CARD
7754-3	
7020-D	
2425-C-Us	
2400 Newport Comerstone 260	
2790-L	
6517 B - Electrometer/ High Resistance Meter	
7045	
2001-M	DMM NAVY NSN7Z6625-01-425-9735
4200-Scs/F-Nosmu	SEMI CHARACTERIZATION SYST W/FPD, NO SMU
Cab-307	
1754	
Kusb-488b	
2600-Std-Res	CALIBRATION STANDARD 1G OHM RESISTOR
6485-3y-Ew-Std	
7072	8X12 SEMICONDUCTOR MATRIX CARD
M1151	
26600-1	
2636a	SOURCE METER, VOLTAGE CURRENT, 30.3W, SOURCE METER FUNCTION:CURRENT-VOLTAGE SOURCE / DMM / ELECTRONIC LOAD / POWER SUPPLY / WAVEFORM GENERATOR, SOUR
196dmm	MULTIMETER
130	
6487/E	
P/N 6011	
2790-H	SOURCEMETER SWITCH W/1 HI V CARD 10M OHM
5804	
2420 (Ex. 228a)	
7058	LOW CURRENT SCANNER CARD
617	
2612b	
7154-102-02c	
176	
Mb32-01	
2500int-2-Si	
2510	

2268-100-8	
C/2604b-3y-17025	
S2008033	
2461	
4804	
7702	DIFFERENTIAL MULTIPLEXER MODULE, ACCESSORY TYPE:DIFFERENTIAL MULTIPLEXER MODULE, FOR USE WITH:KEITHLEY MODEL 2700, 2701, 2750 DMM DATA ACQUISITION D
7024-10	
130130a	
7755	
7708	DIFFERENTIAL MULTIPLEXER MODULE, ACCESSORY TYPE:DIFFERENTIAL MULTIPLEXER MODULE, FOR USE WITH:KEITHLEY MODEL 2700, 2701, 2750 DMM DATA ACQUISITION D
2420-C	
2790-HI	
Kusb-3100	
2110-220	
2220j-30-1	
C/6517b-3y-17025	
2510-Rh	
2001-Tcscan	THERMCPL/GEN PURPOSE SCAN CARD
2306-Pj	BATTERY / CHARGER SIMULATOR, 15V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2, OUTPUT VOLTAGE:15V, OUTPUT VOLTAGE 2:15V, OUTPUT CURRENT:5A
2000-3y-Ew	
6221 Dc	
2600-Acs-Pk1	2636B BUNDLE WITH ACS BASIC EDITION, (1) 8101-PIV, (4) 4200-TRX-1, (1) KUSB-488B
7153-Trx	
2000-Us	HIGH PERFORMANCE 6-1/2 DIGIT DMM AND 1751 TEST LEADS
C/2000-3y-Data	
7751-Ew	
Mb-01	
3791-Cit	
S46-6666	S46 W/4-SP6T
Dda-06	
236-Ilc-3	

8606	
4200a-Scs	
4200-Man	
7152	
62202182a	SOURCE METER, DC CURRENT, 11W, SOURCE METER FUNCTION:CURRENT SOURCE, OUTPUT POWER:11W, SOURCE CURRENT RANGE: 2NA TO 100MA, RESISTANCE MEASUREMENT R
C/Data	
C/2110-5y-17025	
Kusb-3108	
2100/120cal	(PRICE/EA) CALIBRATED WITH CERTS, KEITHLEY P/N 2100/120 SKU # 59T7566
2200-20-5	POWER SUPPLY, AC-DC, PROG, 0-20V, 5A, 100W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:20V, OUTPUT CURRENT:5A, POWER RATING
2500int-2-Igac	
C/6514-3y-Std	
7708-5y-Ew-Std	
Sta-300	
708b	
2015	
Dda-08	
Mb36-04	
2000/2000-Scan	
7700-3y-Ew-Std	
Ctm-05	
2600-Triax	
7168	
7710	
3732-3y-Ew	
2182-Kit	
7011-S	QUAD 1X10 MULTIPLEXER CARD
7018-S-Nms	MULTIPLEXER 28 CHANNEL 3P MULTIPIN NO CONNECTOR
1507a	
7078-Trx-12	
2280s-60-3	
2500intfcpc	
Kusb-3102	MULTI-FUNCTION USB DAQ MODULE

7407402	
Das-8	
1753a	
2306-Vs	BATTERY / CHARGER SIMULATOR, 15V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2, OUTPUT VOLTAGE:15V, OUTPUT VOLTAGE 2:15V, OUTPUT CURRENT:5A
2001/Mem1	
Mb31-02	
7078-Trx-3	
Kpci-3116a	HIGH RESOLUTION MULTIFUNCTION BOARD
7009-5	
Mssr-32	
2100	
3750	
2600-Fix-Trx	
2000/E	
C/2602b-3y-17025	
2100/100	
8607	
3722mtc15mm	
2000-102-02f	
2110-240-Gpib	
Mb41-03	
2400-C-3y-Ew-Std	
2600-Kit	
S40-Q009-12	S40 Q009 W/OPTIONS
7011-C	
4288-5	
2790-3y-Ew-Std	
C/2604b-5y-17025	
6220-3y-Ew-Std	
62212182a	
7012-C	(PRICE/EA) 4X10 MATRIX CARD, ROHS COMPLIANT: NA
2600-Tlink	
Ca-563c	
S46-Sp6t-Kit-40	SP6T 40GHZ RELAY
	POWER SUPPLY, AC-DC, PROG, 0-32V, 3A, 96W, POWER SUPPLY

2200-32-3	OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:32V, OUTPUT CURRENT:3A, POWER RATING:
Ca-568-Xa	
Das1802hrda	METER
6487-3y-Ew-Std	
C/2420-3y-Std	
C/Newdata(Optiononly)	
2000-162-02f	
169	
7067	FOUR-WIRE SCANNER CARD
Shv-Ca-553-1	
7707	
2001-3y-Ew	
C/Newdataiso	
2110-220-Gpib	
130a	
S46-66665678a	S46 W/4-SP6T, 4-SPDT/RADIALL
3706a-Nfp	
6485	
3722mtc3mm	
C/2700-3y-Std	
6147	
Ctm-05/A	
S46l-LI00-0000a	1X12 MICROWAVE SWITCH SYSTEM
7015-St	
7174a	8X12 HI SPEED LO I MATRIX CARD
5806	
2107-30	
Hv-Cs-1613	
7173-50	
191refurb	
Mb38-07	
4200-Mtrx-2	
Pc8382	
Cab-305	
5805-12	

174	
7700	
Kpci-Pio24	
2000-20	DMM WITH 20 CHANNEL SCAN CARD
Dpp-45acp	
2440	SOURCE METER, DC VOLTAGE CURRENT, 55W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE: 200M
2790-Hh	
3723-St	
3720-St	
M1121	
7007-05	
2401	
3402-F	SIGNAL GENERATOR, 2-CHANNEL, SIGNAL GENERATOR TYPE:BURST / EXTERNAL WIDTH / PATTERN / PULSE, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTERNAL HEIGHT:87MM
2100/230-240	6 1/2 DIGIT DMM SET TO 230-240V
3722	MULTIPLEXER CARD, ACCESSORY TYPE:MULTIPLEXER CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:DUAL 1 48, HIGH DE
6524	SOFTWARE, ACCESSORY TYPE:SOFTWARE, FOR USE WITH:KEITHLEY MODEL 6517B ELECTROMETER / HIGH RESISTANCE METERS, FEATURES:HIGH RESISTANCE MEASUREMENT, ROHS
2420-Us	
8009	RESISTIVITY TEST FIXTURE
6220	
M53121	ENCODER
7712	
Cab-308	
707a	
3706a-5y-Ew	
263	CALIBRATOR/SOURCE
2231a-30-3	
3722-3y-Ew-Std	
2502-Us	
3401-R	SIGNAL GENERATOR, 1-CHANNEL, SIGNAL GENERATOR TYPE:BURST / EXTERNAL WIDTH / PATTERN / PULSE, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTERNAL HEIGHT:87MM
3722-Mtc-3	
6522-3y-Ew-Std	

Hv-Ca-571-3	
2303	
3402-R	SIGNAL GENERATOR, 2-CHANNEL, SIGNAL GENERATOR TYPE: BURST / EXTERNAL WIDTH / PATTERN / PULSE, SUPPLY VOLTAGE RANGE: 100V TO 240V, EXTERNAL HEIGHT: 87MM
Kpci-3104	
4200-Scs-Pk1	
Cab-1800/S	
8503	
2182a-Us	
Gm-Ps-6	
3730-3y-Ew-Std	
20002000scan	
6514-Us	
Pio-24	
7006-1	
2520kit1	
2001	
82790-9247/E	
2280-001	
5807-7	
Ssio-24	
4288-4	
7078-Pen	
6221/2182a/J	DELTA MODE SYSTEM @ 90V
3732-St-R	
2010-Us	DIGITAL MULTIMETER
2611a	
4299-4	
Pdis08	
85504a	
4200-Scs/C-Nosmu	SEMI CHARACTERIZATION SYST W/O FPD, SMU
2268-150-5	
S46-Tw	
Mb45-01	
7011-Mtc-1	
6011	

Hv-Ca-554-3	HV TRIAX CABLE, 3 M, MALE TO MALE
2000-Scan-20	
2410-C-Us	
2268-80-10	
Knm-Ps-Conn01	
Mb-Res20ohm	
2010-3y-Ew	
2602a	SOURCE METER, DC VOLTAGE CURRENT, 40.4W, SOURCE METER FUNCTION:CURRENT-VOLTAGE SOURCE / DMM / ELECTRONIC LOAD / POWER SUPPLY / WAVEFORM GENERATOR, S
Sta-Tc	
6487-Us	PICOAMMETER
C/2790-3y-Std	
Part No: 5806	
6482	
Mdb64	
S46t-Bb66uuuuuuuuua	S46 W/2-SP6T (T), 2-SP6T U/T 8-SPDT U/T
7705	
2657a-Pm-200	HI-VOLTAGE 200V PROTECTION MODULE
Pio-12	
775a	
7705-Mtc-2	
Knm-Dcv42	
Mb37-T	
872872a	
2700/E	
3300 Lcz	
2400 Sourcemeter	
2602b-5y-Ew	
2010/E	
73009445/J	
2302-Pj	BATTERY SIMULATOR, 15V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:15V, OUTPUT CURRENT:5A, POWER RATING:60W, INPUT VOLTAGE:
2290-5	
192	
871	

S40-Sq01	HYBRID REED RELAY CARD
3730	
2260b-80-40	
3730-St	
2401-3y-Ew-Std	
128	
D1541-96	
7002	
Exp-16	
7711-Bnc-Sma	
7709	MATRIX MODULE, ACCESSORY TYPE:MATRIX MODULE, FOR USE WITH:KEITHLEY MODEL 2700, 2701, 2750 DMM DATA ACQUISITION DATALOGGING SYSTEMS, FEATURES:6X8 MAT
Hv-Ca-554-X	
Sm-Idc5	
2260b-30-108	
6485/E	PICOAMMETER @220V
3721mtc15	
865	
7999-2c	
14242-2	
2182a	
248-Shv	
Rsa6106b	
2303-Pj	
7025-10	
2002-Us	
Ca-559-2a	
2000-20/E	
3706a-3y-Ew	
5808	
2400-Us	
3723-St-1	
26600-3	PICOAMMETER LOGARITHMIC 10 TO THE 13TH
Stp-37	
6514-5y-Ew-Std	
2015-P	AUDIO ANALYZING DMM

160	
871a	
8008	
4288-10	
7001	SWITCH MAINFRAME, 80-CH, 100MHZ, NO. OF CHANNELS:80, SAMPLING RATE:-, INPUT VOLTAGE MAX:250V, INPUT CURRENT MAX:1A, BANDWIDTH:100MHZ, EXTERNAL HEIGHT:
S46-Spdt-Kit-40	
2425-Us	SOURCE METER, VOLTAGE CURRENT, 100W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:200MV TO
C/6220-3y-Std	
820rb	
2268-20-42	
8010	
6167	
Kpci-3110a	
248/E	
3724-St	
2200-60-2	
2750-Us	
230	
6517b-Ilc-3	
7015-S	40 CHAN SOLID ST MULTIPLEXER
2015-P/E	
2750	
Sta-U	
2400-Lv-Us	
17501	
2110-100	
4299-5	
2510-At	
2200-30-5	
179a	
2400-Ccald	2400-C, CALIBRATED, WITH CERT AND AS FOUND AND AS LEFT DATA IS PROVIDED TO THE CUSTOMER (Z540)
6514/E	ELECTROMETER AT 220V
3401-F	

M1000	
2260b-800-1	
236	
2601a	SOURCE METER, DC VOLTAGE CURRENT, 40.4W, SOURCE METER FUNCTION:CURRENT-VOLTAGE SOURCE / DMM / ELECTRONIC LOAD / POWER SUPPLY / WAVEFORM GENERATOR, S
17502-5	
C/2182a-5y-17025	
428prog	
2601b	
3722-3y-Ew-Std(Optiononly)	
1600a	
C/2110-3y-Std	
3740	GENERAL PURPOSE CARD, ACCESSORY TYPE:GENERAL PURPOSE CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:32 INDEPEN
6430	
2016-P/E	
2303-Nms	
7011-R	
7752	
4288-9	
869	
708a	SINGLE SLOT SWITCHING MATRIX MAINFRAME
2400-5y-Ew-Std	
2510-Cab	
2016/E	THD 6.5 DIGITAL MULTIMETER @ 220V
2182a-5yr-Ew	
7790	
7035-5y-Ew-Std	
Hv-Ca-554-.5	
Pc9532	
2260b-80-13	
7633	
2260b-800-2	
7006-2	
261	
2430-C	SOURCEMETER

78500-9244/G	
2110-120	
S46-66665678	
175175a	MULTIMETER
614	
2450-Ecvcube	
2500int-Sma	
Tr280d	
2400-Lv	(PRICE/EA) LOW VOLTAGE SOURCEMETER
Usb-B-1	
3323a	
500p-2-Main	
7788	
Sm-Odc5	
C/Newdata	
C/6517b-3y-Data	
4200_Scs	
Sta-1800hc	
4210-Cvu	4210 CAPACITANCE VOLTAGE UNIT 1KHZ-10MHZ
2230g-30-1	
5805	
2260b-30-72	
8696	
Kusb-3116	(PRICE/EA) 16-BIT PERFORMANCE USB MODULE
3790-Kit50-R	
8010-Dtb-220	
7002-Rmk-1	
2230-30-1	DC POWER SUPPLY, PROGRAMMABLE, TRIPLE OUTPUT, 90W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:3, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:30
2425-C	
Kusb-3160	
4225-Pmu	
2600-Ban	
N5-0233-0000	
2651a-Kit-3	

6485-5y-Ew-Std	
Kpci-488lpa	
248-Mhv	
Pio96j	
237	VOLTAGE SOURCE PROGRAMMABLE 125/250VAC
2306-Ua	
2110-240	
7053	HIGH CURRENT SWITCH CARD
3721	
6517-Tp	
Acs-Basic	ACS BASIC EDITION SOFTWARE FOR COMPONENT TEST
2281s-20-6	
Stp-100	
Stp-100u	
2635b	
237-Alg-2	
2520	
7024-3	
7036	40 CHAN SINGLE POLE RELAY CARD
2308	PORTABLE DEVICE BATTERY / CHARGER SIMULATOR, 15V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2, OUTPUT VOLTAGE:15V, OUTPUT VOLTAGE 2:15V, OUT
2304-Disp	
7002-5y-Ew-Std	
Lcz Meter	
6522	SCANNER CARD, ACCESSORY TYPE:SCANNER CARD, FOR USE WITH:KEITHLEY MODEL 6517B ELECTROMETER / HIGH RESISTANCE METERS, FEATURES:10-CHANNEL, LOW CURRENT,
2425	
7708-3y-Ew-Std	
2260b-80-27	
7007-4	
6146	
Pdiso-8	
C/6485-3y-Std	
2302	
C/2790-5y-Data	
2430	

182	
Das-802	
2700/7700/E	DMM/DATA ACQUISITION SYSTEM W/20 CH MULTIPLEXER
C/Tracechart	
7707-Mtc-2	
8681	
2410-C	
S46-Sp4t-Kit	
Dac-02	
2306-Disp	
M1141	
2288	
195a	MULTIMETER 5.5 DIGETS
7401	
873f	
Shv-Ca-553-3	
Rel-16/W	
2636b	
6221-3y-Ew-Std	
61600-9252/B	
2016	
2635a	SOURCE METER, VOLTAGE CURRENT, 30.3W, SOURCE METER FUNCTION:CURRENT-VOLTAGE SOURCE / DMM / ELECTRONIC LOAD / POWER SUPPLY / WAVEFORM GENERATOR, SOUR
6517b/E	
616	
706	
2604b	SOURCE METER, VOLTAGE CURRENT, 40.4W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:100MV T
7056	
2611b	
4299-6	
2306	BATTERY / CHARGER SIMULATOR, 15V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2, OUTPUT VOLTAGE:15V, OUTPUT VOLTAGE 2:15V, OUTPUT CURRENT:5A
2260b-30-36	
175a	

3791-Kit78-R	
172	
199	
2750/E	
2410-Us	
Mb31-05	
194	
2220-30-1	POWER SUPPLY, BENCH, DUAL RANGE OUTPUT, 90W, POWER SUPPLY OUTPUT TYPE:FIXED, NO. OF OUTPUTS:2, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:30V, OUTPUT C
2440-5y-Ew-Std	
Stp-36	
4225-Rpm	
2502	
3732	MATRIX CARD, ACCESSORY TYPE:MATRIX CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:QUAD 4 28, ULTRA-HIGHDENSITY
2220g-30-1	
197	
2500intfcapc	
2260b-250-4	
2100120	
Kickstartfl-Hrma	
2001/Mem2	
Mbus-Pwr-Euro	
3731	MATRIX CARD, ACCESSORY TYPE:MATRIX CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:6 16, HIGH SPEED, REED RELAY
7797	
7711	
Ca-18-1	
6220-Us	
2260b-800-4	
2290-10	2290-10 10kV Power Supply
2000-Scan	
She-1101	
2268-40-21	
Mb31-03	
175av	

5801	
237-Trx-Tbc	
S1600	
Ctm-10/05a	
2260b-250-9	
Shv-Ca-553-2	
2420	
6517b-3y-Ew-Std	3 YEAR KEITHLEYCARE GOLD PLAN
4801	
2000-112-02d	
5809	
2187-4	
707b	
Das-16	
Stc-37	
S46t-Spdt-Kit-26t	
Cab30	
2000-Ew	
2500int-4-Ipg1	
Mb38-02	
2110-120-Gpib	
M1541-96	
7700-Ew	
2604b-5y-Ew	
S46-Spdt-Kit	
2410-5y-Ew-Std	
Mb38-05	
6221-Us	
2410	
7706	
Dmm7510	
2510-3y-Ew-Std	
8605	
Cab-1284cc-2	
3720-Mtc-3	

7011-Mtc-2	
Mb45-02	
7999-5	
She-1103	
6521	
7014	
Das-801	
7002-Hd	
2002	
Ca-559-0a And Ca-559-2a	
580	
2450-Ec	
7079	
7153	MATRIX CARD, 4X5, 2POLE, 1.3KV SWITCH, ACCESSORY TYPE:MATRIX CARD, FOR USE WITH:KEYSIGHT MODEL 237 SIMILAR SOURCE MEASURING UNITS, ROHS COMPLIANT: N
3706-Bkpl	
7001-5y-Ew-Std	
237-Alg-2	
7999-3	
Ca191	
Keithley-4200a-Scs-Nicht-F3;R-Den-Wiederverkauf-Istanbul-Turkiye	
6172	
6221/2182a-Uş	DELTA MODE SYSTEM
487	
Probe For 6487	
Mb-05	
7702-5y-Ew-Std	
2602a-3y-Ew	
3720	MULTIPLEXER CARD, ACCESSORY TYPE:MULTIPLEXER CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:60 DIFFERENTIAL CH
197a	
3732-Mtc-1.5	
S40-P011	
3706-Ban	
S46-66661234a	

1701b	
Hv-Ca-554-1	
8009 - Resistivity Test Fixture	
She-1102	
7020	
8680	
2401.-Us	
S46-666612345678a	
2634b	SOURCE METER, VOLTAGE CURRENT, 30.3W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:200MV T
Sta-16	
7073	
Mb39-01	
4803	
2440-C	5A SOURCEMETER WITH CONTACT CHECK
6220-Westinghouse	
Lr:8028	
2000-Benchkit	
6514	ELECTROMETER, 20PA TO 20MA, 2V TO 200V, DMM TYPE:BENCH, VOLTAGE MEASURING RANGE DC:2V TO 200V, VOLTAGE MEASURING RANGE AC:2V TO 200V, CURRENT MEASURIN
7023	
8610	
2790-A	SOURCEMETER SWITCH W/1 HI V CARD 1M OHM
7065	
Keithley 2400	
Mb41-02	
27007700	DMM / DATA ACQUISITION, 6-1/2 DIGIT, DMM TYPE:BENCH, VOLTAGE MEASURING RANGE DC:100MV TO 1000V, VOLTAGE MEASURING RANGE AC:100MV TO 750V, CURRENT MEAS
4802-10	
6485-Us	
C/2410-3y-17025	
2015/E-Nok	
7111-S	
1685	
2002/Mem2	8.5D DMM W/128K MEMORY
She-1100	

2001-Scan	
2614b	SOURCE METER, VOLTAGE CURRENT, 30.3W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:200MV T
7013-S	
2182a-3y-Ew	
2303-Nms-22741	
C/3390-3y-Std	
2100-3y-Ew-Std	
6517	
6221/2182a:2182a-3y-Ew-Std	
2600-Alg-2	
2002/Mem2-Us	8.5D DMM W/128K MEMORY
874f	
3732-St-C	
7751	
14308b2	
2420-3y-Ew-Std	
2700-3y-Ew	
4200-Scs/F	SEMI SYSTEM W/2 MPSMU FPD
Sta-08	
Das-1802st-Da Obsolete	
Kpci3160	
2612a	
7007-2	
2000	
2651a	
7078-Trx-1	
611009301/F	
7078-Trx-5	
6517a Obsolete/Replacement 6517b	
6517-Rh	
4299-1	
Sw433	
2520int-1-Ge	
7158	

2260b-250-13	
2015/E	
169-Dmm	
6487	PICOAMMETER / VOLTAGE SOURCE, DMM TYPE:BENCH, CURRENT MEASURING RANGE DC:2NA TO 20MA, NO. OF DIGITS / ALPHA:5-1/2, DMM RESPONSE TYPE:TRUE RMS, RANGING
3722mtc15	
2280s-32-6	
610	
1651	
2657a	
Dda-08/16	
Mb40-02	
7001-3y-Ew-Std	
2440-U_s	
4299-3	
Lsi22	
840a	
7078-Trx-Gnd	
C/2604b-5y-Data	
S46-4400123456a	
2182a/E	
2600-Iac	
4200-Scp2-3y-Cal	
6221	
Kpc1-3110	
2304a	
740	
2268-60-14	
Pio-Hv	
C/2182a-3y-Std	
237-Bnc-Trx	
6517-Ilc-3	
7018-S	
7154	SCANNER CARD 10-CH HIGH-VOLTAGE 1100V 2POLE
7703	
C/2182a-5y-Std	

2200-30-5-Ew	
3721-Mtc-3	
2400-Intrk	
7753	
2107-50	
2000/E/2000-Scan	
2400	
02500-0700-0003	
6011-10	
3724	MULTIPLEXER CARD, ACCESSORY TYPE:MULTIPLEXER CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:DUAL 1 30, FET, RO
3740-St	
775a5152	
Mssr-32-14071-Pc6432	
C/6487-5y-17025	
Mb47-K-05	
Ucpdisco-8	
2001-Uş	
2602b	
6220/2182a-Uş	
Stp-50-C	
4180	
Model 2401	
7078-Trx-20	
8502	
2010	
50013202caim1	
2700	
Hv-Ca-554-1	
3706a-S	
Ot-2000-3-12812-D	
2700-5yr-Ew	