

Keller Druckmesstechnik

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Keller Druckmesstechnik Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Keller Druckmesstechnik T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
PA-21Y 22-2155-154 400bar	Piezoresistive pressure transmitter Product no. 222155.0019 Pressure 0 ... 400bar Output signal 4 ... 20mA Pressure connection G1 / 4 Electrical connection mPm-393 Total error band [% FS] 1 Linearity Lbfsl [% FS] 0.5 Supply 8 ... 32V Comp. Temperature range 0 ... 50 ° C
PA-21Y / 10bar / 22-2155-143	Piezoresistive pressure transmitter Product no. 222155.1136 Pressure 0 ... 10bar Output signal 4 ... 20mA Pressure connection G1 / 4 Electrical connection DIN43650 Total error band [% FS] 1 Linearity Lbfsl [% FS] 0.5 Supply 8 ... 32V Comp. Temperature range 0 ... 50 ° C Inkl. Kabeldose
PA-21Y / 400bar / 22-2155-154	Piezoresistive pressure transmitter Product no. 222155.0353 Pressure 0 ... 400bar Output signal 4 ... 20mA Pressure connection G1 / 4 Electrical connection mPm-393 Total error band [±% FS] 1.5 Linearity Lbfsl [±% FS] 0.5 Supply 8 ... 32V Comp. Temperature range -10 ... 80 ° Incl. Cable socket
LEO2 / 11bar / 03-00109-03	Digital manometer Product no. 303010.0015 Pressure 0 ... 11bar abs Output / supply 3V batt. Pressure connection G1 / 4 Accuracy RT [% FS] 0.1 Comp. Temperature range 0 ... 50 °

C	
Gsh LEO1/LEX1/LEO Rec	Protective rubber cover 309030.0002 Material NBR Abmasse Ø85x50mm
Protective bag	309030.0003 Dimensions 140 x 85 x 40mm
0-6 bar 4-20 mA 24 V DC	Transmitter
0-10 bar 4-20 mA 24 V DC	Transmitter
222508.0058	PR-25Y / 0,25bar / 81620.55 Piezoresistive pressure transmitter Pressure 0 ... 0.25bar Output signal 4 ... 20mA Pressure connection G1 / 2 Electrical connection DIN43650 Total error band [±% FS] 1.8 Linearity LbfsI [±% FS] 0.5 Supply 8 ... 32V Comp. Temperature range -10 ... 80 ° C Incl. Cable socket
222155.0271	Transmitter Product no .: 222155.1238 Pressure: 0 ... 16bar Output signal: 4 ... 20mA Pressure connection: G1 / 4 external thread Electrical connection: 2m permanently connected Total error band [±% FS]: 1.50 Supply: 8 ... 32VDC Comp. Temperature range: -10 ... 80 ° C Linearity LbfsI [±% FS]: 0.50
PR-23SY / 0,1bar / 81549.33	Piezoresistive pressure transmitter Product no. 222308.3239 Pressure 0 ... 0.1bar Output signal 4 ... 20mA Pressure connection G1 / 4 Electrical connection mPm-393 Total error band [±% FS] 3 Linearity LbfsI [±% FS] 1 Supply 8 ... 32V Comp. Temperature range 0 ... 50 ° C Incl. Cable socket
PA 21Y/ 22-2155 154 400 BAR	
PR-21Y / 4bar / 22-2155-142	Piezoresistive pressure transmitter Pressure 0...4 bar Output signal 4...20mA Pressure connection G1/4 Electrical connection mPm-393 Supply 8...32VDC Compensated temperature range -10...80°C Total Error Band [±%FS] 1.5 Nonlinearity BFSL [±%FS] 0.5 Incl. cable box
PR-21Y / 10bar	output signal 0/10 V DC electrical connection 24 V accuracy ±0,5 %FS Temperature range -40/+100 °C
PA-21Y / 400bar	output signal 0/10 V DC electrical connection 24 V accuracy ±0,5 %FS Temperature range -40/+100 °C
PA-21Y / 1+5bar	output signal 0/10 V DC electrical connection 24 V accuracy ±0,5 %FS Temperature range -40/+100 °C
Model PR-25Y / 0.2 bar / 81620.66 [222508.0279]	
PR-36X / 45mH2O / 03-00007-02	233605.0743 Piezoresistive pressure transmitter Pressure 0...45mH2O Output signal 4...20mA, RS485 Electrical connection 50m Power supply 8...32VDC Comp. temp. range 0...50°C Standard range (FS) [bar] 10 Error band [±%FS] analogous to 0.15 Error band [±%FS] digital 0.1 test protocol
PAA-23SY / 400bar / 81596.55	Piezoresistive pressure transmitter Pressure 0...400 bar abs Output signal 4...20mA Pressure connection 1/4-18NPT male Electrical connection DIN43650 Power supply 8...32VDC

	Comp. temp. range -10...80°C Total Error Band [±%FS] 0.7 Linearity LbfsI [±%FS] 0.25 Seal PTFE Incl. cable box
PAA-23SY / 400bar / 81592.55	Piezoresistive pressure transmitter Pressure 0...400 bar abs Output signal 4...20mA Pressure connection G1/4 Electrical connection DIN43650 Power supply 8...32VDC Comp. temp. range -10...80°C Total Error Band [±%FS] 0.7 Linearity LbfsI [±%FS] 0.25 Seal PTFE Incl. cable box calibration card
PAA-23SY/40 Bar 4-20 mA signal output	Piezoresistiv Absolute Pressure Transmitter with G ¼" male thread connection (PTFE Gasket)
PAA-25Y / 100bar / 81620.55	Piezoresistive pressure transmitter Pressure 0...100 bar abs Output signal 4...20mA Pressure connection G1/2 Electrical connection DIN43650 Power supply 8...32VDC Comp. temp. range -10...80°C Total Error Band [±%FS] 0.7 Linearity LbfsI [±%FS] 0.25 Seal PTFE Incl. cable box
REFLECTOR PR-25	
REFLECTOR PR-25D	
REFLECTOR PR-34	
HL1802E-ADAPTR-PR	REFLECTOR PR-ADAPT
0-10 BAR 4-20mA PA-21Y	
PA-23SYEi/10 bar	
PA-23SY / 400bar / 81593.55	Piezoresistive pressure transmitter Pressure 0...400 bar Output signal 4...20mA Pressure connection G1/4 Electrical connection DIN43650 Power supply 8...32VDC Comp. temp. range -10...80°C Total Error Band [±%FS] 0.7 Linearity LbfsI [±%FS] 0.25 Incl. cable box calibration card
PA-21Y/22-2155	0-16 BAR
PR-23SYEi / 4bar / 81811.05	222309.0058 Pressure 0...4 bar Output signal 4...20mA Pressure connection G1/4 Electrical connection DIN43650 Supply 10...30VDC Compensated temperature range - 10...80°C Total Error Band [±%FS] 0.7 Nonlinearity BFSL [±%FS] 0.25 Ex II 1 GD Ex ia IIC T6 ... T4 Ga Ex ia IIIC T 130°C Da IBExU 10 ATEX 1124 X IECEx IBE 14.0044 X ExV 21UKEX1017X Incl. cable box Operating instructions (incl. CE declaration of conformity) calibration card
PAA-23/20 Bar	Green O-Ring with DIN 3869 M14x1.5 FPM Model
PAA-21Y/22-2155-142	NOTE: Range 0..4 bar abs (must be the model that specifically says abs)
PD-33X	
PRD-33X	
PA-21Y/81562.22 ITT	
	PAA-23 / 100bar / 8465.1 Pressure 0...100bar abs Output signal 0...10V Pressure connection G1/4 Electrical connection

222305.2922	DIN43650 Supply 13...32VDC Compensated temperature range -10...80°C Non-linearity Lnorm [±%FS] 0.5 Incl. cable socket Calibration protocol
Pressure Sensor	
222305.3225	PAA-23 / 250bar / 8465.1 Pressure 0...250bar abs Output signal 0...10V Pressure connection G1/4 Electrical connection DIN43650 Supply 13...32VDC Compensated temperature range -10...80°C Non-linearity Lnorm [±%FS] 0.5 Incl. cable socket Calibration protocol
222305.2624	PAA-23 / 20bar / 8465.1 Pressure 0...20bar abs Output signal 0...10V Pressure connection G1/4 Electrical connection DIN43650 Supply 13...32VDC Compensated temperature range -10...80°C Non-linearity Lnorm [±%FS] 0.5 Incl. cable socket Calibration protocol
303025.0005	Digital pressure gauge LEO record / 1000bar / 03-00206-04 pressure range 0...1000 bar pressure connection G1/4 male Compensated temperature range 0...50°C Accuracy @ RT [±%FS] 0.05 Total error band [±%FS] 0.1 RS485 interface Supply 3.6V battery storage locations 57000 Operating instructions including CE declaration of conformity
309030.0002	rubber protective cover Gsh LEO1/LEX1/LEO Rec Material NBR dimensions Ø85x50mm
309030.0003	protective bag Dimensions 140 x 85 x 40mm
309010.0075	USB converter K-114-A Incl. USB cable
PR-25Y/0.2bar /81620.66	
Pa-21r/250/80 853.3	
Pa-21sr/80520 - Replaced By Pa-21y / 16bar / 81554.55	
Pa-21sr/16/80520.3	
Pa-21sr /200bar/ 80520.5	
Pa-22s	
Ptx 1400 / 0-25	
Pa-21sr/16 Bar 5-20 3271-0010-Nk 700cm 2,2-3,3 Bar	
Pa-21sc Obsolete New Pa-21y / 100bar / 81689.33	
Pr-21sr/16/81520.5	
Pa21sr/16bar/81520.5 - Replaced By Pa-21y / 16bar / 81554.55 Keller Druckmes	
Pa -21mc/30 Bar 80 407.33	

Pr-250806220.55	
Pa-21y / 25bar / 22-2155-143	Produktenr. 222155.1360 Pressure 0 ... 25bar Output signal 4 ... 20mA Pressure connection G1 / 4 " Electrical connection DIN43650 Total error band [% FS] 1 Linearity LbfsI [% FS] 0.5 Power 8 ... 32V Comp.Temperature range 0 ... 50 ° C Incl. cable box
21y/100 Bar Drucksensor	K¼nnen Sie sowohl f¼r 1/4 "BSP-Gewinde als auch f¼r 1/4" NPT-Gewinde anbieten?
222508.0634	
Pa21sr/16bar/81520.5 - Replaced By Pa-21y / 16bar / 81554.55	
Pa-21sr/25/80520.5	
Pa-25y /250 Bar / 80087.55 - Obsolete , Replaced By 222508.0634	
222155.0307	