

## Kiesel

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Kiesel** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Kiesel T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">12098</a>	
<a href="#">28726</a>	
<a href="#">2925</a>	
<a href="#">3025</a>	
<a href="#">3043</a>	
<a href="#">3064</a>	
<a href="#">3066</a>	
<a href="#">47943</a>	
<a href="#">59608</a>	
<a href="#">701509</a>	
<a href="#">701612</a>	
<a href="#">704463</a>	

<a href="#">708621</a>	
<a href="#">712050</a>	
<a href="#">9323</a>	
<a href="#">Model SP45M.V</a>	
<a href="#">Model SP4M.V</a>	
<a href="#">SP03</a>	
<a href="#">SP04 2.0m3</a>	
<a href="#">SP3, 4915-2017</a>	Stator SP 03/1 PU Blue St.-lackiert, FDA konform 65 shore
<a href="#">S-10-110-04p</a>	
<a href="#">Sp/10fb011.403/1.4</a>	
<a href="#">N-05-130-04c</a>	
<a href="#">Sp 03 Sr</a>	
<a href="#">Din3770-63x4.5</a>	
<a href="#">3043 Kiesel-Impeller Ip 30 Cr, Va I30400029 (Art.-Nr. 3043)</a>	
<a href="#">9323, Type Sp 03/1</a>	
<a href="#">Din3770-53x4</a>	
<a href="#">Kst 1.4435</a>	
<a href="#">62250</a>	
<a href="#">701613</a>	
<a href="#">7886 Scharnier</a>	
<a href="#">N-01-044-11s</a>	
<a href="#">701616</a>	
<a href="#">Stator Sp 45/1 Epdm ,Art.Nr.6820</a>	
<a href="#">56518</a>	
<a href="#">N-01-044-10s</a>	
<a href="#">Ip 15</a>	
<a href="#">3022</a>	
<a href="#">S-10-105-04c</a>	
<a href="#">Rg1, Ce Ex Iii3c3, P/N: 1686/2005 Ce</a>	
<a href="#">2956</a>	

<a href="#">701606</a>
<a href="#">Sp10f</a>
<a href="#">26111 Satz Mechanische Dichtung</a>
<a href="#">9093</a>
<a href="#">3066 Stator</a>
<a href="#">N-05-130-05c</a>
<a href="#">Sp 24/1* 2997</a>
<a href="#">701605</a>
<a href="#">14387 O-Ring</a>
<a href="#">Universa Sp-10-Sr-H</a> <p>Stainless steel progressing cavity pump Model: UNIVERSA SP-10-SR-H 1-stage block design EHEDG version general operating conditions: Positioning: horizontal Site: in the building Ambient temperature: approx. 20 ° C assumed Humidity: up to 50% Material and execution: Housing: chrome nickel steel Wst. 1.4301 polished Rotor: chrome nickel steel Wst.1.4301 polished, hollow, low vibration Rotating parts: chrome nickel steel Wst.1.4301 polished Stator: HNBR (FDA-compliant), max. Solid-dia. 20 mm Joints: Cardan joints openly polished Surface Product contact: Ra &lt;0.8 µm Shaft seal: Single-acting slide ring MP W1 / B Input side: external thread DN 50 DIN 11851 Outgoing side: external thread DN 50 DIN 11851 Construction: Basic frame Wst. 1.4301 Paint: white RAL 9001 Performance specifications: Medium: cream (assumed 30-50% fat) Viscosity: 15 - 115 mPas accepted Temperature: max. 80 ° C Suction height: approx. 5 mWs Pressure height: max. 6 bar Flow rate: approx. 6.0 m³ /</p>
<a href="#">S-10-106-15c</a>
<a href="#">N-01-044-09s</a>
<a href="#">16038</a>
<a href="#">Sp/10fb011.403/1.4301/2436</a>
<a href="#">Pumpe Sp03</a>
<a href="#">2908</a>
<a href="#">708080</a>
<a href="#">3046 Satz Gleitringdichtungen</a>
<a href="#">33876 O-Ring</a>
<a href="#">61408 O-Ring</a>
<a href="#">S-10-120-01a</a>

[707801](#)