

Kistler



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Kistler Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Kistler Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
5073A111	18004735 ICAM - Programmable, industrial course 1-channel, BNC input connector - Measuring range: $\pm 100 \dots 1\,000\,000$ pC - Number of channels: 1 - Charge input: BNC neg. - Output signal: -10 ... 10 V - Interface: RS-232C
9257B	Piezo multicomponent dynamometer Measuring range Fz - 5 ... 10 kN - Measuring range Fx, y: -5 ... 5 kN - Measuring range Fz: -5 ... 10 kN - Dimensions cover plate LxW: 100x170 mm - Connection: Fischer flange 9-pin neg.
TYPE 8330B3 ServoK-Beam Accelerometer -	- Force Feedback Capacitive Accelerometer
2151B60154002	NC joining module NCFH with hollow shaft motor and compact design Integrated piezoelectric force sensor including charge amplifier and Absolute displacement encoder Measuring direction pressure / tension Measuring range 1: 60 kN Measuring range 2: 15 kN Stroke: 400mm Path repeatability: 0.01 mm Max. travel speed: 300 mm/s With holding brake Wall and flange mounting
Type:9211	
18000522	
PAAE618699	
ISS-20-30-1-A	Inductive analog sensor Type: ISS-A series with integrated amplifier Circuit type: analog output 0 - 10 V Linearity range: 0.5 - 2 mm Measurement distance (Se ST 37): 1.25 mm Dimensions: 30 x 20 x 8mm Connector: M8 3-pin.
PSI-40-40/3-P	Single-beam infrared fork light barrier Type: PSI 8mm series with integrated amplifier Circuit type: PNP constant light trigger Switching function: light / dark switching Fork width: 40 mm Fork depth: 40mm Connector: M8 3-pin.

4501A	
9129AA	Piezo multi-component dynamometer Measuring range - 10 ... 10 kN - Measuring range Fx,y: -10 ... 10 kN - Measuring range Fz: -10 ... 10 kN - Dimensions cover plate LxW: 90x105 mm - Connection: Fischer flange 9-pin neg.
Application advice	Depending on the application, approx. 4 days on site plus travel expenses
INSTRUMENT TYPE:5038A2YO463	CONSISTING OF 5038A2 WITH 4PG9 THREAD HOLDES INPUT RESISTOR 15 MOHM 5.730.419 FOR ALL CHANNELS.4 COUPLING TYPE1900A 3 MOUNTED AND CONNECT TO AMPLIFIER(2BY2) 1 CHASSI SOCKET 1500A59 MOUNTED ACCESORY 1 PLUG 1500A57 LABELIN ON TOP PLATE CHANNEL1=RANGE 1000N ADJUSTED TO MEAN SENSITIVITY OF TYPE 9341SN../SN.. CHANNEL 2=RANGE 500N ADJUSTED TO MEAN
9257B	18007542 Piezo multi-component dynamometer Measuring range Fz - 5 ... 10 kN - Measuring range Fx,y: -5 ... 5 kN - Measuring range Fz: -5 ... 10 kN Dimensions cover plate LxW: 100x170 mm - Connection: Fischer flange 9-pin neg.
LOADCELL JUNCTION BOX PCB 63-1135-01/03	
application advice	90000011
TYPE 7513A	
ISS 20-30-1	
4097Q02-SN4520683,	
6157C Quartz Pressure Sensor	
6192B K-type Thermocouple	
Ascenix ADCR	
ADCR ATL4-0lot	
6157CAUMRKF	1,0
6192BGSP2,0	k-type 4mm ,2m S102 2-pin
5074B211	dICA - digital industrial LV with Industrial Ethernet - Measuring range: ±20 ... 1 000 000 pC - Number of channels: 2 - Charge input: KIAG 10-32 neg. - Interface: EtherCat
18005972	6215 Quartz crystal high pressure sensor, M10 x 1 For ballistic applications Nominal pressure range 6 000 bar Front sealing Incl. 1063, 10x 1100
18000528	1631C5 High temperature connection cable, KIAG 10-32 pos. - BNC pos., l = 5 m
	2180ANCFN0300SB Servo amplifier for NCFN 300 kN IndraDrive 100 A Interface: Sercos III Integrated Safety

18029231	Technology S4 (up to PL e) Functions: SMES, SMST2, SMM1 safety zone box Mains filter and choke: HNK01.1A-A075-E0080-A-500 Braking resistor: HLR01.1N-0470-N11R7-A-007 Firmware MPB-18
18025912	2151B10052001 NC joining module NCFH with hollow shaft motor and compact design Integrated piezoelectric force sensor including charge amplifier and absolute position encoder measuring direction compression / tension Measuring range 1: 10 kN Measuring range 2: 5 kN stroke: 200 mm Path repeatability: 0.01 mm Max. travel speed: 300 mm/s With holding brake wall and flange mounting
18032002	5847B0 maXYmos NC for monitoring and control of NC joining modules - 128 independent programs with up to 10 evaluation elements through various types with online and offline evaluations - Integrated sequence control for highest flexibility - Real-time behavior through Sercos III control of the servo amplifier - 5000 curve memories, 8 000 measured value memories - Statistics and logging of measurement results (Q-DAS®, CSV, PDF, XML, IPM 5.0, QDA9) Consisting of: Measurement and Evaluation Module (MEM) connection options - Channel-Y: Piezo, DMS, Active ±10 V - Channel-X: Servo, Incremental, SSI, Potentiometer, ±10 V, inductive - Fieldbus: PROFIBUS DP, PROFINET, EtherNet/IP, EtherCAT - Network: Ethernet (TCP/IP) - USB
18025908	2151B05012001 NC joining module NCFH with hollow shaft motor and compact design Integrated piezoelectric force sensor including charge amplifier and absolute position encoder measuring direction compression / tension Measuring range 1: 5 kN Measuring range 2: 1 kN stroke: 200 mm Path repeatability: 0.01 mm Max. travel speed: 300 mm/s With holding brake wall and flange mounting
18032002- 5847B0	5847B0 maXYmos NC for monitoring and control of NC joining modules - 128 independent programs with up to 10 evaluation elements through various types with online and offline evaluations - Integrated sequence control for highest flexibility - Real-time behavior through Sercos III control of the servo amplifier - 5000 curve memories, 8 000 measured value memories - Statistics and logging of measurement results (Q-DAS®, CSV, PDF, XML, IPM 5.0, QDA9) Consisting of: Measurement and Evaluation Module (MEM) connection options - Channel-Y: Piezo, DMS, Active ±10 V - Channel-X: Servo, Incremental, SSI, Potentiometer, ±10 V, inductive - Fieldbus: PROFIBUS DP, PROFINET, EtherNet/IP, EtherCAT - Network: Ethernet (TCP/IP) - USB
5847B0	
1631C5	
FORCE SENSOR M10X1 9217A	
3.220.139	
KIAG 10-32 5M 1641B5	
6021A	

5181A
Ksm036448
18006740
4740awy2x0b4
18000582
5037b3211
1603bz
5038a1
1939a1
Ksm301660-5
18025926
1939a3
18001539 2516b10
9215a
1635cspo.5
00052101
18025985
1603b2
5125c1
5995a
44000178
4740aey2x0b4
18025989
1700a111a2
9101a
4740aey1x0b4
1633csp16m
18028885
45326
18007651 9313aa2

18008983
18007841 9500a01
18026095
1700a111a2 Replaces Type 1500b15
18029223
18007542 9257b
Ida 354-5c-S78b
9333a
Ksm313720-5
18009072
18010639 5134b1(E)
1500a57
88102-1000hz
Ksm036457-5
18005348
1609b2
5027a12j-500n/Fs
Transmitter For 6652ci39a1q01
18008896
516157ba6457
1635c
18007197, 9124b1011
Kig 10-32 Neg 1307 24 1631c5
6457
1500as7
1651c5
1900a3
Integrated Cable With Sensor For 6652ci39a1q01
18000590
18029160

2516b11
1687b5
Art. Nr. 18007552 , Type 9272
10 U
5039a221
18005236
4734awdy2x400s1
1411a
5073a111
5027a2(500m)
18005274
18005753
2p10a10ka
18004872, 5223b1
1943a2
Cat1401
1662asp015
18004711 5070a11100
18004871, 5221b2
18025915
Tp6157a
18028884
5027a12
18000617 1677a5
5361a
18029580
5867b0000
1633c1
Cat6157
18026545
1631c3

18009139
18010953 8688a50
Ksm036438
Model: 9125a
18004238
1667b2
Cat6457
18007552 9272
2112a27
18029161
28820/A400
18009065
18009088
18004220
7613ca
18007353, 9165