

Kistler Morse

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Kistler Morse Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Kistler Morse T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
2HTJ60CW001	BICARBONATE SILO WEIGHT SVS2000
2HTJ20CW001	AC SILO WEIGHT SVS2000
LOAD CELL LD360S	
HW 1DM-MCELM30F00	Strain gauge sensor M30-F for structural steel columns (temperature-compensated strain gauge sensor) microcell Supply: 5 - 12 VDC Measuring range: up to 7 kg/mm2 Sensor linearity error: +/- 0.1% Reproducibility: +/- 0.05% Degree of protection with cap: IP 65 Working temp. range: -15 to +65 ¼C Compensated range: -10 to +50 ¼C System Accuracy: Typically +/- 2%
HW 4AB-DMSAD00000	Terminal box for 2 strain gauge sensors Material: ABS plastic Degree of protection: IP 65 Connection: 3-wire technology
HW 3AW -T260SDMS00	Evaluation electronics - Target 260S OFFER ITEM for retrofittable DMS measurement Supply: 12 - 30 VDC or alternatively 110 - 240VAC, 50-60Hz Display: OLED display / alphanumeric easy to read Input: full bridge - DMS signal, CAN bus, 2 digital TTL inputs Output: analog output (e.g. 4 - 20 mA), 3 adjustable switching points (further interfaces on

	request) Operation: Via membrane keyboard with 5 keys Housing protection class: IP 65 Working temperature: -10 to +50°C Housing material: plastic Mounting type: wall mounting (alternatively: on C-rail) When placing your order, please specify the one you want variant regarding the supply!
LOADCELL TI-MC FM-01	COAL BUNKER LOADCELL KISTLER MORSE MICROCELL
TRANSMITTER SVS2000 WEIGHT	"SVS 2000A-A-A-A-N"
SVS-2000/4-20MA (SVS2000A-A-A-A-N)	SVS2000 ASSY (w 4-20mA option card)
WALL MOUNT KIT (SVS-2000)	SVS2000 Wall Mount Kit
Km-503	
C1125kx025x	SENSOR
Sono2baabagyy	SONOLOGIC 2 MULTI-VESSEL SYSTEM
Ld360s25kxpx	LOAD CELL
Mvs-4d-Ac-F4-Xn	WEIGHT INDICATOR W/LEVELING INTEGRATION FRP NEMA4
Mvs-4d-Ac-S4	WEIGHT/LEVEL INDICATOR
64-5034-07	SONOLOGIC 5000 LEVEL I (100FT)
Uwbaaaae	LEVEL DETECTOR
Mvs4dacf4n	MODULE
C1202kx015	LOAD CELL
C1275kx015p	LOAD CELL
Svs-2000-Sag	
Load-Disc Ii, C1-2-20k	
C1203kx025x	LOAD CELL
Sonoiiaaaaaeyy	SONOLOGIC 2 MULTI-VESSEL SYSTEM 110/230V
Svs2000aaann	WEIGHT INDICATOR 115VAC +/- 10PERCENT 50/60HZ
C1110kx025x	SENSOR
Svs2000aabac	WEIGHT INDICATOR 115VAC +/- 10PERCENT 50/60HZ
66-5034-04	SONOLOGIC 5000 LEVEL I (50FT)
Svs2000	TRANSMITTER WEIGHT
C1-1-35k	LOAD DISK 30MV/V 3500LB
C1-1-20k-X-010	LOAD CELL 30MV/V AT 20000LB .1PERC LOAD 10FT CABLE
Svs2000aaacn	WEIGHT INDICATOR 115VAC +/- 10PERCENT 50/60HZ

Uwb-A-A-A-A-N	ULTRA WAVE ULTRASONIC LEVEL MONITOR 110/230 VAC
Uw-Baaaaf	CONTROLLER ULTRAWAVE 30WATT 220VAC 50/60HZ
Svs2000aaabn	WEIGHT INDICATOR 115VAC +/- 10PERCENT 50/60HZ
Sono2baakahyy	SONOLOGIC 2 MULTI-VESSEL SYSTEM 110/230V
Sono2aaaalayy	SONOLOGIC 2 MULTI-VESSEL SYSTEM 115/230V 30W
Uwbaabag	SONOLOGIC 2 MULTI-VESSEL SYSTEM
64.5017.21	BATCH CONTROLLER MODEL1200 120V