

Kito

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Kito Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Kito T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Kito® Efa-Def0-Iia-400/200-1,2	008301 DN 200 PN 10 Deflagration tube protection bidirectional, short-term fire proof Can be used for all substances in explosion group IIA with a Standard gap width > 0.9 mm. Valve tested and approved for a maximum operating pressure from 1.2 bar abs. and a maximum operating temperature of 60 °C. Housing halves: GS-C25 (W.-Nr. 1.0619) KITO® fuse: completely replaceable KITO® grate cage: galvanized steel KITO® grate: stainless steel (mat.no.1.4310) Gap width: 0.5 mm Housing seal: HD 3822 Screws / nuts: galvanized steel Flange connections: EN 1092-1 PN 10 form B1 Type Examination Certificate No. : IBExU 09 ATEX 2067 X Customs tariff number: 84798997 Country of origin: Germany
001723	about the housing material used, issued by the rolling mill / steel mill or by the foundry
40 m. CHAIN HANGER WITH HOOK 2.5 t CAPACITY	LOT NO (LIEFERNR.): ER2A - 73SY3914 OR EQUIVALENT BRAND/MODEL, HAS BEEN REQUESTED FOR OCCUPATIONAL SAFETY REQUIREMENTS FOR LIME QUARTER BRICK LAYING AND QUARE INTERIOR REVISION.

Cf1071
Molle Paranco
Ine-I-250/125-1.2
E6f 5032
Er2m-001ih-S/L
46096/98
Capo Fisso Paranco
23352
Pak-20jk-S96
Bozzello Paranco
Catena Paranco