

Klay Instruments

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Klay Instruments Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Klay Instruments T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Type 8000-SAN-F-M50	1 pieces Electronic Pressure Transmitter, series 8000 Type 8000-SAN-F-M50 8000-SAN = output 4-20mA, accuracy 0.2% of adjusted span zero and span adjustable with potmeters F = min 0-2.5 max 0-10 bar Adjusted at 4-20mA = 0-10 bar M50= process connection coupling nut DN50 acc to DIN 11851 Wetted parts AISI316L Housing AISI 304 Electrical connection PG9 gland
10662	
11018	
2000-SAN-2-X1-H-G0	
2000-SAN-2-X3	
2000-SAN-2-X7-H-G0	
20171	
8000-C-S-G0-G20	
8000-C-S-G0-G20-G65	

8000-SAN-C-W-G0	
8000-SAN-D-X3-HT-G0	
8000-SAN-E-W-V-G26-G0	
8000-SAN-F-M25-G0	
8000-SAN-F-X3-G0	
8000-SAN-H-X7-G0	
CER-8000-D-R-V-G0	
CER-8000-D-R-V-G0(-1...0 bar)	
FR	
FR-5mWC-G16-104	
HYD-CA(20M)-FR-6MWC-G54-104	
HYD-CA-FR-5MWC-G16-104	
HYD-CA-FR-6.4MWC-G16-104	
HYD-CA-FR-6MWC-G16-104	
HYD-CA-FR-7.6MWC-G16-104	
TT-E-D-M(50)-L60xD6-S	
VSC-S-100-3	
VSC-S-500-3	
VSS-S-200-3	
3AH 50-70/1500	
8000 – san – D- M40	
Type 8000-G-S-G53	Pressure transmitter 4-20mA = 0-16 bar connection size ½ male
KMW-LC	Level switch
Sanitary welding socket LZN	for KMW-LC Art. nr. 10662
2000-SAN-Cable(3m)-1-F	Intelligent Pressure Transmitter, series 2000 2000-SAN = microprocessor based transmitter output 4-20mA, accuracy 0.1% of adjusted span easy adjustable using 3 push buttons and display, no test pressure needed Cable(3m) = cable 3m between electronics housing and sensor 1 = min 0-0.04 max 0-0.4 bar Adjusted at 4-20mA = to be determined F = process connection lockring for use in existing flange, a new PTFE gasket is included in delivery Wetted parts AISI316L Electronics housing AISI 304 with wall mounting bracket Electrical connection PG9 gland

900 - 106 HT	
8000-San-?-?7	
Level Indicator Vibra-Switch " C " (Compact, 1 " Bsp, Length 100 Mm, 12 ... 40 V, Pnp Output)	
11018 Seal On Sanitary Nipple 1 "bsp For Vsc/Vss Sensors Material Epdm	
8000-San-D-X3-Ht-G0 Drucksensor	
8000-San-E-M25-V-G0-G26 Level And Pressure Sensor	
8000-San-F-M25-G0 Drucksensor	
Sensor2000-San-2-X1-H-G0	
Vsc-S-47-3-G151	
2000-San-3-F(Dn80)-H	Range: adjustable from 0 - 1 to 0 - 10 bar Calibrated at: 0 - 2.5 bar Output: 4-20 mA + HART Protocol Process connection: Flange DN80
Vsc-S-200-3-G151	
8000-C-S-G0-G20-G65 Drucksensor	
8000-C-S-G0-G20 Drucksensor	
8000-H-S-Ex	
Kmw-Lc	
Cer-8000-D-R-V	
20668	
Hydrobar-Cable(4m)-Fr-0,25bar	
Vsc-M40-47-3-G151	
Level Switch "c" (Compact, 1" Bsp, Length 100 Mm, 12...40 V, Pnp Output)	
2000-San-2-X1-H-G0 Sensor	
8000-H-S-Ex Pressure Transmitter	
Aisi316	
11018 Eichmeister	
Kema 03atex1219 X Ii 1 G Ex Ia Iic T4 Ga	
2000-San-2-X7-H-G0 Sensor Themenbereich	

2000-3-W-H-G1	PRESSURE TRANSMITTER
Vsc-S-500-3-G151	
Wm10189	
Vsc-S-100-3-G151	
Vsc-S-100-3 Tuning Fork Level Switch	
Sensor Klay Instruments2000-San-2-X1 - Hgo 999	
8000-San-B-W-G0	