

## Krom Schroder



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Krom Schroder** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Krom Schroder Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">Tzi 7,5-12/100w</a>	ignition transformer new order no. for 34331383 For high voltage ignition of gas and oil burners High voltage 7.5 kV Output current 12 mA at 50 Hz Duty cycle 100% Mains voltage 230 V ~ TZI 7.5-12 / 100W Ignition transformer new order no. for 34331383 For high-voltage spark ignition of gas or oil burners 7.5 kV high voltage Output current: 12 mA at 50 Hz 100% duty cycle Mains voltage: 230 V AC Stat. Product number 85043200 Country of origin: DE
<a href="#">Dmg S2610</a>	For measuring pressure, negative pressure and differential pressure of air and non-aggressive, gaseous media, digital display, switchable pressure units, hold function for current measured value, display of minimum and maximum measured values, plasticized PVC housing with securing magnet Measuring range: ±1000 mbar, accuracy: ± 1.0 % of measured value, resolution: 0.01 (up to 199.9); 0.1 (from 200) mbar, max. positive pressure: 3 bar Stat. Warennummer 90262020 Ursprungsland: DE
<a href="#">Uvs 10d0g1</a>	UV-sensor For monitoring gas burners in intermittent operation, EC type-tested and certified in conjunction with Elster Kromschrder automatic burner control units Series 10 Quartz glass heat guard Rp 1/2 internal thread - M20 cable gland Stat. Warennummer 90275000 SK
<a href="#">74960445</a>	UV-Photozelle fr UVS 10 Accessory Stat. Warennummer 90329000 SK
<a href="#">Vgbf 25r10-1</a>	Gas pressure regulator Spring-loaded, with inlet pressure compensation membrane and Zero closing, for Keeping the adjustable pressure constant DN 25 Rp internal thread pu max. 1 bar Lock screw in the entrance For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar) Stat. Lot number 90322000 Country of origin: SK
<a href="#">TZI 5-15/100W</a>	84331381 ignition transformer new order no. for 34331381 For high-voltage ignition of gas and oil burners High voltage 5kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~

<a href="#">DG 50U-6</a>	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches with increasing overpressure (gas/air), negative pressure (air), differential pressure (air-air) Electrical connection: With 4-pin plug, with socket
<a href="#">GRSF 25R</a>	03150674 Non-return gas safety device, flameproof at combustion with air To prevent creeping and sudden Gas withdrawal, for Gas, air and oxygen, DVGW tested and registered DN 25 G internal thread Flameproof up to pu max. 5 bar natural gas, LPG pu max. 1.5 bar city gas, hydrogen
<a href="#">DG 500UG-4</a>	84447040 gas pressure switch IP65 / Kapsto conical plug in the lower part, Gold contacts 24/250V For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 100-500 mbar Function: Switches with increasing overpressure (gas/air), negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With screw terminals and M16 cable gland, IP65
<a href="#">DKR 250Z03F100D</a>	03149246 Ring damper for air and flue gas For continuous control of a volume flow DN250 Installation between two DIN flanges PU max. 300 mbar With free shaft end temperature range
<a href="#">DKR 300Z03F450D</a>	03149252 Ring damper for air and flue gas For continuous control of a volume flow DN 300 Installation between two DIN flanges PU max. 300 mbar With free shaft end Temperature range 450°C resounding
<a href="#">Length compensation GRSF 25R</a>	03150679 gas non-return device For use with GRSF 25R (03150674) for exchange GRSF 25R50 (03150645) Overall length 174 mm DN 25 G male/female thread PU max. 5 bar
<a href="#">CG 225R01-DT2WF1</a>	84741205_S compact unit The product contains 'Substances of Very High Concern' (SVHC?s) in a concentration > 0.1% by mass according to REACH contain. With filter or dirt trap, pressure regulator, pressure monitor, valve(s) and quantity setting to save and regulate atmospheric burners, forced draft burners, forced draft boilers up to 400 kW, EC type tested and certified Size 225 Rp internal thread PU max. 100 mbar pressure regulator Mains voltage 220/240 V~, 50/60 Hz 2 valves ,pressure switch, filter
<a href="#">GRS 25R</a>	03150669 gas non-return device To prevent creeping and sudden Gas withdrawal, for Gas, air and oxygen, DVGW tested and registered DN 25 G internal thread PU max. 25 bar
<a href="#">DG 50U-3</a>	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches with increasing overpressure (gas/air), vacuum (air), differential pressure (air-air) Electrical connection: With

	screw terminals and M16 cable gland, IP54
<a href="#">88000043</a>	VAS 350R/NW gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 3 Certification: EU certified Inlet: DN 50 (2") Outlet: DN 50 (2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
<a href="#">Flame guard</a>	'When replacing IFW 15-T 84359010; (without transformer)' please follow the conversion instructions. This is permitted within the scope of European directives product only be used for replacement purposes. For multiple flame monitoring with IFS 110/111IM, for intermittent Operation Ionization or UV monitoring Mains voltage 220/240 V~, 50/60 Hz, for grounded or unearthed networks
<a href="#">Ignition transformer</a>	new order no. for 34331381 For high-voltage ignition of gas and oil burners High voltage 5 kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~
<a href="#">VMO 120R05M10</a>	Measuring aperture To supplement valVario routes or as Single product Size 1 Inlet: DN 20 (3/4") Output: DN 20 (3/4") Rp internal thread pu max. 500 mbar (7 psig) Basic (no accessories possible) Measuring nozzle Aperture diameter 10 mm
<a href="#">DL 3,3K-3</a>	Air pressure switch For monitoring air and flue gas pressures, for overpressure, underpressure and differential pressure, EC type tested and certified Setting range 0.2-3.3 mbar Housing with hose connection and handwheel Electrical connection with screw terminals
<a href="#">IFD 258-5/1W</a>	Gas burner control unit replaces Mat. No. 84620630, compatible Ignites and monitors gas burners, for continuous operation with ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type-tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate fault shutdown or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
<a href="#">DG50U-3</a>	
<a href="#">88600122</a>	
<a href="#">Gdj40ro40</a>	
<a href="#">Vg65a03nd93</a>	
<a href="#">Van4o32r02n31</a>	
<a href="#">74912692</a>	
<a href="#">Bvg65/50z05</a>	
<a href="#">Pfs778l-3/1t/N</a>	

<a href="#">85231050</a>	
<a href="#">Uvs 1</a>	
<a href="#">Dg 6u-3</a>	
<a href="#">Vg20r02Ik061d</a>	
<a href="#">Dg 150 U-3</a>	
<a href="#">88000011</a>	
<a href="#">Ifd 244-3/1w</a>	Automatic burner control unit replaces Mat.No.84620025 + 84620035, compatible Ignites and monitors gas burners, for continuous operation, display for indicating program status and flame signal intensity, IP 54, EC type-tested and certified, FM and CSA approved Series 200 Ionization control Restart in the event of flame failure Safety time on start-up: 3 s Safety time during operation: 1 s Mains voltage: 230 V AC, 50/60 Hz Stat. Warennummer 90268020 Ursprungsland: DE
<a href="#">Zt42</a>	
<a href="#">Dg50u-3</a>	
<a href="#">88300180</a>	
<a href="#">Dl3a</a>	
<a href="#">84367720</a>	
<a href="#">Vg15/10r01t6</a>	
<a href="#">Zkih 300/100r</a>	pilot burner For safe ignition of gas burners, with forced air supply 300 mm in length Additional 100 mm Rp internal thread ZKIH 300 / 100R Pilot burner For safely igniting gas burners, with forced air supply Length: 300 mm Plus 100 mm Rp internal thread Stat. Lot number 84162080 Country of origin: DE
<a href="#">Vas115r/Nw</a>	
<a href="#">Dm160z80-160</a>	
<a href="#">Tzi 5/15/20r</a>	
<a href="#">Vg20/25</a>	
<a href="#">88300177</a>	
<a href="#">Van120r/Nw</a>	
<a href="#">Gdj25r04</a>	
<a href="#">74105884</a>	
<a href="#">Vg10r01n60</a>	

<a href="#">74923048</a>	
<a href="#">75442337</a>	
<a href="#">Cg340r01-Dt2wf1</a>	E2495 84742200 SIEHE ANHANG
<a href="#">Vas125n/Lqgr</a>	
<a href="#">Rv40kf</a>	
<a href="#">Kfm100</a>	
<a href="#">Vr20r01nt31d(Ex.Vr20r01nt61d)</a>	
<a href="#">84444970</a>	DL 5AT Air-pressure switch For monitoring of air and flue gas pressures, for Overpressure Negative pressure and differential pressure, FM approved Adjustment range 0,2-2 ' WC (0,5-5 mbar)
<a href="#">Cg 120r01-Vt2wf1</a>	compact unit The product contains ' Substances of Very High Concern '(SVHC? S) in a concentration > 0.1 mass% acc. REACH contain. With filter or strainer, pressure regulator, Pressure switch, valve (s) and quantity setting for securing and regulating atmospheric Burners, forced draft burners, fan-assisted Boilers up to 400 kW, EC type tested and certified Size 120 Rp internal thread pu max. 100 mbar Adjustable ratio pressure regulator Mains voltage 220/240 V ~, 50/60 Hz 2 valves pressure switch filter CG 120R01-VT2WF1 Combination control There is / are 'Substances of Very High Concern concentration of more than 0.1 mass% contained in this product With filter or dirt trap, pressure regulator, pressure switch, valve (s) and flow adjustment for safeguarding and control of atmospheric burners, forced draft burners and fan-assisted boilers up to 400 kW, EC type-tested and certified Size 120 Rp internal thread pu max. 100 mbar Adjustable variable air / gas ra
<a href="#">3155152</a>	
<a href="#">88003382</a>	
<a href="#">88000016</a>	
<a href="#">84329111</a>	
<a href="#">Dg 50 U-3</a>	
<a href="#">Gbf50f023</a>	
<a href="#">88003923</a>	
<a href="#">Gt50-30m20e</a>	
<a href="#">Uvd1</a>	
<a href="#">Tzi-7,5/100w</a>	
<a href="#">Dg 150u-3</a>	
<a href="#">Vgbf 40r40-3</a>	

[Dl03a](#)