



Kromschroeder

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Kromschroeder Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Kromschroeder Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Ifd 258-5/1w 84621630	Automatic burner control unit replaces Mat.No. 84620630, compatible Ignites and monitors gas burners, for continuous operation with ionization control, adjustable cut-off point, display for indicating program status and flame signal intensity, IP 54, EC type-tested and certified, FM and CSA approved Series 200 Ionization or UV control Immediate fault lock-out or restart in the event of flame failure, switchable Safety time on start-up: 5 s Safety time during operation: 1 s Mains voltage: 230 V AC, 50/60 Hz Stat. Warennummer 90268020 Ursprungsland: DE
Tzi 5-15/100w 84331381	Ignition transformer new oder-No. for 34331381 For high-voltage spark ignition of gas or oil burners 5 kV high voltage Output current: 15 mA at 50 Hz 100% duty cycle Mains voltage: 230 V AC Stat. Warennummer 85043200 Ursprungsland: DE
Tc 3r05w/W	Tightness control For checking two safety valves before and/or after burner run, with adjustable measurement time (5-30 s) for adjustment to different test volumes, leakage rates and inlet pressures, EU certified For quick or slow opening individual valves Rp internal thread pu max. 500 mbar Mains voltage: 230 V AC, 50/60 Hz Control voltage: 230 V AC, 50/60 Hz Stat. Warennummer 90262020

Ursprungsland: DE
Ze 10/5 Enr 4041719 Obsolete/Replaced With Ebi 052 F 4046
Gear For Gt 50 30m20e - 16302443
Bvhs80w01a
03262051
C3895
84391055
Gvs125 MI02 T3
P/N: 15104601 Type: Rv 350/Gml10t60e
P/N: 84765710 Type: Tc 318r05t
Ifs 137b-10/1/5t
Ecc00183
P/N: 88000287 Type: Vag 115r/Nqbe
P/N: 12042559 Type: Ze 23/8,5 (Oem*)
Gik 80ta02-3
Ecc00185
P/N: 88300100 Type: Bva 50z05
84447810
03152149
Zic 165l235 (Poz: 7)
84447523
P/N: 88020788 Type: Vah 350r/Nqae
B2896
Bvhs65w01a
Vgbf 15r10-2
Zkih 300/100rz
Bcu 460-5/1w1gbd284631420- E.18.5- 001716 Ce- 006b01064
P/N: 84214040 Type: Zkih 400/100r
Gt31-60m3e

P/N: 86362020 Type: Jsav 40f40/1-3 Dg 6b Dg 6u
P/N: 84765860 Type: Tc 410-10k
74960445
74921748
84447200 Dg 50b 3
Vg65f02nt33d
Vg 25r02nt31d Solenoid valve for gas for automatic shut off, closed when deenergized, for natural gas, town gas, LPG and air, class A according to EN 161, EC type tested and certified DN 25 Rp-internal thread pe max. 200 mbar fast opening, fast closing 220/240 V AC, 50/60 Hz terminal box with terminals, IP 54 screw plug in inlet flow rate adjustment Stat. Product number 84814090 Country of origin: SK
B4695
Poz: 2 For Zic165
Vg 25 / R02-Nd31
Uvc 1l1q1a (84320300)
Vgp 15r02w62 (Tag N: Sov-72763)
84621460
Poz: 5 For Zic165
84329111
Ic 40 Sa3d
Gdj 15r04-0l
Dg 50b
P/N: 88202685 Type: Vas 9125f05na3b/Pp/Pp
6bvm-Ar
P/N: 85294300 Type: Vgp 15r02q6
Vsbv 25r40-4z
Ifs 110im-5/1/1t (84367020)
P/N: 88300121 Type: Bvg 50z05
Vqbf 80f02-3 Replaced By Vqbf 80f05-3
Dg6u 3

Dg 500ug-3k2	
X0004139	
Ecc00061	
Tc 218r05t	
Ks85311040	
Kfm 160rb100	Capsule To indicate pressures, overpressure, with Zero correction, for gas and air Measuring range 0-160 mbar R outer thread overprint 100 mm visible scale diameter KFM 160RB100 Pressure gauge with capsule element For pressure display, positive-pressure-proof, with zero point correction, for gas and air Measuring range: 0-160 mbar R external thread Positive pressure 100 mm visible scale diameter Stat. Lot number 90262040 Country of origin: DE
Bic 140 Hb/O35	
Dg 150ug 4	
P/N: 84447528 Typ:Dg 150ug-3k2	
84228020	
P/N: 88000003 Type: Vas 115r/Nw	
85093320	
Ifs 110imt-W-5/2/2n	
Vg 25 R02-Nd31	
Bcu370wfeu0d3b1	
Ic50-60w30tr10	
Vas1-/Ly88012617 Pa Max 500mbar. 200	
Vac 33w	
Bcu 460-5/1lw3gbs3b1/1	
Vas240r/Nq	
Ifd 244-3/1wz (84621029)	
P/N: 88300103 Type: Bva 100z05	
Lõ;Ngenausgleich Grsf 50r	
75422041	
03200108	
84234030	
74960611	
Ze 14-12a1 (Poz: 4)	

Rfm0,6rb100	
Dg 450ig 4	
Valvario Set 1 1/2"	FOR HOLDING BURNER TV2-T/VASN40-40/VAG40/VAS1BP/V
Grsf 50r	
6292 94	
Poz: 3 For Zic165	
P/N: 88001137 Type: Vas 115r/Nk	
Fzlksi	
74921671 Ic20 Ic40	
84447550	
Ifw 15-T (84359020)	
P/N: 88000056 Type: Vas 365r/Lq	
8bvm-Ar	
Dl-3a-3z	
Dg 30ug-3k2	
Cg35f05-Vw2w (Tag N:72757)	
84447800	
Gik 65f02-6(85092220)	
Vas 120 R/Nw	
Vas 250r / Nwsr K¼c¼ Tip	
Gik 50r02-5 (03155158)	
P/N: 03150646 Type: Grsf 50r50 Obsolete, Replaced By Grsf 50r	
84447250	
84765713	
84447200	
Dg 500u-3 (84447550)	For monitoring gas and air pressures, also for biologically produced methane, with hand wheel for switching point adjustment, can be used as "special-design pressure switch", EC type-tested and certified Adjusting range: 100-500 mbar Positive pressure (gas/air), negative pressure (air), differential pressure (air-air) Electrical connection via screw terminals Stat. Warennummer 90262080 Ursprungsland: DE
61969	

Cg_220r01-Dt2wf1z	
Vas_125_R/Lq	
Dg_500b	
84230031_Zmi_16_G_300	
Bvhs100w01a	
Bva_80/50z05	Throttle valve for air For continuous or gradual regulation of a volume flow DN 80 Reduced to DN 50 Installation between two DIN flanges pu max. 500 mbar (200 " WC) resounding BVA 80 / 50Z05 Butterfly valve for air For continuous or staged control of flow rates DN 80 Reduced to DN 50 For fitting between two DIN flanges pu max. 500 mbar (200 " WC) With disc clearance Stat. Lot number 84818085 Country of origin: DE
8830063_Ic_20_15q3t	
Vgbf_80f05-3	
03200435_Uz	