



Krone Filter Solutions Gmbh

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Krone Filter Solutions Gmbh Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Krone Filter Solutions Gmbh T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Filter Angaben:	<p>Self-cleaning automatic filter, type KAF - Bernoulli DN 300 GGG-50, EN-GJS-500-7, 2.5 mm rubberized Connections: Nominal size: DN 30 DIN EN 1092-1 PN 10 Flushing outlet: DN 100 DIN EN 1092-1 PN 16 Operating conditions: Medium: sea water Operating pressure: Unknown (min. 0.6 bar during flushing) Design pressure: 6 bar Design temperature: 0 / + 80 ° C Operating temperature: Unknown Flow rate: 560 m³ / h Backwash quantity: 1.5 m³ Backwashing time: approx. 42 seconds Pressure loss clean: approx. 0.07 bar Differential pressure flushing: 0.11 bar + pressure loss clean Materials: Filter housing: GGG-50, EN-GJS-500-7 External parts: galvanized steel Inner parts: SS 316Ti Seals: NBR Filter element: Siebart: Edge gap sieve / basket sieve - perforated plate Filter fineness: 300 µm / 0.3 mm Material: SS 316 Perm. Differential pressure: 1 bar Equipment: Differential pressure switch: Aplisens, membrane made of Hastelloy Flush valve: DN 100, wetted parts duplex 1.4462 / 1.4469, pneum. drive Control: SPS - Crouzet Millenium III Supply voltage: 230V AC, 1 Ph, 50 Hz Control voltage: 24 V DC Corrosion protection: Inside: 2.5 mm rubberized Chemonit 33 Outside: epoxy RAL 5010 Interpretation: Classification and</p>

	conformity assessment according to PED 2014/68 / EU Design based on AD2000
Kaf Dn 150 - 1201476-5	
Kdfk032.0305160040	KDFK double filter DN32, Gr. 3, screws, FPM, oil version, standard GGG-50 / FPM / studs / including. Chicks, adapters and Handle KDF double filter Closure with studs Flanges DN32 PN16 DIN 1092-1 PN 16 Design pressure 16 bar Material GGG-50, cover seal FPM Rooster chicks GGG Draining G 3/8 ", vent G 1/4" from VA Color RAL 5010
Idfk032.030221002501	Basket strainer double filter KDFK Gr. 3; 25 µm 204.00 408.00 Basket strainer for double filter KDFK Suitable for housing size 3 / DN32 / 40 / Filter fineness 25 µm, filter surface 440 cm ² Material 1.4301 / 1.