

K¼enle

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
K¼enle Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız K¼enle T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Kdgn2w 315-S-6-Kt-Kty	
KTE2W 132M4 SFEIR 7.5 KW	
D90 A420 B150 F9	Fan blade (aluminum) (D = inner diameter / shaft diameter A = outer diameter (outer edge wing-wing) B = width fan wing F = number of wings)
IE3 100L/B5/3Ph/4p/2,2/PTC	Iso F, IP55, RAL 7030
FRQ5S-10A + LED V2 frequency convert.	208-480V, Imax: 10A Technical specifications: Nominal data Voltage: 208 to 480V Frequency: 50 Hz Frequency: 60 Hz Phase (s): 3 ~ max.current: 10 A Protection class / classification Degree of protection: IP54 Controller and sensors Recommended fuse: 16 A Permissible ambient temperature: max. 40 ° C Dimensions and weights weight: 6.3 kg
KPER 63 G4 3301 372549	EXPLOSION PROTECTION CLASS: EEX E II T3 OUTPUT POWER(KW): 0.18 KW NUMBER OF POLES: 4 SPEED (r/min): 1350 INPUT VOLTAGE: 400V OUTPUT VOLTAGE: 400V SUPPLY FREQUENCY: 50HZ TEMPERATURE RISE CLASS: F INSULATION CLASS: IP 54 EFFICIENCY CLASS: IE2-IE3 FRAME SIZE: 63

MOUNTING ARRANGEMENT: B5 TERMINAL BOX POSITION:
BOTTOM FRAME TYPE: ALUMINUM STANDARD-1: VDE 0530

[Komplett](#)