



Kvaser

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Kvaser** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Kvaser Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Leaf Light V2 Hs	Art Nr. 00685-0 □□ USB / CAN interface □□ CAN 2.0A and CAN 2.0B support □□ 1 channel high speed □□ Performance: 8000 msg / s □□ Time resolution 100µs □□ 1 x 9-pin DSub connector □□ galvanic insulation □□ Temperature range: - 20 ° C ... + 70 ° C □□ Weight: 100g
Kvaser Leaf Light V2	Kvaser Memorator Light HS V2 Stand alone CAN data logger Single-channel high speed CAN bus (compatible with ISO 11898-2) Supports 11 bit (CAN2.0A) and 29 bit (CAN2.0B) Identifier Bit rates from 50 Kbit / sec up to 1 Mbit / sec. Automatic detection of the bit rate Always in silent mode - logging of bus traffic without send the Acknowledge. 1 GB of internal memory CAN data are stored in a ring memory 1 x 9-pin DSub connector Temperature range: -40 ° C to + 85 ° C Weight: 150g
USBcan light 4xHS (00831-1)	KVASER USB-CAN-Wandler, vierkanalig, fr High-Speed CAN (ISO 11898-2), Bit Rate von 40 kbits/s bis 1 Mbits/s, Zeitstempel fr CAN-Nachrichten mit 100µs Genauigkeit, 8000 Nachrichten pro Sekunde, untersttzt sowohl 11-bit (CAN 2.0A) als auch 29-bit (CAN 2.0B active) Identifier, untersttzt Data und Remote Frames, Fehlererkennung fr Error Frames, 26-poliger DSUB Stecker (inkl. Splitterkabel HD26 auf 4x 9pol. DSUB, mit Belegung gemB CiA-DS102), kompatibel mit USB 2.0 und USB 1.1., mit Potentialtrennung, 68x170x25mm, 0,15kg, -20 ... +70°C
	KVASER USB-CAN converter, single-channel, for high-speed CAN (ISO 11898-2), bit rate from 40 kbits/s to 1 Mbits/s, time stamp for CAN messages with 100µs accuracy, 8000 messages per second, supports

Leaf Light HS v2 (00685-0)	both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifier, supports data and remote frames, error detection for error frames, very good EMC behavior, 110cm USB cable and 30cm CAN cable, CAN connector: 9 -pin DSUB plug with assignment according to CiA-DS102, compatible with USB 2.0 and USB 1.1., with electrical isolation, 40x100x20mm, 0.1kg, - 20 ... +75°C
Leaf Light v2 HS	00685-0 □□ USB / CAN interface □□ CAN 2.0A and CAN 2.0B support □□ 1 channel high speed □□ Performance: 8000msg/s □□ Time resolution 100µs □□ 1 x 9-pin DSub connector □□ galvanic isolation □□ Temperature range: - 20°C ... + 70°C □□ Weight: 100g □□ Customs tariff number: 85176200 □□ Country of origin: Sweden
Leaf Light v2 HS	□□ USB / CAN interface □□ CAN 2.0A and CAN 2.0B support □□ 1 Channel High Speed □□ Performance: 8000 msg/s □□ Time resolution 100µs □□ 1 x 9-pin DSUB connector □□ Galvanic insulation □□ Temperature range: - 20 ° C ... + 70 ° C
Kvaser T-connector v2	□□CAN distributor box □□4x D-SUB9 connections □□ Intended schedule 120 (60) Ohm □□12V 1A power supply □□LED for displaying the power supply □igh. Possibility of power supply (PIN 9) 12V - 24V DC □□T temperature range: -30 ° C to +85 ° C
00752-9	USBcan Pro 2xHS v2 □□ USB / CAN interface □□ CAN 2.0A and CAN2.0B support □□ CAN FD support □□ Kvaser MagiSync □□ 2 channels, galvanically isolated □□ Performance: 20,000 msg/s □□ CAN bit rate: 50 kbit/s up to 1 Mbit/s □□ CAN FD bit rate: up to 8 Mbit/s □□ Temperature range : -40°C ... +85°C □□ 2 x 9-pin DSub connector □□ 2x CAN HS □□ Weight: 170g
01407-7	OBD II adapter cable □□ 1 x OBD II connector □□ 1 x 9 pin DSub connector □□ Length 2.5 m □□ Weight: 160g
1000817508 USB CAN	
Leaf Light HS v2 (00685-0)	KVASER USB-CAN converter, single-channel, for high-speed CAN (ISO 11898-2), bit rate from 40 kbits/s to 1 Mbits/s, timestamp for CAN messages with 100µs accuracy, 8000 messages per second, supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifier, supports data and remote frames, error detection for error frames, very good EMC behavior, 110cm USB cable and 30cm CAN cable, CAN plug: 9 -pin DSUB connector with assignment according to CiA-DS102, compatible with USB 2.0 and USB 1.1., with potential isolation, 40x100x20mm, 0.1kg, -20 ... +75°C
U100 (01173-1)	KVASER USB-CAN converter, single-channel, for harsh environmental conditions (higher insulation and robust fiberglass-reinforced housing), for high-speed CAN (ISO 11898-2), bit rate from 10 kbits/s to 1 Mbits/s, time stamp for CAN Messages with 100µs accuracy, 8000 messages per second, supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers, supports data and remote frames, error detection for error frames, very good EMC behavior, 100cm USB cable and 30cm CAN cable, CAN plug: 9-pin DSUB plug with assignment according to CiA-DS102, compatible with USB 2.0 and USB 1.1., with electrical isolation up to 5000 Vac rms for 60sec, LED display 38x128x26mm, 0.167kg, - 40 ... +85°C
Leaf Light v2	73-30130-00685-0
KVASER USB-CAN converter, single-channel	for high-speed CAN (ISO 11898-2), bit rate from 40 kbits/s to 1 Mbits/s, timestamp for CAN messages with 100µs accuracy, 8000 messages per second, supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifier, supports data and remote frames, error detection for error frames, very good EMC behavior, 110cm USB cable and 30cm CAN cable, CAN plug: 9 -pin DSUB connector with assignment according to CiA-DS102, compatible with USB 2.0 and USB 1.1., with potential isolation, 40x100x20mm, 0.1kg, -20 ... +75°C Leaf Light HS v2 (00685-0)
	01424-4 □□ USB / CAN interface □□ CAN 2.0A and CAN 2.0B support □□ CAN FD support up to 8 Mbit/s □□ CAN bit rate: 20 kbits/s to 1

Kvaser Leaf v3	Mbit/s □□ Performance: 20000 msg/s □□ Time resolution 50µs □□ 1 x 9-pin DSub connector □□ galvanic isolation □□ Temperature range: -20°C ... + 70°C □□ Weight: 110g
P10745	Leaf Light HS v2 (00685-0) KVASER USB-CAN converter, single-channel, for high-speed CAN (ISO 11898-2), bit rate from 40 kbits/s to 1 Mbits/s, time stamp for CAN messages with 100µs accuracy, 8000 messages per second, supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers, supports data and remote frames, error detection for error frames, very good EMC behavior, 110cm USB cable and 30cm CAN cable, CAN connector: 9-pin DSUB connector with assignment according to CiA-DS102, compatible with USB 2.0 and USB 1.1., with electrical isolation, 40x100x20mm, 0.1kg, -20 ... +75°C
Usbcan Ii Hs/Ls	
Leaf Light Hs V2 P/N: K-00685-0	
205361	
73-30130-00752-9	
00241-8	
Leaf Light v2 HS	00685-0 Leaf Light v2 HS □□ USB / CAN Schnittstelle □□ CAN 2.0A und CAN 2.0B Unterstützung □□ 1 Kanal High Speed □□ Performance: 8000 msg/s □□ Zeitauflösung 100µs □□ 1 x 9-poliger DSub Stecker □□ galvanische Isolierung □□ Temperaturbereich: - 20°C ... + 70°C □□ Gewicht: 100g
00752-9	
Kvaser Obd Ii To Dsub9 Adapter Cable (Ean Number: 73-30130-00723-9)	
Usbcan Professional Hs/Hs	
00801-4	
00357-6á;Obsolete, Replacement 00752-9	
Kvaser Blackbird Semipro Hs/Hs (Ean Number: 73-30130-00453-5)	
00243-2	
00351-4	
73-30130-00801-4	
Usbcan Ii Hs/Hs	
00427-6	
00685-0	
73-30130-00779-6	
D-Sub 9 Pin 120 Ohm	
Semipro Hs/Hs	
00175-6	
Hs V2	
73-30130-00331-6	
Art.No. 00241-8 Obsolete, Replaced By Ean: 73-30130-00685-0	

[00029-2](#)

[Em2789](#)

[?00242-5](#)