

Kyowa

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Kyowa Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Kyowa Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
19b05164	min. order?
AC200V 50/60 HZ MR-Q3-42-314-8AAAA-18F11322	
AC380V 50/60HZ MR-Q3-57-285-8AFBA-18F20177	
DTH-A-100	Displacement transducer Measuring range: 100mm 350 Ohm bridge output, supply voltage max. 6V AC or DC Including 2m cable and two assembly straps.
DTH-A-10	Displacement transducer Measuring range: 10mm 350 Ohm bridge output, supply voltage max. 6V AC or DC incl. 2m cable and mounting tape.
04F01121?	
CC-33A-5	
EDX-200A	
EDX-200A-4H	

KLPC-100FR	
KSP-6-350-E4	
LC-20TV	
LC-5TSHR-7Z5	
LCTB-A-10KN	
LUK-A-10KN	
LUK-A-20KN	
LUK-A-50KN	
MR-A3-42-288-4YAAA	
PAL-500KB	
PAV-250KC-M28 (SERIAL NO: YV6841)	
S32-7	
WGA-100B-1 0	
PCD-400A	Four channel USB 2.0 sensor interface. Expandable to 16 channels. 24-bit ADC with a maximum sampling rate of 10 kHz. Measuring ranges: 200, 500, 1000, 2000, 5000, 10000, 20000µm/m LP filter switchable: 10, 30, 100Hz & Flat Bandwidth: 200Hz Working temperature range: 0°C ... 40 °C Dimensions [mm]: 210x35x157.5 Incl. DCS 100A control software and USB cable.
LMB-A-2KN	Low Profile Compression Load Cell Messbereich: 2000N, Spring rate: 41 kN/mm, Cable: 2m Long
CFM-16B	Mounting plate for LMB-A-500N up to 2KN
PCD-400A	3 cm strain guage
Manuel Hydro Pressure Test Pump	
LMB-A-2KN	Low Profile Compression Load Cell Messbereich: 2000N, Spring rate: 41 kN/mm, Cable: 2m Long
DTS-A-100	Strain type Displacement Transducer for tension and compression 100mm Rated Capacity Fast response (DC to 50 Hz, when the head is fixed, displacement:30 mm) Safe temperature range -10 to 70 °C(Noncondensing) 4-conductor(0.08 mm ²) vinyl shielded cable, 3.2 mm diameter by 1 m long, terminated with connector plug. Incl. Probe: X-1-DT , 1 PC and Mounting band (FXBP-100A) 2 PCs.
S32-7	NDIS Kupplung (Female) (PRC03-32A10-7F10.5) Passend zu den Kyowa Sensoren.
PR TD 50 1191 45zmgf motorized angle roller	

[PR TD 50 1191 45zmgf dimensions to be idle](#)

[PR-AD-50-578-25ZMGT](#)

[Phc-B-2mp](#)

[Dlt-5bs](#)

[Mr-Q3-57-700-25afba](#)

[Pav-300kh M76](#)

[Kfc-10-C1-11, Replaced By Kfgs-10-120-C1-11](#)

[Sc-18-00a](#)

[Ksp-6-350-E4\(4 Pcs/1 Bag\)](#)

[Ber-A-2mp79s](#)

[Lcn-A-20kn](#)

LOAD CELL

[Kfg-1-350-C1-11\(10 Pcs/1 Bag\)](#)

[Pav 300ku](#)

[Pcd430a](#)

INTERFACE

[Lmc-A-5 Kn](#)

[Edx-200a](#)

[Cable For The Charge Cell Of F340a](#)

[Das200a](#)

SOFTWARE

[Dtj-A-200](#)

[Sc01r100a](#)

[Sp-20-88ax915l](#)

[Wga-100b-00](#)

[Kfrs-02-120-C1-13n10c3](#)

[Lcr-S-160kns19c](#)

[Lc-10tv](#)

[Lcna20knp](#)

LOAD CELL

[Kfgs-10-120-C1-11 \(Pack Of 10\)](#)

[Phf-S-5mpsa2](#)

Single-axis slides DMS Executed with 25mm ready applied solder flags Nominal resistance: 120 Ω Grid in mm: 5 x 1.4

Kfg(S)*-5-120-C1-11	Carrier in mm: 9.4 x 2.8 Thermally adjusted to 11ppm / degree Kelvin Package content 10 pieces
Pav-H-300-K	
Dts-A-100	
Pcd400a	INTERFACE
Kmp-3-4c114-508-20	
Phl-A-50mp-A	
Wds-180a	
Kfg-6-120-C1-16(10 Pcs/1 Bag)	
Wga-800c-20ac-M253	
Kmp3-114-520-20	
Pav-350kh M76	
Lma-A-20n	
Pav-250kc-M28 (Serial No: Yv6841)	
Id/DIt-5bs	
Kfg-5-120-C1-11	Single-axis slides DMS Executed with 25mm ready applied solder flags Nominal resistance: 120 Ω Grid in mm: 5 x 1.4 Carrier in mm: 9.4 x 2.8 Thermally adjusted to 11ppm / degree Kelvin Package content 10 pieces
Bpr-A-50kps	
Kfg-30-120-C1-11 L1m3r	
Ksp-1-350-E4(4 Pcs/1 Bag)	
Lck5ta	LOAD CELL
Wga-800b-20ac-M253	
Dth-A-30	
S21-7 Prc03-21a10-7f	
Yeni Model	