

## Loehrke

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Loehrke** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Loehrke T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



| ¼r¼n   | A¼ıklama   |
|--|--|
| <a href="#">diaphragm valve;</a>                           | threaded sleeve; ISO228 G3/8" (DN12); pneumatically actuated (NC); PVC-U; diaphragm: EPDM  |
| <a href="#">replacement diaphragm for diaphragm valve;</a> | DN 10-15; EPDM   |
| <a href="#">1705000003</a>                                 | flat jet nozzle; 4.8l/h 2bar; 75°; 1.4305  |
| <a href="#">5000001779</a>                                 | Brush; G 1/8"; connection at the top; WxHxD 38x25x20<br>Bristle height = 40 mm In order to reduce wear, it is advisable to select the setting angle of the nozzle holder so that the brush rests on the chain with light pressure. |
| <a href="#">1705000009</a>                                 | Nozzle adapter piece; Di 6.5; G 1/8" a; 1.4305   |
| <a href="#">1705000011</a>                                 | Sealing ring; 14.8 x 8 x 2 mm; PA  |
| <a href="#">1705000137</a>                                 | Dosing orifice; "14"; 4.8 l/h; bore 0.36 mm; 1.4404  |
| <a href="#">1705000010</a>                                 | Ball valve filter; mesh size approx. 80µm; 0.35 bar; PP; ball 1.4305; blue   |
| <a href="#">1705000020</a>                                 | Nozzle union nut; 11/16" - 16-UN; SW 19; 1.4305  |

[5000001778](#)

Brush; G 1/8"; connection at the top; WxHxD 80x25x20  
Bristle height = 40 mm In order to reduce wear, it is  
advisable to select the setting angle of the nozzle holder so  
that the brushes rest on the chain with light pressure.