

Logtag

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Logtag Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Logtag T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
LTI-HID Interface for LogTag® data loggers	LTI-HID
HAXO-8	Humidity and temperature data logger Use: reusable Sensor type: Internal Measuring range: -40 ¼C to +85 ¼C 0% to 100% RH Display: Status LED Data storage: ~ 8,000 readings Self-sufficient PDF report:-
TRIX-8	LogTag® TRIX-8 temperature data logger - EN12830 compliant & WHO pre qualified Dimensions : 86mm (H) x 54.5mm (W) x 8.6mm (D) Applications: room surveillance, transport surveillance Recording interval: adjustable from 30 seconds to several hours Readout time : less than 5 seconds Battery replaceable : yes (by technician) Battery life with typical use: 2-3 years Operating temperature : -40 ¼C to +85 ¼C Data transfer : LTI/HID interface Display: no Housing material : polycarbonate Weight: 33g Maximum temperature : +80 ¼C Temperature measuring range: -40 ¼C to +85 ¼C Measurements : Temperature Minimum temperature : -40 ¼C Degree of protection: IP 65 Protection class: IP 65 (jet water) Power supply : 3V LiMnO2 battery Storage capacity : 8,000 events Temperature sensor: internal

Trid30ã173;7r	
Haxo8	
Trix-8	
Lt/Usb 8	
Logtag Pe	
Sundry Spare	
Trid 30-7f	
Hax0-8	
HAXO-8 humidity and temperature data logger	Data logger HAXO-8 with or without calibration: HAXO-8 without calibration
Utrid16	
Logq82	
Tred30-7r	
Logtag Trid30r Starter Kit3 - Not Available	
Utrix16	
Logtag Usb	
Logtag Wmb	