

Lutz

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Lutz** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Lutz T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n

A¼ıklama

Nominal size: 1200 mm sealless and conditionally safe to run dry

Pump tube PP 41-L-DL HC	Impeller made of PP Pump tube made of PP Drive shaft: Hastelloy C - 4 (2.4610) Dip tube diameter: 41 mm Pressure connection: external thread G 1 1/4
Motor MI 4 / 500W	230V AC/50 Hz Universal motor, input power 500 W, with 5 m connection cable and plug thermal overcurrent release, protection class IP 24, double pole on/off switch with single pole 230 V, 50 Hz, with double protective insulation,
motor MI 4 - E / 500W	Characteristic data: medium: unknown solid matters: none operating temp.: approx. 20 °C (assumed) viscosity: max. 500 mPa s density: max. 1,4 kg/dm ³ quantity: up to 87 l/min. delivery head: up to 19 m water column 230V AC/50 Hz IP 24, with 5 m connection cable and plug release, protection grade of enclosure with single-pole thermal overcurrent double insulated, bipolar on/off switch power input 500 W, 230 V, 50 Hz, Universal motor with speed controller
pump tube PVDF 41-L-SL	nominal size: 1200 mm Seal-less and contingently safe to run dry Pressure joint: outer thread G 1 1/4 Pump tube diameter: 41 mm Drive shaft: hastelloy C - 4 (2.4610) Impeller made of ETFE Pump tube made of PVDF (natural)
0205-402	Characteristic data: medium: unknown solid matters: none operating temp.: approx. 20 °C (assumed) viscosity: max. 350 mPa s density: max. 1,6 kg/dm ³ quantity: up to 95 l/min. delivery head: up to 14 m water column pump set Ex "solvents" container drainage consisting of: Universal motor ME II 3 / 460 W, 230 V AC/50 Hz explosion-proof acc.to type of protection II 2G Ex db eb IIC T6 Gb (ATEX), protection class IP 54, double-pole thermal overcurrent release, seal made of PTFE. with turnable hose connection, Nozzle made of brass, connectors made of brass. conductive, cpl. with pre-assembled hose solvent hose DN 19 (3/4"), electrically drive shaft made of stainless steel (1.4571). explosion-proof acc. Ex II 1/2 G IIB T4 Ga/Gb (ATEX), seal-less and contingently safe to run dry, type SS 41 - L - SL, nominal size: 1200 mm, Pump tube made of stainless steel (1.4571) cable and non-explosion-proof plug. with low-voltage-release, with 5 mtr. connection
As010rn11982180	
84123900	
M16x18x80	
3.87.03.37j	
0201-501	
215cgrn11982172	
0150-004s Pumpwerk Niro 41-L-DL	
1.14.13.02	
0.56.00.62	
345038	
0204-401 Schlauchanschluss Niro Dn 25 (1") Schlauchanschluss Niro, Dn 25 (1")	
1.21.03.01	
1.21.55.05a	
Gear 1.21.03.01	
3.Cm.16.02	
0204-401	

1.17.09.13a	
0050-000 Pump	
8.71.07.01a	
M20x200	
3.Et.16.01	
M24x225	
3.88.00.88d	
8.71.24.06	
Ss41-L-SI	
105424	
0060-000 Motor Ma Ii 3 / 460w, 230v Ac/50 Hz, Ousp	
0300-445 Stufenlose Ohr Klemme Stufenlose Ohr Klemme	
1.23.55.00	
3.88.00.38f	
0050-002	
4558083903	
0402_0200	
Uni5738m10x1(960)	
0150-004	
3.87.03.37g	
M24x28x125	
3.88.00.65g2	
4558083902	
1.21.60.05h	
Maii 7-795w	
0110-205	
0030-006+0103-042	MOTOR 0030-006PUMP 0103-042
115nbr90	
M20x160	
0.26.00.62	
1.03.10.03	
M20x22x125	
1.21.50.05a	
M20x100	
M20x22x100	

0204-994 Potentialausgleichskabel
0.60.Dc.62v
0151-004 Pumpwerk Niro 41-L-Glrd
1.17.19.13a
5.6b.04:13l
063350037/0
1.22.21.02
Uni5588m10x1
0115.1000
8.71.24.08
0 60 Dc 62v
8.72.51.35d
3.88.00.30f
L-175
1.26.01.00
3.89.83.81
3452353
0204-370 Zapfpistole Niro / Fpm G 1 1/4 Ag
3030803
0004-087
1 03 10 03
3.89.10.50a
602055 immersion 1000mm
1.17.16.10a
M24x120
0204-734 Mehrpreis Zapfpistole Niro G1 1/4 Pu Physiologisch Unbedenklich Mehrpreis Zapfpistole Nir
M16x100
Rn11982168
0150-100s Mehrpreis Pw Niro 41-L DI Pu Physiologisch Unbedenklich (Max. Mediumstemperatur 80 °c)
1. 17.A1.21
1.22.02.02
3.87.03.37h
8.71.24.02
1.25.60.03

0 26 00 62	
Md1 400 W	
Asa3/8"x3/16"asa35g63	
3.89.80.81	
M16x80	
1.25.30.04	
1.17.A2.33	
Din3852d1/4"	
1.17.50.00	
3.Cm.20.02_L	
M24x28x250	
1.14.13.04	
1.22.01.02a	
G35x45x4	
1.17.33.13a1	
M20x22x160	
220nbr90	
0402.0200	
3.Cm.20.02	
Me-Ii-5-230	DRUM PUMP 240V INFLAMMABLE ELECTRIC FUEL LUBRICANT
1.26.03.00	
1.21.34.00	
M20x22x200	
0374-463 Mtr. Lebensmittelschlauch Dn 25 (1")	
0 56 00 62	
Uni5738m10x1	
M6x20	
M8x20	
84137081	
3.88.00.17x	
0201 501	
0205-115	
M20x125	
1.17.17.10a	
105423	

8.71.24.05	
3.87.03.37i	
1.22.50.05	
0410.0200	
3.Et.20.01	
1. 17.A1.21/1	
6.40.16.00	
1.17.08.13a	
0030-000	
1/2"x5/16"z24	
1.17.44.13a	
743100	INTERFACE MODULE
1.26.02.00	
M16x18x100	
3.89.13.50a	
1.17.37.00	
8.71.24.04	
1.21.13.05	