



## Lutz-Jesco

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Lutz-Jesco** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Lutz-Jesco Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">Magdos Lp 2 Pvc/Fpm</a>	10231003 0102P0020CC031A2K2KC1ZC1Z00 Magnetic diaphragm metering pump Product: MAGDOS Type: LP Delivery rate: 1.9 l / h at 16 bar - 2.3 l / h at 8 bar Capacity adjustment: stroke frequency adjustable 0 - 160 strokes / min Material dosing head and valves: PVC Control unit: 110 - 240 V + 5 / -10%, 50/60 Hz Electrical connection: 1.8 m power cord with plug, Europe (at 230 V AC) Suction valve DN4: double ball ceramic / PVDF / FPM (ball / seat / seal) Pressure valve DN4: double ball ceramic / PVDF / FPM (ball / seat / seal) Suction connection material: PVC Suction connection: Hose clamp connection set 4/6, 6/9 and 6/12 Material pressure connection: PVC Pressure connection: hose clamp connection set 4/6, 6/9 and 6/12 Dosing head arrangement: floor mounting Option: without Functions Stroke frequency precisely adjustable with the keyboard
<a href="#">Magdos Lp 05 Pvc/Fpm</a>	0102P0005AC031A2K2KC1ZC1Z00 Magnetic diaphragm metering pump Product: MAGDOS Type: LP Flow rate: 0.36 l / h at 16 bar - 0.54 l / h at 8 bar Capacity adjustment: stroke frequency adjustable 0 - 120 strokes / min Material dosing head and valves: PVC Control unit: 110 - 240 V + 5 / -10%, 50/60 Hz Electrical connection: 1.8 m power cord with plug, Europe (at 230 V AC) Suction valve DN3: double ball ceramic / PVDF / FPM (ball / seat / seal) Pressure valve DN3: double ball ceramic / PVDF / FPM (ball / seat / seal) Suction connection material: PVC Suction connection: Hose clamp connection set 4/6, 6/9 and 6/12 Material pressure connection: PVC Pressure connection: hose clamp connection set 4/6, 6/9 and 6/12 Dosing head arrangement: floor mounting Option: without
	Control cable PVC length 2 m with M12x1 coupling, 4-pin, A-

<a href="#">79113</a>	coded CONTROL CABLE Use for the following functions possible: - external release - pulse output - Analog input - Pulse input - level monitoring Nominal voltage <= 300 V
<a href="#">79112</a>	Control cable PVC length 2 m with coupling M12x1 4-pin B-coded CONTROL CABLE Fault signal relay contacts output Nominal voltage <= 300 V
<a href="#">P-109 A/Y</a>	45GCN20AP010-AP020 Material: PVDF 0,48-13,5m3/h max.1,84g/cm3 0,55Kw 2900rpm 400V AC 50Hz Komplett mit Rohr und befestigungen
<a href="#">P-110 A/Y</a>	45GCN30AP010-AP020 Material: PP 0,48-13,5m3/h max.1,84g/cm3 0,55Kw 2900rpm 400V AC 50Hz Komplett mit Rohr und befestigungen
<a href="#">52897</a>	Shaft protection sleeve with raceway for mechanical seal Ø35 Mathcode:: SHAFT PROTECTION SLEEVE Customs tariff number: 84139100 Weight: 0.196 kg + 59005 Kleber Weicon VA300 - 12 g
<a href="#">0102D0150BC011A2020C1ZC1Z0</a>	
<a href="#">0201-502</a>	
<a href="#">0205-502</a>	
<a href="#">10221305</a>	
<a href="#">10231005</a>	
<a href="#">10241001</a>	
<a href="#">10241002</a>	
<a href="#">10241003</a>	
<a href="#">10241004</a>	
<a href="#">10241019</a>	
<a href="#">10407008</a>	
<a href="#">10417022</a>	
<a href="#">104L15XXX-151</a>	
<a href="#">104P10XXX-140</a>	
<a href="#">10501488</a>	
<a href="#">12201149</a>	
<a href="#">12201177</a>	
<a href="#">12302007</a>	
<a href="#">12335495</a>	
<a href="#">12600052</a>	

[12601001](#)

[12701332](#)

[12701435](#)

[12724321](#)

[13600319](#)

[13600320](#)

[18185](#)

[18186](#)

[18327](#)

[18331](#)

[18353](#)

[18359](#)

[20890](#)

[20891](#)

[22066](#)

[23892](#)

[25087](#)

[25088](#)

[25162](#)

[26845](#)

[27517](#)

[28274](#)

[28300](#)

[28301](#)

[28404](#)

[29312](#)

[29434](#)

[29435](#)

[29746](#)

[29750](#)

<a href="#">29951</a>
<a href="#">29995</a>
<a href="#">32393</a>
<a href="#">32394</a>
<a href="#">32980</a>
<a href="#">33855</a>
<a href="#">33897</a>
<a href="#">34506</a>
<a href="#">37164</a>
<a href="#">38196</a>
<a href="#">39121</a>
<a href="#">40356</a>
<a href="#">40357</a>
<a href="#">42387</a>
<a href="#">44101002</a>
<a href="#">44101004</a>
<a href="#">44102011</a>
<a href="#">50072</a>
<a href="#">50301001</a>
<a href="#">50355</a>
<a href="#">50580</a>
<a href="#">51750</a>
<a href="#">52532</a>
<a href="#">52533</a>
<a href="#">52536</a>
<a href="#">52537</a>
<a href="#">59005</a>
<a href="#">60082</a>
<a href="#">60083</a>
<a href="#">68052</a>
<a href="#">68103</a>

<a href="#">68531</a>	
<a href="#">68706</a>	
<a href="#">68728</a>	
<a href="#">68729</a>	
<a href="#">68772</a>	
<a href="#">69156</a>	
<a href="#">69465</a>	
<a href="#">78509</a>	
<a href="#">80502</a>	
<a href="#">80583</a>	
<a href="#">80584</a>	
<a href="#">80814</a>	
<a href="#">81424</a>	
<a href="#">81463</a>	
<a href="#">81464</a>	
<a href="#">81465</a>	
<a href="#">81627</a>	
<a href="#">81628</a>	
<a href="#">81853</a>	
<a href="#">85099999</a>	
<a href="#">97120</a>	
<a href="#">LP 10 PVDF/FPM</a>	
<a href="#">34877</a>	Membrane flange for membrane Ø52 PP/Ms MEMDOS E/DX 4 - 25 + 83619 Cylinder screw M6x20 DIN 912 A2 + 29462 Membrane insert for membrane Ø52 PPO + 80816 O-ring Ø79x2.5 NBR + 34868 Diaphragm rod M4 1.4305 MEMDOS E/DX - 75 + 80814 Compact seal Ø14/22x5.5 94AU925 + Wiper Ø14/22x7 Type AUASOB Simritan + 81464 Diaphragm Ø52 EPDM/PTFE-coated Base material 70EPDM281 with fabric insert
<a href="#">83619</a>	200121M0602020 Cylinder screw M6x20 DIN 912 A2
	Motor diaphragm dosing pump 0104A0004CF11A2K2KC1FC1F Product: MEMDOS Type: LA Flow rate: 4 l/h at 50/60 Hz against max. 12 bar Material dosing head and valves: PVC Electric drive: 230 V 1ph 50/60 Hz 0.37 kW with motor 0.18 kW Electrical connection: 1.8 m power cable with plug,

<a href="#">MEMDOS LA 4 PVC/FPM</a>	Europe (at 230 V AC) Suction valve: DN4 double ball ceramic/PVDF/FPM (ball/seat/seal) Pressure valve: DN4 double ball ceramic/PVDF/FPM (ball/seat/seal) Material suction connection: PVC Suction connection: hose clamp connection 6/12, short Material pressure connection: PVC Pressure connection: hose clamp connection 6/12, short Functions: Stroke frequency can be adjusted from 0 - 100% using a potentiometer Signal LEDs for status, operation and error display Analogue input 0/4 - 20mA Level input with main alarm Release input for external start/stop Hub feedback output alarm relay output Analogue output 0/4 - 20mA ---- A NOTICE: The successor to the MEMDOS DX type, the MEMDOS LP, is currently not available. We offer another alternative here.
<a href="#">SDL-2 DN10 PVC L=1100</a>	Suction Line 0122N0010C5U1100BP200K0025S Suction lines Product: Suction line Version: Rigid, non-return valve, level control, protection pipe Ø40 Nominal width: DN10 (200 l/h) Material: PVC Suction connection: Threaded spigot G3/4 M Suction line length: 1100 mm Gasket material: FPM + EPDM (both added) Level control: PP float Number of switching points: 2 Material hose: without suction hose Hose length: - Tank connection: with screwing cap K60x6 Special design: without Electrical connection: free cable ends without plug free cable length: approx. 2.5 m Switching function: Contact on rising level Switching voltage: max. < 50 V DC; < 50 V AC Switching current: max. 1 A Switching power: max. 20 VA (protective contact relays at inductive loads)
<a href="#">SDL-2 DN10 PVC L=1100</a>	suction line Match code: 0122N0010C5U1100BP200K0025S suction lines Product: suction line Execution: rigid, non-return valve, level monitoring, protective tube Ø40 Nominal width: DN10 (200 l/h) Material: PVC Suction connection: threaded pin G3/4 outside Suction line length: 1100 mm Gasket material: FPM + EPDM (both included) Level monitoring: PP float Number of switching points: 2 Material hose: without suction hose Hose length: - Tank connection: with screw cap K60x6 Special version: without Electrical connection: free cable ends without plug free cable length: approx. 2.5 m Switching function: normally open when the level rises Electrical load capacity of the float switch Switching voltage: max. < 50 V DC; < 50VAC Switching current: max. 1 A Switching capacity: max. 20 VA (contact protection relay for inductive loads)
<a href="#">68487</a>	Shaft set for bearing bracket A1 Ø35 1.4305/pc
<a href="#">68531</a>	GLRD 35 E Mechanical seal Ø35 eMG1/35-G7 Q7 Q1 EGG independent of direction of rotation complete with split pin
<a href="#">68177</a>	Stud bolt set for BN and N pumps for mechanical seal B2D and B2Q E-steel STUD BOLT SET
<a href="#">50357</a>	Back plate complete for shaft Ø35 PP/1.4305 N/BN pumps
<a href="#">68485</a>	Bearing cap set for bearing bracket A1 N 32/40/50-200, N 50-160
<a href="#">68484</a>	Bearing carrier housing set A1

<a href="#">68059</a>	O-Ring-Satz N/BN 50-160,50-200 EPDM
<a href="#">69000</a>	Suction nozzle DN80 PP/EPDM N/BN 50-160
<a href="#">50289</a>	Impeller cap LH for shaft Ø35 PP/Ms58
<a href="#">50211</a>	Spiral casing for N/BN 50-160 PP
<a href="#">34174</a>	
<a href="#">10499357 /Memdos E160 Pvc</a>	
<a href="#">35043</a>	
<a href="#">Magdos Dx 2 Obsolete, Replaced By Magdos Lp 2 Pvc/Fpm</a>	
<a href="#">Magdos Lt 6 230v Pvdv 10208322</a>	
<a href="#">28400</a>	
<a href="#">Adjustment Knob Memdos E/Dx 160...380</a>	
<a href="#">99393</a>	
<a href="#">10241147</a>	
<a href="#">Fedos E-8</a>	
<a href="#">Magdos Ld 4 Pvc/Ss/Fpm</a>	
<a href="#">79407</a>	
<a href="#">39911</a>	
<a href="#">Magdos Lb 4 Pvc/Fpm(10211005)</a>	
<a href="#">Magdos Dx 40 Pvc</a>	
<a href="#">21469</a>	
<a href="#">10208381 - Obsolete , Replaced By Magdos Ld 4 Pvc/Ss/Fpm</a>	
<a href="#">Minidos A 24 (10301005)</a>	
<a href="#">91195</a>	
<a href="#">814080-1</a>	
<a href="#">80815</a>	
<a href="#">Exproof Panel For Memdos Lb</a>	
<a href="#">Accessory Kit For Magdos Pvc/Fpm</a>	
<a href="#">34173</a>	

[10407624](#)

[Magdos Lt 06 230v Pvdf \(Dn3\) 10208333](#)  
[Matchcode: 0102I0006v001a33v1bv1b4](#)