



Madgetech

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Madgetech Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Madgetech T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
Hitemp140x2-Td-Fp-12	mt-901913-00 Data logger with rigid probe 508 mm and flexible probe 305 mm, including NIST certificate 30 ° C and 140 ° C Measuring range -60 ° C ... + 260 ° C (probe only), data logger -40 ° C ... + 140 ° C, max. 4 bar (60 PSIA), storage 32,700 Measured values, IP68
mt-900140-00	HiTemp140-1 data logger with immersion probe 27 mm, incl. NIST certificate at 30 ° C and 140 ° C Measuring range -200 ... + 260°C (probe only), 32,700 Measured values, IP68 HiTemp140 with flexible probe available with various probe lengths, please specify model when ordering
mt-900211-00	HiTemp140-FP-12 data logger with flexible probe 305 mm, including NIST certificate at 30 ° C and 140 ° C Measuring range -60 ° C ... + 260 ° C (only probe), data logger -40 ° C ... + 140 ° C, max. 4 bar (60 PSIA), memory 32,700 Measured values, IP68 HiTemp140 with flexible probe available with various probe lengths, please specify model when ordering
mt-900992-00	PR140 pressure logger with NPT connection can be used up to 6.9 bar, IP68, 25 mm x 58 mm, food safe for autoclave validation and Steam sterilization
mt-900998-00	PR140 pressure logger with flush top can be used up to 6.9 bar, IP68, 25 mm x 51 mm, food safe for autoclave validation and Steam

	sterilization simple interface
mt-900319-00	IFC400 USB interface for HiTemp140, PR140 various accessories, consumables, ... for HiTemp140 / Pr140
mt-900097-00	Replacement battery ER1425S-HT for HiTemp140 / PR140 Lithium, 3.6 V, 500 mAh, size 1/2 AA up to 150 ° C
mt-900229-00	O-ring set for HiTemp140 series
mt-900332-00	KEY RING END CAP fastening cap with eyelet for HiTemp140, PR140, RHTemp1000 series (for IS certified loggers only if installed by the manufacturer)
mt-902011-00	SVP Secure System - MadgeTech 4 Secure Validation Software Package IQ/OQ/PQ Secure Software Validation Workbook and Software Package, 21 CFR Part 11
mt-900385-00	MT-AluCase-18 transport and storage case Internal dimensions 44.45 x 34.04 x 14.99 cm / external dimensions 47.63 x 38.10 x 15.24 cm / foam insert can itself be adjusted RTDTempX data logger with 12 inputs
mt-902173-00	RTDTempX12 temperature data logger, Pt100, 12 channels Measuring range -200 °C to +850 °C (depending on sensor) ****RTDTempX data logger with 12 inputs***
Pt100	Pt100 probe for "dry heat sterilization / dehydrogenation" Sensor Pt100 4-wire class AA according to DIN IEC 751; probe Sheath 1.4541, diameter 3 mm, probe length: 150 mm, bendable; Transition sleeve stainless steel 6 x 40 mm, encapsulated; Fiberglass cable insulated with steel braiding, length 5 m; Application range up to 350 ° C (dry heat sterilization + dehydrogenation process); Connection free ends; Customs number: 9025 9000 Origin country: Germany
RHTemp1000Ex	902154 MadgeTech RHTemp1000Ex data logger Humidity + temperature Measuring range 40°C ... + 80°C / 0 ... 100% RH, memory 16,384 measured values, intrinsically safe, ATEX / IECex specifications see website, incl. traceable NIST certificate
MadgeTech IFC400 USB interface	900319 for HiTemp140, PR140 and 1000 data loggers
MT-902213-00	FM certified (no ATEX approval!) MadgeTech RHTemp1000IS data logger Humidity + temperature (intrinsically safe, Class I, Division 2, Groups A, B, C & D), including NIST traceable Certificate, measuring range 40°C ... + 80°C / 0 ... 100% RH, Memory 16,384 measured values
MT-902154-00	ATEX, IECEx, FM 3610 Certified MadgeTech RHTemp1000Ex data logger Humidity + temperature Measuring range 40°C ... + 80°C / 0 ... 100% RH, memory 16,384 measured values, intrinsically safe, ATEX / IECex specifications see website, incl. traceable NIST certificate
Madgetech	
Madgetech	
MT-902170-00	MadgeTech TCTempX4LCD data logger, 4 channels, thermocouple 4 channels for thermocouple (type J, K, T, E, R, S, B, N), with Display, incl. battery and USB Micro B cable, without sensor (please order separately) Origin: US Customs #: 9025 8050
MT-900140-00	MadgeTech HiTemp140-1 data logger, probe 27 mm rigid with 27 mm long rigid immersion probe, measuring range -200...+260°C

	(probe only), 32,700 readings, IP68, incl. NIST Certificate at 30°C and 140°C Origin: US Customs No.: 9025 1900
HiTemp140	-40+ -140
MT-902154-00	MadgeTech RHTemp1000Ex data logger humidity+temperature Measuring range 40°C...+80°C / 0...100%RH, memory 16,384 Measured values, intrinsically safe, ATEX/IECex Specifications see website, incl. traceable NIST certificate
MT-902208-00	MadgeTech RHTemp1000Ex-KR data logger humidity+temperature with key ring end cap, measuring range 40°C...+80°C / 0...100%RH, memory 16,384 readings, intrinsically safe / Intrinsically Safe, ATEX/IECex specifications see website, incl. traceable NIST certificate
MT-902213-00	ATTENTION ! The RHTemp1000IS data loggers have no (!) ATEX approval. (intrinsically safe, Class I, Division 2, Groups A, B, C & D), incl. NIST traceable certificate, measuring range 40°C...+80°C / 0... 100%RH, memory 16,384 readings
MT-902218-00	MadgeTech RHTemp1000IS-KR data logger humidity+temperature Measuring range 40°C...+80°C / 0...100%RH, memory 16,384 Readings, with installed Key-Ring end cap, intrinsically safe / Intrinsically Safe, Class I, Division 2, Groups A, B, C & D, incl. traceable NIST certificate
MT-902214-00	ATTENTION ! The Temp1000IS data loggers have no (!) ATEX approval. Temp1000IS-1 data logger, probe 25mm Measuring range 40°C...+80°C, memory 65,536 measured values, with 25 mm probe and standard (flush bottom) end cap (intrinsically safe / Intrinsically Safe, Class I, Division 2, Groups A, B, C & D), incl. NIST certificate traceable certificate The Temp1000IS is available with the following probe lengths: 1", 2", 5.25", 7". The Temp1000IS is available in the "Flush
MT-900319-00	for HiTemp140, PR140 and 1000er Datenlogger
MT-900319-00	MadgeTech IFC400 USB-Interface HiTemp140, PR140 und 1000er Datenlogger
Hitemp140-1	HiTemp140-1 data logger with immersion probe 27 mm, incl. NIST certificate at 30 ° C and 140 ° C Measuring range -200 ... + 260°C (probe only), 32,700 Measured values, IP68
Prhtemp2000	
Rfprhtemp2000a	
Ew-18010-15	
Avs140-1	AUTOCLAVE VALIDATION SYSTEM: INCLUDES (1) HITEMP140 DATA LOGGER WITH NIST CALIBRATION CERTIFICATE, IFC400 INTERFACE CABLE, (1) LICENSE MADGETECS FDA
Shock101-50-Eb	
Block Data Loger	
Ifc200 Usb-Interface Für Madgetech Standard	Datenlogger Serie u.a. für QuadVolt, OctVolt, QuadTcTemp2000V2, OctTcTemp2000V2, QuadThermoVault, OctThermoVault
Level1000	
Svp-Securesystem	IQ/OQ/PQ SECURE SOFTWARE VALIDATION WORK BOOK AND SOFTWARE PACKAGE.

Quadthermovault	
Rhemp101a - Humidity And Temperature Data Logger / Range -40*C To +80*C	
Pr140	
Rhemp101a	
Pr140-Lvl	
Hitemp 140-Fr	
Ifc200 Usb Interface Cable For Standard	
Hightemp 140-1	
Tc101a	
Ifc400	
Oct-Quad-Thermobarrier	THERMAL BARRIER FOR QUADTEMP AND OCTTEMP
Rhemp1000is	
Pr140 Pressure Data Logger	
Prtemp1000d-100	0-100 PSID, DIFFERENTIAL PRESSURE, TEMPERATURE RECORDER
Rfc1000	
Pr 140 Range : 0 To 5 Bar Pressure Data Loger For High Temperaturs	
Prtemp1000d-500	0-500 PSID, DIFFERENTIAL PRESSURE, TEMPERATURE RECORDER
Pr140 - Pressure Data Logger / Range 0 To 5 Bar	
Avs140-6 Autoclave Validation System	
Rfrhemp2000a	
Ifc400 Interface	
Ifc200	
Prtemp140-Npt	HIGH TEMPERATURE PRESSURE DATA LOGGER WITH NPT PORT TOP
Hitemp140-1 High Temperatur Presure Data Logger	
Hitemp140x2 Dual Probe Data Logger	
Octthermovault	8-CHANNEL OVEN TEMPERATURE PROFILER AND AMERICAN POWER SUPPLY
Hp-1	
Hitemp140x2	
Avs140-6	AUTOCLAVE VALIDATION SYSTEM: INCLUDES (5) HITEMP140 DATA LOGGERS AND (1) PR140 NPT WITH NIST CALIBRATION CERTIFICATES FOR ALL, IFC406 MULTIPLEXER DOCK
Prtemp1000is-300-Psig	