

Magnet Schultz



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Magnet Schultz Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Magnet Schultz Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Awef 004 A05	24 VDC Measuring path - + 4 mm Execution according to the attached, identical. drawing
Ip0065	
E-G 028-446 G PC	purge/drain valve
GFCX040X00B12	G004079001 GS magnet 24V 100% ED 8.0mm 12.20N 0.590 amps CU & Leg. 0.094kg Execution according to attached, the same. Dimensional drawing
GTCA060X43A01	GS magnet DCV + 6 / -10% 100% ED 12mm 22.00N 25.5 WATT 35 ° C 1.100 amps Wickl. 0.301kg Execution according to attached, the same. Dimensional drawing
GTCA060X43A01 DC24V +6/-10% S3 5%ED 12mm	GS-Magnet 130.00N 376 WATT 15.700Amp 35 ° C Wickl. 0.320kg CU price 6.66EUR / kg Execution according to attached, the same. Dimensional drawing
GDAY050X20B21	G003844001 Rotary solenoid 24V 100% ED 65 ° rotation. 2.4Ncm 0.550 amps Execution according to the attached, the same. Dimensional drawing
WZAW060 X00 D31 200V173VA	
GTAF020M20A01	GS magnet 24V 100% ED 3.0mm 1.70N 0.160 amps Wickl. 0.012kg CU Execution according to the attached, the same. Dimensional drawing
GTAF020N20A01	GS magnet 24V 100% ED 3.0mm 1.70N 0.160 amps Wickl. 0.012kg CU Execution according to the attached, the same. Dimensional drawing
GBKK017K00A01	GS magnet 24V + 5 / -10% 100% ED 2.5mm 1.00N 7.0 WATT 35 ° C 0.293 amps Wickl. 0.008kg CU Execution according to the attached, the same. Dimensional drawing
GBKK017L00A01	GS magnet 24V + 5 / -10% 100% ED 2.5mm 1.00N 7.0 WATT 35 ° C 0.293 amps Wickl. 0.008kg CU Execution

	according to the attached, the same. Dimensional drawing
GBKP017K00A01	GS magnet 24V + 5 / -10% 5% ED 3.0mm 1.00N 36.5 35 ° C 1.520 amps Wickl. 0.007kg Execution according to the attached, the same. Dimensional drawing
GBKP017K00A02	GS magnet 24V + 5 / -10% 5% ED 3.0mm 2.20N 36.5 35 ° C 1.520 amps Wickl. 0.007kg Execution according to the attached, the same. Dimensional drawing
GRFY060F20B01	Proportional solenoid 24V 100% ED 8.0mm 145.00N 1.110A Wickl. 0.338kg CU price 8.49EUR / kg CU & Leg. 0.026kg Execution according to the attached, the same. Dimensional drawing
GDAY035X20B23	Rotary solenoid 24V 100% ED 35 ° rotation. 1.19Ncm 0.290 amps CU & Leg. 0.028kg CU price 8.08EUR / kg Execution according to the attached, the same. Dimensional drawing
GDAY035X20B03, 24VDC, 25%ED	
GDAY035X20B03, 24VDC, 5%ED	
GDAY035X20B03, 24VDC, 15%ED	
GDAY035X20B03, 24VDC, 40%ED	
GDAY035X20B03, 24VDC, 100%ED	
GDAY035X20B23 24V 5%ED	Rotary magnet = 24V 5% ED 35 ° rotation. 5.14Ncm 105 WATTS 4,350 amps Execution according to attached, the same. Dimensional drawing
1 piece blocking magnet (successor type) 110V DC	DC high-performance single stroke solenoid 110V DC (+ 10 / -15%) with locking bolt 8 mm diameter with integrated electronics Power 14W
1 piece blocking magnet (successor type) 220V DC	DC high-performance single stroke solenoid 220V DC (+ 10 / -15%) with locking bolt 8 mm diameter with integrated electronics Power 14W
GDPR012X00A12	Ist es m¼glich, eine zus¼tzliche Operation an der D-f¼rmigen Fl¼che auf der Welle des entsprechenden Magneten vorzunehmen? Kann die Schaftl¼nge ge¼ndert werden?
GDAY035X20B23 40%ED	Rotary magnet = 24V 40% ED 35 ° rotation. 2.42Ncm 0.670 amps
GDAY035X20B23 100%ED	Rotary magnet 24V 100% ED 35 ° rotation. 1.19Ncm 0.290 amps
GMHX065X20A01	GS holding magnet 24V 100% ED 0mm 1,432.00N 9.5 WATT 35 ° C 0.410 amps CU & Leg. 0.189kg CU price 8.03EUR / kg Execution according to attached, the same. Dimensional drawing
RS Pro Magnetic Lock, 1670N	739-3233 65mm 24VDC 1670N
WABX 035-F43-B02(110V 50HZ, 100%ED S5,5mm F14)	

0009736026
066293
100223493
1441743
301.RD28.0909ET001
35000727
35000733
35000760
35000763
35002809
A0900109
AW EX 020 A01
G000912001
G001058001
G003844001
G003889001
G003902
G005117001
G005914001
G006001001
G007076001
G008093002
G009125002
G009126002
G009471001
G012572001
GAAX 035 F20 D02
GDAE 060 AXD E01
GDAY 025 X20 E03
GDAY 060 X20 B03

GDAY 060 X20 B25	
GDRX 050 X20 A01	
GFCX 035 X00 B12	
GMPX 050 X00 B01	
GRFY 035 F20 B01	
GRFY035F20E58	
GSCX 063 M30 B01	
GSCX037M43D01	
GTCA 040 X43 A21	
KSBX 066 X00 A01	
KZZM 066 X00 A01	
msm grfy 035 f20	
VACE-B-K1-3A-5-EX4-M	
W ZA W 080 X00 A01	
WBAX 050 A00 A01	
WX-2170-301	
WZAW 060 X00 D31	
YZAW 080X00 A01	
YZUW 120 X00 A01	
YZUW 120 X00 D05	
YZUW090X00A01	
Z258-00228-99999	
VR032AA035V12	
GFCX 040X00E22	
VR032AA035V04	
0501980110K	Typ : 110V DC Earth Locking Solenoid Assembly
WZAW060 X00 D31 200V173VA	
GBRE022AMXE05V	
G012358001	GDAE060AXDE01 rotary magnet Ex II 3D Ex mc IIIC T120°C Dc X 24V 100% ED 35° rot. 9.9Ncm 0.532 amps Execution according to attached, equals dimensional drawing

GDAX050X20B21	G003828002 rotary magnet 24V 100% ED 95° rot. 0.77Ncm 0.550 amps CU&Leg. 0.087kg Execution according to attached, equals dimensional drawing
WZAW_060_X00_D31	
GRFY035F20B01	GS proportional solenoid 24V 100%ED 4.0mm 50.00N 0.680A CU&Leg. 0.087kg CU price 7.92EUR/kg Execution according to attached, equals dimensional drawing
GRCY-037	
GRCY-045	
GRYF-035	
GRFY-045	
Oscillating magnet type WZAW060X00D31	for : GL 1 Rated voltage : 200V 50Hz Vibration frequency : 100Hz Power : 173VA Potting compound : black in CE / CSA UL design Magnet including anchor
Magnet Typ OAC009.500042	for : SRC-N 400-1/630-1 Rated voltage : 200V 50Hz Vibration frequency: 50Hz Power : 251VA Potting compound: red in CE / CSA UL version Magnet including anchor Replaces YZAW080X00D20
GFCX_040_X00_E22, 240 V DC, ED=S1	
GBRE022AMXE05V	
Typ OAC009.500096	for : SRC-N 400-2 Rated voltage : 200V 50Hz Vibration frequency: 100Hz Power : 284VA Potting compound : black in CE / CSA UL version Magnet including anchor Replaces WZAW080X00D13
MSM GRFY030F20D06	
WZAW_060_X00_D31	200V 50 Hz 173VA ED:S1 s:1mm 2265413 35000727
GHUZ040M30A02	GS locking unit 24V 100%ED 8.0mm 6.30N 0.440Amps CU&Leg. 0.068kg CU price 7.78EUR/kg Execution according to the attached, identical. Dimensional drawing
G008095002	GDRX035X20A01 24V +6/-10% 100%ED 110° rotation 2.0Ncm 35°C 0.273Amps winding 0.018kg CU price 7.82EUR/kg Execution according to the attached, identical. Dimensional drawing
WHDX_025_E00_D08) 230V	
GFCX_040_X00E22	827367
MSM-GRFY025F20-E05 24V-1G-0,65A	
YZUW_120	
WZAW_80	
WZUW_080	

YZUW120	
GHUZ040M30A02	G006672001 GS locking unit 24V 100%ED 8.0mm 6.30N 0.440 amps CU&Leg. 0.068kg CU price 8.58EUR/kg Execution according to the attached, identical dimensional drawing
Yzaw 080x00 A01 Chwingmagnete Typ Yzaw 080 X00 A01200 V/50 Hz, S1	
Gtca 040 X43 A21 Gs-Magnete	
Wzaw 060 X00 D31 Elektromagnet	
A9900003	
Asew001d08-Ip65	
Gbre022amxe06w	
W Za W 080 X00 D13 Solenoid Vibrating	
Gbre022amxe07v	
Awex 020 A01 Sensor	
Typ Yzaw 080 X00 A05	vibrating solenoids 230 V / 50 Hz, S1 Version according to enclosed, gleichlt. Drawing
Gscx063m30b01 Elektromagnet	
Permanent-Elektro-Haftmagnete Typ Gmpx 050 X00 B0124 Vdc, S2	
Ghpy 045 N54 A01	
Elektromagnet Gtaf020n20a01	
Msm Grfy 035 F20 Ventil	
Ghuz 050 E 43 A03 Knoten Blockierende	
W Za W 080 X00 D04 Solenoid Vibrating	
Siehe Bilder	Resistance 200 ohm Diameter 17 220 v Elektro Ventil
Ghuz 050 E43 A01	
Solenoid Magnet-Schultz Ghuz 050 E43 A01 24 Vdc, S1	
Electromagnetic Solenoid (Grfy 045 F 20 Bo1) S1(100%) - 12v	
Gaax035f20d02 Solenoid	
Gbrer022amxe05v	
Msfg-24dc-M-Ex	

Yzuw 120 X00 D05 Elektromagnet 220v/50hz, 100% Ed	
Gday 060 X20 B03 Magnet24 Vdc, 100% Ed, 35 Drehwinkel	
Gfcx035x00b12 24v	
Xbpx-030-K54-A01	
G Da Y 65 060 X20 B25 Rotary Solenoid	
Gzze030	
Ghuz 050 E43 A03	
Ghuz040m30a02	
Yzuw 120 X00 D05 220v/50hz, 100% Ed	
Grcy 037 N54 A01	
Grfy 045 F20 E11 High Pressure Solenoid Valve	
Gtca050x43a02	
Awex020d06	
Grfy060f20b01	
Msm 2398206	
Whcx070f20d05	
Wbax 030 A00 A01	
Ghmx080x20a01	
Grfy 045 F20 B01	
Gscx037m43d01 Elektromagnet 220v Dc	
Yzaw 080 X00 A05	GS-vibrating solenoids 230V / 50Hz, 100% ED Version according to enclosed, similar. drawing
Ghuz040n30a01	
Proportional Solenoid (Grfy 045 F 20 Bo1) S1(100%) 24v	
902190001	
Yzaw 080 X00 A05 Elektromagnet	
Elektromagnete Wzaw 060 X00 D31	
Magnet 24v 000 973 6026	
2619674 Yzaw 080 X00 D19 110v 50hz 251 Va S=2.5	

Gdae060axde01 Dc 24 V 11 W	
Ghuz 050 E43 A01 Elektrischer Solenoid	
35000758	
35003343	
Wzuw080x00d11	
Gmpx 050 X00 B01 Magnet24v 100%ed	
Gakx 065 E34 D03	Schindler Id. Nr. 987200
Yzaw080x00d20	
Gdae060axde01	
Proportional Solenoid (Grfy 035 F 20 B01) S1 (100%)	
Ghuz 050 E43 A03 Elektromagnetische Schutzschalter Lockout	
Gdrx 050 X20 A01 Solenoid Rotary	
Gmhx030	
301.Rd28.0909et001 Schmieroelpumpenmagnetgaax025f20d01 24v Dc	
W Za W 080 X00 A01 Solenoid Vibrating	
100223493 Prop. Magnet Gs 24v Ri 12-13,5proportionalmagnet	
Grfy035f20b01 Solenoid	
Elektromagnet Gfcx035x00b12	
2619674 Vibrator Zaw 080 X00 D19 110v 50hz 251 Va S=2.5 Mm	
Ghuz032m30a0124vdc	
W Za W 060	
Gday 025x20e03 Solenoid	
9115375-100	
Yzuw120x00d05 Electromagnet	
Wzuw 080 X00 D11 Magnet	
Vr032aao3507 12volt	
	oscillating magnet for GL1 Rated voltage : 200V 50Hz Vibration frequency : 100Hz Power : 173VA Potting

WZAW060X00D31	compound : black in CE / CSA UL design Magnet including anchor
Elektromagnetischer Vibrator Wzaw 080x00 A01 (230v 50hz 205va)	
35000739 Magnet	
Schwingmagnet Typ Yzuw 090 X00 A01230 V/50 Hz, 100% Ed	
Asew001d10	
Gdae 060 Axde 01	
- Solenoid Wzaw 040 X00 D13 Magnet Schultz	
Yzaw 080 X00 D21 - Magnet Schultz	
Ghuz 040 N30 A02	
Yzaw 080 X00 A05 Schwingmagnet 230v/50 Hz, S1	
Grfy035f20e58 Solenoid	
W Za W 080	
Typ Gtca 060 X43 A02	GS-Magnete 24 VDC, 100% ED, s = 12 mm Version according to enclosed, gleichlt. Drawing
35000721	
Typ Gtca 060 X43 A03	GS-Magnete 24V D C, 100% ED, s = 12 mm Version according to enclosed, gleichlt. Drawing
Msm 6/55228 Ghuz 050 E43 A03 Magnet Msm 6/55228 Ghuz 050 E43 A03 24v 100%ed	
9/82021 Elektromagnet Bax 050 A00 A01 220v 50hz 25% Ed Mm S40	
Yzuw090x00a01 Elektromagnet	
Schwingmagnet Typ Wzaw 060 X00 A03	
Gfcx 030 X00 B12	GS-magnet 24 VDC, S1, s = 5 mm, FM approx.4.3 N Execution according to the attached, identical. Dimensional drawing
35000739	
Ghuz 050 E43 A01 Solenoid Elektrisch24 Vdc, 100%	
Gbre022amxe05v	
Verriegelungseinheit Typ Ghuz 050 E43	

[A03205vdc_100%_Fd](#)