

Mapro

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Mapro Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Mapro T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Side channel blower CL 98/1 G	Scope of delivery: · Single-stage side channel blower CL 98/1 G · Bare shaft with free shaft end · Without electric motor, coupling and base frame · Threaded flange at the inlet and outlet, IG 4 " · Condensate drain cock · Rubber buffers for installation · Complete assembly of the assembly, testing and painting according to our standard (Color: RAL 5010) ATEX certificate for category 2G for indoor use (Ex zone 1) · Identical to CL 98/1 G - S / No. 530115 B
Pipe bends at the entrance and exit, DN 100	
CL 520-6K3 HS	side channel compressor Scope of delivery: · Single-stage side channel blower CL 520-6K3 HS · Electric motor 4.0 kW , 3-ph., 400/690 V, 50 Hz, 2-pin, IP54, iso cl. F, thermal contact 125° · Inlet and outlet silencers · Threaded flange at the inlet and outlet, IG 2" · Complete assembly of the assembly, testing and painting to our standard (Colour: RAL 7032)
	side channel compressor Scope of delivery: · Single-stage side channel blower CL 720-5K3 HS · Electric motor 4.3 kW ,

CL 720-5K3 HS	3-ph., 400/690 V, 50 Hz, 2-pin, IP54, iso cl. F, thermal contact 125° · Inlet and outlet silencers · Threaded flange at the inlet and outlet, IG 2" · Complete assembly of the assembly, testing and painting to our standard (Colour: RAL 7032)
Side channel blower CL 2R8	
CL 98/1 G - bare-shaft	side channel compressor Scope of delivery: · Single-stage side channel blower CL 98/1 G With free shaft end (bare-shaft) · Without base frame, coupling and electric motor Aluminum elbows at the inlet and outlet, DN 100 · Condensate drain cock · Rubber buffers for positioning · Complete assembly of the assembly, testing and painting to our standard (Colour: RAL 1021) · Certification of the entire assembly: o Inside: ATEX CE Ex II 2G Ex h IIB T3 Gb · Version identical to CL 98/1 G - S/No. 530115
CL 720 HS Blower	komplett
Gasfilter	· Aluminum body · Filter insert made of stainless steel, 100µ · Flange connections in DN 100
Side channel blower CL 50-6BU HS	Scope of delivery: · Single-stage side channel blower CL 50-6BU HS · Electric motor 2.2 kW, 3-ph., 230/400 V, 50 Hz, 2-pin, IP54, iso cl. F, thermal contact 125° · Inlet and outlet silencers · Threaded flange at the inlet and outlet, IG 2" · Complete assembly of the assembly, testing and painting to our standard (Colour: RAL 7032)
Gasfilter, DN 80	Aluminum body Filter insert made of stainless steel, 100µ Length: 312mm Colour: RAL5010
CL98/1 G EXPROOF	
MPF2	
MPF1	
Side channel blower CL 80-6K3-Z HS	Scope of delivery: • Single-stage side channel compressor CL 80-6K3-Z HS • Electric motor 7.5 kW, 3-phase, 345-415/595-720 V, 50 Hz, 2-pole, IP54, insulation class F, thermal contact 125 °C • Silencer at the inlet and outlet • Threaded flange at the inlet and outlet, G 2" ½ • Complete assembly of the module, testing and painting according to our standard (color: RAL 9006)
side channel blower CL 50/6BU HS	Scope of delivery: • Single-stage side channel compressor CL 50/6BU HS • Electric motor 2.2 kW, 3-phase, 200-240/345-416 V, 50 Hz, 2-pole, IP54, insulation class F, thermal contact 125 °C • Silencer at the inlet and outlet • Threaded flange at the inlet and outlet, G 2" • Complete assembly of the module, testing and painting according to our standard (color: RAL 9006) 3 pcs filter insert C8C (paper) for CL 50 HS
side channel blower CL 40/6BU HS	Scope of delivery: • Single-stage side channel compressor CL 40/6BU HS • Electric motor 1.1 kW, 3-phase, 200-240/345-416 V, 50 Hz, 2-pole, IP54, insulation class F, thermal contact 125 °C • Silencer at the inlet and outlet • Threaded flange at the inlet and outlet, G 1" ½ • Complete assembly

	of the module, testing and painting according to our standard (color: RAL 9006) 3 pcs Filter insert C6C (paper) for CL 40 HS
CL 520/6K3 HS	<ul style="list-style-type: none">• Two-stage side channel compressor CL 520/6K3 HS •Electric motor 4.0 kW, 3-phase, 345-416/595-720 V, 50 Hz, 2-pole, IP54, insulation class F, thermal contact 125 °C •Silencer at the inlet and outlet • Threaded flange at the inlet and outlet, G 2" • Complete assembly of the module, testing and painting according to our standard (color: RAL 9006)
CI 20/21 - Kw 3	
CI 1r9	
Fh8	
CI 72/1	
CI 23/21 - 5.5kw	
CI 23/21	
CI 46/1	
CI 60 Hs	
Sv10d	
CI 30/21	
CI 42/21	
CI 14/21	
Manometro	
Tbt/M	
CI 18/01	
CI 720 Hs	
CI 40/1	
CI 28/1	
CI 60/1	
CI 7/21	
CI 49/21	
CI 420 Hs	
CI 42/21hc	
CI 49/21 Kw 15	
Motor For Blower CI28/1	

CI 98/1
CI 220 Hs
CI 2r9
CI 30-Z Hs
CI 2r8
CI 1r5.5
CI 20 Hs
CI 36/21
CI 4/01
C10c
CI 22/01
Sv7t
CI 12/21
CI 10/21
CI 15/01
CI20/21s
CI 17/21
152-Hc-Pos16
CI 3.6/01
CI 49/21 - Kw11
CI 80-Z Hs
CI10/21 Kw 2.2
CI 30/21 - 7.5kw
CI 50 Hs
CI 7/01
C14
CI 60 M Kw 3
CI 84/1
CI 34/1
CI 40 Hs

[Cl 1r3.5](#)
[Suction Filter For Cl20/21s](#)

[Cl 10/01](#)

[Vr8](#)

[Vr7](#)

[Peg-580](#)

[Cl 520 Hs](#)