

## Marelli Motori

Garanti: 12 ay  
Bu rne ait Trkiye  
ii kapı teslim fiyat  
ve teslim sresi  
ieren teklifimizi  
almak iin  
**info@yursat.com.tr**  
e-posta adresine  
baŐvuru yapabilir ya  
da ayrıntılı bilgi iin  
+90 224 240 03 04  
numaralı  
telefonumuzdan  
bizlere  
ulaŐabilirsiniz.  
**Marelli Motori**  
Markası, tedarik  
sresi iin ltfen  
bizimle iletiŐime  
geiniz.

*Firmamız Marelli Motori  
Trkiye Distribtr veya  
temsilcisi deĐildir. Firmamız  
sipariŐ durumunda,  
belirtilen rnlerde sadece  
Orjinal ve yeni rn teklifi  
sunmaktadır. Bu sitede  
gsterilen zel marka adları  
ve ticari markalar ilgili  
sahiplerinin  
mlkiyetindedir, talep  
durumunda  
kaldırılmaktadır.*





rn	Aıklama
<a href="#">6202-2Z</a>	
<a href="#">(Mjh 710 Rotating Rectifier )</a>	
<a href="#">(Mjh 710 PMG )</a>	
<a href="#">Order: H30816</a>	
<a href="#">MA 71 MB4 - B3</a>	
<a href="#">D6C0802A00017</a>	
<a href="#">D6C0962A00017</a>	

<a href="#">M6Q 80 MB4</a>	<ul style="list-style-type: none"> <li>• General specifications</li> <li>• Rated outputs and efficiency values are in accordance with IEC 60034-30-1</li> <li>• all parameters are measured in accordance with IEC 60034-2-1;</li> <li>• continuous duty (S1) with sufficient thermal margins to withstand short overloads;</li> <li>• IP 55 protection degree;</li> <li>• F insulation class;</li> <li>• + 40°C maximum ambient temperature;</li> <li>• 1000 m a.s.l. installation. Technical features</li> <li>• Terminal box can be rotated by 90°;</li> <li>• drive end locked bearing from 160 mm frame size;</li> <li>• PTC in main terminal box from 160 mm frame size;</li> <li>• grease nipples (drive end and non drive end) as standard from 160 mm frame size.</li> <li>• 4 POLES - 400 V - 50 Hz</li> </ul>
<a href="#">Type: MJB 355 MA 4 (cod. MJB3532G067M0 - 13011021)</a>	<p>Design: IM B34 Rated power [kVA] : 680 Speed / [rpm]: 1500 Voltage / [V] : 400 (+/-5%) Connection: Star series (12 conductors) Frequency / [Hz] : 50 Cosphi: 0.8 overexcited Operating mode: S1 Exploitation according to: H Insulation class: H Max. ambient temperature / [°C] : 40 Protection class: IP 23 Cooling type: IC 01 Max. installation height above sea level / [m]: 1000 Spin speed / [rpm]: 2250 Direction of rotation: Clockwise (viewed from A side) Electrical connection: In the terminal box Phase sequence: Right (U-V-W) Cable outlet: Right (seen from A-side) Paint [RAL] : 5010 Included: - Item 101: Auxiliary winding - Pos. 117: Parallel operation generators (static device) - Pos. 139: Relubrication device (A side) - Digital AVR MEC-20, cod. M31FA600A or AVR E-Vo, cod. M31FA605A (depending on availability)</p>
<a href="#">A2C 71 MA2</a>	<p>Mounting Type : IM B14 Rated Power / [kW] : 0,37 Rated Speed / [rpm] : 2745 Voltage / [V] : 400 Connection : Star Frequency / [Hz] : 50 Starting Method : DOL (direct-on-line) Duty Cycle : S1 Temperature Rise Class : B Insulation Class : F Max. Ambient Temperature / [°C] : 40 Protection Degree : IP 55 Cooling Type : IC 411 Max. Altitude a.s.l. / [m] : 1000 Direction of Rotation : Clockwise (cw) - seen from D-End Phase sequence: Right (U-V-W) Terminal box position : Top mounted Cable Entry : Right hand - facing shaft-end Final Color [RAL] : 5010 Weight / [kg] : 7</p>
<a href="#">A4c225m2 45kw B3 400v D 50hz Ip55</a>	
<a href="#">D1c132 Ma-4im B3</a>	
<a href="#">Ma132sb2- Obsolete, Replacement - Maq1311a 00017</a>	
<a href="#">Voltage Regulator Compatible With Code M16fa610a</a>	
<a href="#">M16fa650a</a>	
<a href="#">D1c90l4 B3 ? D1c0962a00010</a>	
<a href="#">Maq132sa4</a>	
<a href="#">Mjb 200 Mb 4 - B2</a>	
<a href="#">D4c160l4 B3 ? D4c1672a00020</a>	
<a href="#">A6c250m4 55kw B3</a>	
<a href="#">D5c1132b00016 , By D6c1132b00016</a>	
<a href="#">Nv 180 L6 B3</a>	
<a href="#">A5c2842q00016</a>	
<a href="#">B6q 225 S-4</a>	
<a href="#">D6c 100 La2 3kw B3 Ii 2g Ex D Iib T4 Gb 400v D 50hz Ip55 Zone 1</a>	
<a href="#">E4f160m4</a>	
<a href="#">0810041002 Maa132sa2 Obsolete - Replaced</a>	

<a href="#">By Maq1301a 00016 Maq132sa2 5,5kw B3</a>	
<a href="#">Maa 132 Sa2 B3 2890tr/Min 5.5kw</a>	
<a href="#">B6q 200 La2</a>	
<a href="#">Maq1301a 00016 Maq132sa2 5,5kw B3</a>	
<a href="#">D6c112m4 4kw B5</a>	Art Nr. D6C1132B00016 Net weight: 68 kG Customs tariff number: 85015220 400V / 690V 50Hz IP55 Ex IIB T4 Gb
<a href="#">Dn500 Ansi150</a>	
<a href="#">Maq0902b 00017</a>	
<a href="#">Maq1063c00017</a>	
<a href="#">M7b 250-315</a>	
<a href="#">D6c 132 Ma4b5</a>	
<a href="#">M16fa648b</a>	
<a href="#">B5h 355 Lb 4</a>	
<a href="#">A6c 225 S-4</a>	
<a href="#">Main Switchboard Station + Offset Mjb 400 Mb4</a>	
<a href="#">Maq0963c00017</a>	
<a href="#">100lb8</a>	
<a href="#">Kwa6c250m4b3</a>	
<a href="#">Maa0712b 00017</a>	
<a href="#">B5s3533a64822</a>	
<a href="#">M6q1062c00017</a>	
<a href="#">Mjb 400 - 311 Surge Suppressor</a>	
<a href="#">D6c 132 Sb2 7,5kw 2910rpm B3</a>	
<a href="#">A22dk1000 / A4c225/2-250/2</a>	
<a href="#">Art.Nr. Maa1342a 00016</a>	
<a href="#">W0d1600 / D5x160l4 15kw B3 -20/40 C</a>	
<a href="#">A6c 250 M4 B3 Ie3</a>	
<a href="#">Electric Transformer 1600 Kva 20/04 Kv Mjb 400 Mb4</a>	
<a href="#">M 40fa640a/Amark1 24166s - Voltage Regulator Replacement Vg</a>	
<a href="#">A22dk101</a>	
<a href="#">Man100la4-B35</a>	
<a href="#">Mjb 250 La 4 - B2</a>	
<a href="#">W0m4000 (Mjb 400 Mb 4 - B34)</a>	
<a href="#">Maa0962b00017 / 1.5 Kw</a>	MOT.3 MAA 90 L4 B5 Please see attached Photo
<a href="#">B4c3132a1 1116</a>	

[Autonomus Fan For Mot.3~ A4c 280 M2 B3 S](#)  
[Cod. A4c2841ax2616 N` S021521 06-06 I](#)

[Mjb 225 Ma 4 - B2](#)

[Maa1302c11116 \(Maa132sa4\) - Obsolete,](#)  
[Replacement Maq132sa4](#)

[Water Switchboard Station 30 Kw, 3 \\* 400v, 2](#)  
[Inverters + Automation Mjb 400 Mb4](#)

[Type: Ma 90s4](#)

[A4c2542aast16](#)

[D5s225m4](#)

[A4c250m4 B3 A4c2542a00016 By A6c250m4](#)  
[55kw B3](#)

[D6c 90 L2 B5](#)

[Sb35dv135c](#)

[90s-4](#)

[Maq1311a 00017](#)

[100lb-4](#)

[B5s 355 Ld6](#)

[A6c 280s-4](#)

[W0a2000 A5c200I8](#)

[D6c1132b00016](#)

[Baa 160 L8](#)

[E4f2243a00010](#)

[Maa 132 Sb2 B3 2910tr.Min 7.5kw](#)

[Szwc04343a](#)

[Mjb 355 Ma/4-Im B34](#)

[A4c28420a365](#)

[Pt100 Temperature Transmitter](#)