

Marelli Motori

Garanti: 12 ay
Bu rne ait Trkiye
ii kapı teslim fiyat
ve teslim sresi
ieren teklifimizi
almak iin
info@yursat.com.tr
e-posta adresine
baŐvuru yapabilir ya
da ayrıntılı bilgi iin
+90 224 240 03 04
numaralı
telefonumuzdan
bizlere
ulaŐabilirsiniz.
Marelli Motori
Markası, tedarik
sresi iin ltfen
bizimle iletiŐime
geiniz.

*Firmamız Marelli Motori
Trkiye Distribtr veya
temsilcisi deĐildir. Firmamız
sipariŐ durumunda,
belirtilen rnlerde sadece
Orjinal ve yeni rn teklifi
sunmaktadır. Bu sitede
gsterilen zel marka adları
ve ticari markalar ilgili
sahiplerinin
mlkiyetindedir, talep
durumunda
kaldırılmaktadır.*





¼r¼n	Açıklama
6202-2Z	
(Mjh 710 Rotating Rectifier)	
(Mjh 710 PMG)	
Order: H30816	
MA 71 MB4 - B3	
D6C0802A00017	
D6C0962A00017	

M6Q 80 MB4	<ul style="list-style-type: none"> • General specifications • Rated outputs and efficiency values are in accordance with IEC 60034-30-1 • all parameters are measured in accordance with IEC 60034-2-1; • continuous duty (S1) with sufficient thermal margins to withstand short overloads; • IP 55 protection degree; • F insulation class; • + 40°C maximum ambient temperature; • 1000 m a.s.l. installation. Technical features • Terminal box can be rotated by 90°; • drive end locked bearing from 160 mm frame size; • PTC in main terminal box from 160 mm frame size; • grease nipples (drive end and non drive end) as standard from 160 mm frame size. • 4 POLES - 400 V - 50 Hz
Type: MJB 355 MA 4 (cod. MJB3532G067M0 - 13011021)	<p>Design: IM B34 Rated power [kVA] : 680 Speed / [rpm]: 1500 Voltage / [V] : 400 (+/-5%) Connection: Star series (12 conductors) Frequency / [Hz] : 50 Cosphi: 0.8 overexcited Operating mode: S1 Exploitation according to: H Insulation class: H Max. ambient temperature / [°C] : 40 Protection class: IP 23 Cooling type: IC 01 Max. installation height above sea level / [m]: 1000 Spin speed / [rpm]: 2250 Direction of rotation: Clockwise (viewed from A side) Electrical connection: In the terminal box Phase sequence: Right (U-V-W) Cable outlet: Right (seen from A-side) Paint [RAL] : 5010 Included: - Item 101: Auxiliary winding - Pos. 117: Parallel operation generators (static device) - Pos. 139: Relubrication device (A side) - Digital AVR MEC-20, cod. M31FA600A or AVR E-Vo, cod. M31FA605A (depending on availability)</p>
A2C 71 MA2	<p>Mounting Type : IM B14 Rated Power / [kW] : 0,37 Rated Speed / [rpm] : 2745 Voltage / [V] : 400 Connection : Star Frequency / [Hz] : 50 Starting Method : DOL (direct-on-line) Duty Cycle : S1 Temperature Rise Class : B Insulation Class : F Max. Ambient Temperature / [°C] : 40 Protection Degree : IP 55 Cooling Type : IC 411 Max. Altitude a.s.l. / [m] : 1000 Direction of Rotation : Clockwise (cw) - seen from D-End Phase sequence: Right (U-V-W) Terminal box position : Top mounted Cable Entry : Right hand - facing shaft-end Final Color [RAL] : 5010 Weight / [kg] : 7</p>
A4c225m2 45kw B3 400v D 50hz Ip55	
D1c132 Ma-4im B3	
Ma132sb2- Obsolete, Replacement - Maq1311a 00017	
Voltage Regulator Compatible With Code M16fa610a	
M16fa650a	
D1c90l4 B3 ? D1c0962a00010	
Maq132sa4	
Mjb 200 Mb 4 - B2	
D4c160l4 B3 ? D4c1672a00020	
A6c250m4 55kw B3	
D5c1132b00016 , By D6c1132b00016	
Nv 180 L6 B3	
A5c2842q00016	
B6q 225 S-4	
D6c 100 La2 3kw B3 Ii 2g Ex D Iib T4 Gb 400v D 50hz Ip55 Zone 1	
E4f160m4	
0810041002 Maa132sa2 Obsolete - Replaced	

By Maq1301a 00016 Maq132sa2 5,5kw B3	
Maa 132 Sa2 B3 2890tr/Min 5.5kw	
B6q 200 La2	
Maq1301a 00016 Maq132sa2 5,5kw B3	
D6c112m4 4kw B5	Art Nr. D6C1132B00016 Net weight: 68 kG Customs tariff number: 85015220 400V / 690V 50Hz IP55 Ex IIB T4 Gb
Dn500 Ansi150	
Maq0902b 00017	
Maq1063c00017	
M7b 250-315	
D6c 132 Ma4b5	
M16fa648b	
B5h 355 Lb 4	
A6c 225 S-4	
Main Switchboard Station + Offset Mjb 400 Mb4	
Maq0963c00017	
100lb8	
Kwa6c250m4b3	
Maa0712b 00017	
B5s3533a64822	
M6q1062c00017	
Mjb 400 - 311 Surge Suppressor	
D6c 132 Sb2 7,5kw 2910rpm B3	
A22dk1000 / A4c225/2-250/2	
Art.Nr. Maa1342a 00016	
W0d1600 / D5x160l4 15kw B3 -20/40 C	
A6c 250 M4 B3 Ie3	
Electric Transformer 1600 Kva 20/04 Kv Mjb 400 Mb4	
M 40fa640a/Amark1 24166s - Voltage Regulator Replacement Vg	
A22dk101	
Man100la4-B35	
Mjb 250 La 4 - B2	
W0m4000 (Mjb 400 Mb 4 - B34)	
Maa0962b00017 / 1.5 Kw	MOT.3 MAA 90 L4 B5 Please see attached Photo
B4c3132a1 1116	

[Autonomus Fan For Mot.3~ A4c 280 M2 B3 S](#)
[Cod. A4c2841ax2616 N` S021521 06-06 I](#)

[Mjb 225 Ma 4 - B2](#)

[Maa1302c11116 \(Maa132sa4\) - Obsolete,](#)
[Replacement Maq132sa4](#)

[Water Switchboard Station 30 Kw, 3 * 400v, 2](#)
[Inverters + Automation Mjb 400 Mb4](#)

[Type: Ma 90s4](#)

[A4c2542aast16](#)

[D5s225m4](#)

[A4c250m4 B3 A4c2542a00016 By A6c250m4](#)
[55kw B3](#)

[D6c 90 L2 B5](#)

[Sb35dv135c](#)

[90s-4](#)

[Maq1311a 00017](#)

[100lb-4](#)

[B5s 355 Ld6](#)

[A6c 280s-4](#)

[W0a2000 A5c200I8](#)

[D6c1132b00016](#)

[Baa 160 L8](#)

[E4f2243a00010](#)

[Maa 132 Sb2 B3 2910tr.Min 7.5kw](#)

[Szwc04343a](#)

[Mjb 355 Ma/4-Im B34](#)

[A4c28420a365](#)

[Pt100 Temperature Transmitter](#)