



Mdler

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Mdler** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Mdler Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece OrĐinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
10711900	
10711700	
10700000has	
14000700	Chain tensioning wheel KSP 12 B-1 3 / 4x7 / 16 "15 teeth with ball bearing
14000712	Chain tensioning wheel KSP 12 B-1 3 / 4x7 / 16 "12 teeth with ball bearing
10799117	Kettenrad KRR mit einseitiger Nabe 12B-1 3/4x7/16" 17 Zhne Mat. 1.4305
10711500	Sprocket KRS with one-sided hub 12 B-1 3 / 4x7 / 16 "15 teeth Mat. Steel
10711200	Sprocket KRS with one-sided hub 12 B-1 3 / 4x7 / 16 "12 teeth Mat. Steel
10700300	Plug-in link with spring lock No. 11 / E for single roller chain 12 B-1 pitch 3 / 4x7 / 16 "packaging unit 5 pieces
10700000has (161)	Single roller chain 12 B-1 pitch 3 / 4x7 / 16 "on reel 2 x 161 links = 3.067m
10700000has (203)	Single roller chain 12 B-1 pitch 3 / 4x7 / 16 "on reel 3 x 203 links = 3.867m
10700000has (231)	Single roller chain 12 B-1 pitch 3 / 4x7 / 16 "on reel 4 x 231 links = 4,400m
10799119	Sprocket KRR with one-sided hub 12B-1 3 / 4x7 / 16 "19 teeth Mat. 1.4305
64640625	Shaft bracket GWL for shaft diameter 25mm

24102000	Spur gear made of C45 without hub module 2 20 teeth tooth width 16mm Outside diameter 44mm Customs tariff number: 84839089
24111020	Spur gear made of C45 without hub module 2 20 teeth tooth width 20mm Outside diameter 44mm Customs tariff number: 84839089 Country of origin: Non-EU
25460511	Precision gear rack made of bright steel 900N/mm ² , module 4, 1000mm long, tempered with milled teeth, helical teeth 19°31'42" right-hand with bores
25402140	Precision spur gear made of 16MnCr5 module 4 21 teeth bore 40H6 hardened and ground helical teeth 19°31'42" left hand Outer diameter 97.1mm
68580665	Rubber-metal bump stop MGS diameter 60mm height 40mm Thread M12x33
60092500	Split shell coupling MAT on both sides bore 25mm with keyway steel C45 burnished with screws DIN 912-12.9
60092000	Split shell coupling MAT on both sides bore 20mm with keyway steel C45 burnished with screws DIN 912-12.9
A: 60099925	alternative position Split shell coupling MAT on both sides bore 25mm with groove stainless steel 1.4305 with screws DIN 912 A2-70
5555 Shore 68580665	Rubber-metal bump stop MGS diameter 60mm height 40mm thread M12x33
Mdler 24343200	
68583500	Rubber metal stop buffer MGK diameter 50mm thread M 10x28
17422800	HTD toothed strap made of steel profile 8m 56 teeth for straps 30mm
17533700	HTD toothing straps neoprene profile 8m width 30mm acts 1600mm Number of teeth 200
68580500	Rubber metal stop buffer MGS diameter 40mm height 30mm thread M8x23
66651500	Switching cross 2130 ST hub diameter 60mm ball button made of plastic
63261000	Journey head GT DIN ISO 12240-4 Ma series K Inner thread M10 right maintenance -free
63271000	Journey head GT DIN ISO 12240-4 Ma series K Inner thread M10 left maintenance -free
66402000	Cumer button DIN 319 Pf Form C plastic with press fabric thread Bug diameter 20mm
	Metal balgace coupling MBK Short execution on both sides bore 10mm Total length 49.7mm hub diameter 37.4mm ***

60153710	we offer standard part without editing => no production drawing ***
62399480	Split clamping ring stainless steel 1.4305 bore 80mm with screws DIN 912 A2-70
S10031100	Sprocket KRS with one-sided hub 03 pieces. 5mm 11 teeth material steel Including editing: Machining according to drawing 18095.0008.05.008
10030000-265	Single roller chain No. 03 Pitch 5mm Length: 265mm 53 links ending inside
10030000-275	Alternative position Single roller chain No. 03 pitch 5mm length: 275mm 55 links ending inside
10030300	Plug-in link with spring clasp No. 11 / E for single roller chain No. 03 pitch 5mm
A: 10030300	Alternative position Plug-in link with spring clasp No. 11 / E for single roller chain No. 03 pitch 5mm
62410606	Flange socket, slotted version 6 x 8.0 / 12 x 7 mm
62399470	Split clamping ring stainless steel 1.4305 bore 70mm with screws DIN 912 A2-70
10881325	Sprocket KRF with one-sided hub 16 B-1 13 teeth bore 25H7 keyway DIN 6885/1 2 Adjusting screw thread material steel teeth induction hardened
10800000-991	Single roller chain 16 B-1 pitch 1"x17.02mm length: 990.6mm 39 links ending inside Please check length!
14000800	Chain tension wheel KSP 16 B-1 1"x17.02mm 12 teeth with ball bearings
62599125	Ball pillow block bearing SSUCP 205 bore 25mm housing and bearing made of stainless steel
20099900	Turnbuckle nut M36 - DIN 1478 M 36 x 295 zn* grade S235 or steel with corresponding properties
14040201	Chain tensioner SPANN-BOX® size 0 high clamping force up to 06 B-1
65522400	Articulated plate 2259 Version A Thread M24 Plate made of tempered steel
64673001	Open linear bearing unit KG-3-O ISO series 3 Premium with open linear ball bearing with angle compensation with double lip seal for shaft diameter 30mm
51077301	Precision shaft steel with shaft support Ø 30h6 Length 3500 +/-2mm Support rail as a complete piece (no separation points)
623 994 80 , 1.4305 (X8CrNi18-9)	
	Flange bushing similar to DIN 1850-3 Form V made of

62355500	sintered bronze bore 50mm outer diameter 60mm collar diameter 70mm length 32mm
63415000	Rod end GEW DIN 12240-4 series E internal thread M45x3 right maintenance-free
A: 63415000	Rod end GEW DIN 12240-4 series E internal thread M45x3 right maintenance-free
685 311 20	
685 805 20	