

Medenus

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Medenus Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Medenus T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



| ¼r¼n | A¼ıklama |
|------------------------------|----------|
| 0102-044/2 | |
| 0102-044/3 | |
| 12x.1.5 | |
| 751000-00442 | |
| 751000-00450 | |
| 791600-00228 | |
| 861100-00188 | |
| 861100-00228 | |
| 870800-00282 | |
| 9204-019/11 | |
| 9204-019/12 | |
| 9204-019/9 | |

| |
|--|
| AFM34-DN25 |
| BFA100X90X25 |
| Dn50 pn6 |
| E01-751500-00358 Index 2006 |
| ES-00001 |
| ES-00015 |
| ES-00024 |
| ES-00030 |
| ES-00036 |
| ES-01005 |
| R50 |
| RS 250/50/50/80 |
| RS250 |
| RS250 Dn50 |
| RS250/025/160/17,5/MD-R |
| RS250/050/320/17,5/MD |
| RS251 |
| RS251 DN80 |
| RS251/080/385/65/MD-R no. 0611-001/04G |
| Typ: RS 250 |
| ZA-3.1 |
| 751500-00243 <p>Gas pressure regulator with built-in SAV RS250/100/275/52.5/MD like Serial No.: 0711-058 Gas pressure regulator with integrated SSV Type: RS 250 / connection: DN 100 PN 16 Flow direction: left to right Max. allowed pressure PS: 8 bar Design: IS / Temperature: -20°C - +60°C Housing material: aluminum alloy Control facility: 275 Nozzle: 52.5 mm / KG value: 1800 m³/(h*bar) (natural gas) Overall length: 350 mm / weight: 23 kg Inlet pressure Pu min.: 4 bar Inlet pressure Pu max.: 4 bar Outlet pressure Pds min.: 150 mbar Outlet pressure Pds max.: 150 mbar Specific conduction range Wds: 133-239 mbar Flow rate Q min.: 2300 Nm³/h Flow rate Q max.: 2300 Nm³/h Gas type: natural gas L SAV functional class: A SAV trigger min. Pdsu: 20 mbar Specific control range Wdsu: 18-30 mbar SAV triggering max. Pdso: 250 mbar Specific control range Wdso: 210-370 mbar + FA010 Regelfeder / regulating spring FA + FD915 control</p> |

| | |
|---|---|
| | spring pilot regulator + FE902VA SAV minimum spring FE 902 |
| B-DN100-M16 | Mounting kit housing DN 100 incl. 2x rubber-steel seal Mounting kit housing DN 100 incl. 2x rubber steel gasket consisting of: 16x threaded rod M16 32x nut M16 32x washer M16 2x rubber-steel gasket KGS-GII-DN-100 |
| 0909-017/04B | |
| TYP:RS-251 DN:80 PN:16 Fab-Nr:0909-017/03j | |
| D-5064 1210036723/001 065.057.127 | |
| 870800-00300 | |
| E01-870800-00208 | |
| Afm34-Dn50 | |
| Rs251 Dn80 Pn16 | |
| Rs251 861100-00228 | |
| R-2 | |
| Sealing Washer For Regulator Medenus Rs251 | |
| 751000-00450 Fabr.-Nr.: 1408-048/01 | |
| Rs251 Dn50 Pn16 | |
| Dn 80:Rs 250/Rs 251 | |
| Fa011 | |
| 861200-00151 | |
| R-4 | |
| Es-00017 | |
| E01-861100-00177 Index 2006 Rs251/050/275/32,5/Md-R | |
| Rs251/050/275/52,5/Md-R | |
| Rs251/050/275/27,5/Md-R | |
| 861100-00228 (Typ: Rs 251) | |
| R-3 | |
| En 1706 | |
| 840100-Sbv-00004 | |
| 861100-00179 | |
| | |

[723200-U-00011 Index Aerzen Typ: R
100-U](#)

[Dn 100:R 101/Rs250](#)

[R-6](#)

[E-01-751500-00218](#)

[B2709/0401/.278-Hagsr,Dn100](#)

[SI10](#)

[Rs251/050/275/42,5/Md-R](#)

[Rs250 Dn100](#)

[R 100 U Dn50 723000-U-00005](#)

[1101-059/01](#)

[Item 3 - Medenusgas, En 1706, Ac-
42100sf, Ac-43000](#)

[D-5064 Flowrate 450m3/ Hr](#)

[Compensation Membrane For Regulator
Medenus Type Rs251](#)