

## Menzel Elektromotoren

Garanti: 12 ay  
Bu rne ait Trkiye iĐi kapı teslim fiyat ve teslim sresi iĐeren teklifimizi almak iĐin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iĐin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Menzel Elektromotoren** Markası, tedarik sresi iĐin ltfen bizimle iletiŐime geĐiniz.

*Firmamız Menzel Elektromotoren Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	AĐıklama
<a href="#">Menzel Elektromotoren</a>	
<a href="#">Menzel Elektromotoren</a>	
<a href="#">Mebssl450-04</a>	three-phase slip ring motor Make Menzel Condition new Norm IEC / EN 60034-1 Rated power kW 710 Duty S1 Voltage [V] 380 Connection D Frequency [Hz] 50 Rated speed [min-1] 1490 Nominal current A 1333 Poles 4 Direction of rotation Both Rotor voltage [V] 608 Rotor current A 726 Efficiency % 94 Cos phi 0,85 Starting method: DOL Breakdown torque % 210 Mounting IM B3 Protection: IP 55 Cooling IC611 Balancing: Half Key Vibrations max. mm/s 2,3 Moment of inertia: J (kgm <sup>2</sup> ) 19 Weight [kg] 5010 Anti-friction bearings, grease-lubricated Accessories: 6 RTD Winding 2 RTD Bearing 2 SPM Nipples Heater, 220 - 240 V, 50 Hz, 1Phase Main Terminal Box RHS Rotor Terminal Box RHS Terminal Box RTD Terminal Box Heater Site Conditions & Others: Starts cold / hot / pa: 3 / 2 / 1000 Insulation class: F Temperature rise: B Ambient temp.: -20...+40 °C Altitude: <1000 m a.s.l. Humidity: < 95% Use: Outdoor
<a href="#">7.5kw,Speed:3000rpm(2-Pole</a>	

[61602](#)

[Mebk225m-06-190](#)