

Metalwork

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Metalwork** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Metalwork T¼rkiye Distrib¼t¼r¼ veya temsilcisi deėildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	Aıklama
5206011	
9700110	
7020010100	
7020 0102 00	3/2-way valve, 1/4" PNV 33 PNS-NC pneumatic normally closed, Control ports = 1/8
9200701	
1213630050cn	Cylinder ISO 15552 Ø = 63mm stroke = 50mm Series 3, double acting, adjustable cushioning, with magnet, Piston rod = C45 hard chrome plated, Seals = NBR
2400 80R0 12CP	Compact cylinder UNITOP Ø = 80 mm stroke = 12 mm 001 2400 80R0 12CP - 2-fold multi-position cylinder - IG piston rod - double acting - with magnet - piston rods = C45 hv - Seals = PU
W095 4110 00	REED SENS. T7 SQR 2 Wires 300 mm M8 Rob
W095 2028 184	REED sensor for T-slot CR2M8 2-pin M8
2130 6300 20CN	Short-stroke cylinder SSCY Ø=63 mm, stroke=20 mm double-acting, without magnet Piston rod = C45
2700 6311 50CN	Cylinder Ø=63mm Stroke=1150mm 2700 6311 50CN rodless, standard, double-acting, with magnet, Gaskets=NBR
	Cylinder ISO 15552 Ø=80 mm Stroke=850 mm 002 1213 8008 50AN

1213 8008 50AN	Series 3, double-acting, adjustable cushioning, with magnet Piston rod = C45 hard chrome plated, Seals= NBR
7045 0202 10	Two-channel 3/2-way valve, 3/8" SOV C3 SOS DD 3F Valve series 70 SAFE AIR, monostable
W021 5000 101	COIL 22 Ø8 BA 2W-24VDC 100% ED, IP65, DIN 40050
W097 0510 011	Socket 22mm standard black DIN industry standard - form B
0227 3013 03	Intermediate plate separate exhaust air HDM 1-25D Ø10
9041 0050 00	Flow regulator RFL U 1/2" can be regulated on one side
W 143 032A 200	Compact guide cylinder Ø=32 stroke=200 001 W 143 032A 200 Alternative to W 1450302200, as it is no longer manufactured! - Multifix series - double-acting - with elastic cushioning - with bronze bushings - Piston = aluminum alloy - Piston rod = rolled chrome steel - Guide rods = rolled chrome steel - Seals = NBR
7010 0212 00	5/2 way valve, G1/8" Type: SOV 25 SOB 00 Connection: 1/8" electro pneumatic, bistable
7010 0211 00	5/2 way valve, G1/8" Type: SOV 25 SOS 00, monostable Electropneumatic Spring return
2031018	
2031005	
0227300300	
1213a10180ap	
0227300302	
2032017	
2032005	
2031003	
2032008	
2004001	
2001002	
9041202	
2031014	
2001014	
2131014	
2031017	
2101012	
2004004	
2031009	
561b26	
2001007	
7069030532	
2031012	

2031002
2001012
2032010
1211000180ap
2031013
2001008
2001011
2001003
2005005
2101013
2001010
2031011
2005001
2001006
2032002
2031008
2004003
2004005
2032014
2031006
2032011
2005002
2032009
2001013
W0950025390