

Michell

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Michell Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Michell T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



| ¼r¼n | A¼ıklama |
|--------------------------------|---|
| EA-XP-TX | Basic model: Easidew PRO XP 2-wire trace moisture transmitter with 3/4 "UNF-16 process connection for gases (4-20mA current loop, heavy-duty version for field use, explosion & flame proof). Standard measuring range -110 / + 20 ° C dew point + EX2 Local display: integrated in the transmitter housing with viewing window + C2 Sensor protection: Standard HDPE filter for Easidew sensors (protection against fine particles > 10 µm) + D2 Sensor block: 3/4 "UNF stainless steel sampling block (with 1/8" NPT gas ports for inlet / outlet) + E1 Mounting bracket: Without mounting bracket + F2 Material certification: BS EN 10204 3.1 Material Certificates + G1 Housing material: aluminum + H1 Measuring range: -110 to + 20 ° C (-148 to + 68 ° F) dew point measuring range |
| I7000-XP | Basismodell: Interchangeable RH and Temperature Sensor |
| I7000-XP-B1 | %RH output signal: 0-1 V |
| I7000-XP-C2 | Temperatursignal: No temperature output |
| Cea-M20-Npt-Ss | |

| | |
|---|--|
| Ms/0/232616 | |
| Dt722-Sd-H-T0-02-Cc-F02 | |
| Apt-Pan | |
| St-3217-Pc | |
| Ms/0/232615 | |
| Msa299-295 | |
| Sf52-Tx-2-S-D3-B | |
| Hf132-Sb1xxxxx | Transmitter for humidity and temperature room sensor, 3/4-wire version. Power supply: 15 ... 40 VDC / 12 ... 28 VAC, accuracy @ 23 ° C ± 5K: ± 3% RH / ± 0.3K, application / measuring range: 0 ... 50 ° C / 5 .. .95% RH, housing: ABS / IP30, output signals: OUT1: 4 ... 20 mA = 0 ... 100% RH, OUT2: 4 ... 20 mA = 0 ... 50 ° C. |
| Cg-M20-Ss | |
| Cea-M20-Bsp-B | |
| A000350 | |
| 9934042 | |
| Cg-M20-B | |
| Ea2-Tx-80hd | |
| Cea-M20-Npt-B | |
| Hf320-Sba3xxxx | Transmitter for humidity and temperature Version: room mounting, 2x2-wire version, application range: -40..60 ° / 0 ... 100% RH, power supply: 12 ... 28 VDC, accuracy: ± 2% RH / ± 0, 3K, output signals: OUT1: 4 ... 20 mA = 0 ... 100% RH, OUT2: 4 ... 20 mA = 0 ... 100 ° C. |
| Ea2-Cab-02 | |
| Cea-M20-Bsp-Ss | |
| Epr-Brk | |
| Ea2-Tx-100-Hd | |
| Ea2-OI-Hyg-100-Hd-Ac-Sc08 | |
| Epr-Is-2 | |
| Ms/0/232614 | |