

## Micro Detectors

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Micro Detectors** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Micro Detectors T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">AE6/AP-3FML</a>	M.D. Standard d.c. 3 wires inductive proximity sensor, M8 short LD shielded NO / PNP SN = 2 mm, flush, plug connection M8 x 1 mm Housing length: 40 mm, short Design; DC 3-wire, PNP, normally open, LASER MARKING ON SENSOR INSTEAD OF LABEL
<a href="#">AE6-AP-3FML</a>	Protected sensor diameter 8 mm NA PNP distance 2 mm connector 8 m
<a href="#">AE6/AP-3F</a>	M.D. Standard d.c. 3 wires inductive proximity sensor, M8 short LD shielded NO / PNP SN = 2 mm, flush, plug connection M8 x 1 mm Housing length: 40 mm, short Design; DC 3-wire, PNP, normally open
<a href="#">FAI7/BP-0E</a>	M.D. FAI7/BP-0E Optosensor 85365080 - IT
<a href="#">S5N-PA-2-A00-NN</a>	952002091
<a href="#">BX10SR/0A-HB</a>	MD BX10SR/0A-HB Sensor, transmitter + receiver, NO, 10 beams with 0.3...2m, PNP/NPN, M12 plug / 10mm resolution at 90mm height/ IP67 PBT standard, PC window 85365080 - IT - 0.2kg
<a href="#">AM1/AP-2H</a>	Inductive sensor M12 unshielded NO/PNP conn. M12
<a href="#">AM6/AP-2H</a>	Inductive sensor M12 short unshielded NO/PNP conn. M12
<a href="#">AM6/AP-4H</a>	Inductive sensor M12 unshielded NO/PNP conn. M12
<a href="#">AM1/AP-4H</a>	Inductive sensor M12 unshielded NO/PNP conn. M12

<a href="#">FAR3/BP-1E</a>	
<a href="#">FARN/BP-1E</a>	
<a href="#">FAI7/BP1E</a>	
<a href="#">BX10R/AD-HB</a>	Area sensor Receiver 10 beams DO. conn. M12P+N10-26VDC
<a href="#">BX10S/X0-HB</a>	Area sensor Emitt. 10 beams adj. CK. Conn.M12 10-26VDC
<a href="#">MD MICRO DETECTORS SSP/CP-1H</a>	
<a href="#">MD MICRO DETECTORS SSP/AP-1H</a>	
<a href="#">gw ak6/d2-5h</a>	
<a href="#">CTR.AB..0336 H8R/1</a>	
<a href="#">CTR.AB..0335 H8E/1</a>	
<a href="#">CTR.AA..0171 B&amp;T TIPOMET 60 OPTICAL</a>	
<a href="#">FAIZ/BP-0E, FAIH/00-0E, FAIH/00-1E</a>	FAIZ/BP-1E
<a href="#">AM6/AP-3H</a>	
<a href="#">M924/SAM8540P04137</a>	280XX910
<a href="#">BX10S/00-HBLSAN</a>	
<a href="#">FAIH/00-0A84</a>	
<a href="#">Diak1ap4h</a>	
<a href="#">Ak1/AP-4h</a>	