

Minsup

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Minsup Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Minsup T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
173 X 08/001/03/000	1" Minsup Typ A, BSP AG
08/013/16/000	Minsup claw clutch, small head 1" hose nozzle Wst.: steel, galvanized Size 1" Small Material SG Iron Seal Natural Rubber Working Pressure 1000 PSI (6.9 MPa) Burst Pressure 4000 PSI (27.58 MPa) SG Iron ISO 1083 Zinc Plated AS1789 Natural Rubber Seal (-29°C to 71°C) Constant vibration created by air drills, pavement breakers etc. is destructive to air hose couplings, especially the quick-acting type. To provide protection, connect one end of a 1 to 3 meter length of air hose to the tool using the heat-treated "No. 3500" Steel Nipple which withstands vibration for a longer period. Connect the other end of "Whip Hose" to the air supply with the quick-acting coupling. "Whip Hose" should remain permanently connected to the tool and should be the same diameter as the supply line hose.
	Diverse Minsup® A Type Three Way Connector stole Gasket natural rubber Material SG Iron Seal Natural Rubber Working Pressure 500 PSI SG Iron ISO 1083 Zinc Plated Natural Rubber Seal (-29°C to 71°C) All Minsup Claw Couplings comply with AS 2554 and AS2660 - Hose and Hose

08/001/16/000	Assemblies for Air/Water. Constant vibration created by air drills, pavement breakers etc. is destructive to air hose couplings, especially the quick-acting type. To provide protection, connect one end of a 1 to 3 meter length of air hose to the tool using the heat-treated "No. 3500" Steel Nipple which withstands vibration for a longer period. Connect the other end of "Whip Hose" to the air supply with the quick-acting coupling. "Whip Hose" should remain permanently connected to the tool and should be the same diameter as the supply line hose.
08/080/01/000	wood pickaxe Steel head, wood handle
08/080/01/000C	Diverse Various hoe Steel head, impact-resistant plastic handle
08/001/04/000	Minsup hose coupling 'A' 1" BSPT F Steel Gasket natural rubber
08/001/03/000	Minsup Hose Coupling Type 'A' 1" BST AG Steel Gasket natural rubber
COUPLING 1" BSP FEMALE TYPE-A MINSUP	1001961
COUPLING 1" BSP MALE TYPE-A MINSUP	1001962
08/001/05/000	Claw clutch 'A' 001/05 pants end 25 mm