

Montwill

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Montwill Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Montwill T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
M1-1VR4B.0001.770DD	4-digit digital display, dimension: neutral Housing size W96xH48xD40mm including plug-in terminal Digit height 14mm, red Display range from -1999 to 9999 MIN / MAX value query can be switched off Operation lock via 4-digit code 10 support point linearization of the measurement input Degree of protection: IP65 on the front Supply: 24VDC galvanically isolated Measuring input: 0 / 4-20mA, 0-10VDC Measuring span: -22 .. + 24mA, -12 .. + 12VDC Connection: plug-in screw terminal Operation: on the front via foil keyboard including fastening material Operating instructions M1_x1D
96-047PVE4/PVE4/PVE4	
DV 3.001.320B	
M1-1VR4B.0005.570DD	
M1-1VR4B.0506.570CD	
M1-7SR4A.0001.K70DD	
M1-7TR4A.020C.710DD	

M1O-1VR4B.0001.770DD	
MB1-33RHO.0001.770AD	
MB1-33RHO.0001.770BD	
PBVD2.001.3722B	
PFE 4.307.380B	
PME.4.20X.1592B	
PTE.4.40X.1542B	
M2-1GR5B.00X0.570CD	
M2-1MR5B.020X.572CD	5-digit digital display, dimension: neutral Housing size W96xH48xD89mm including plug-in terminal Digit height 14mm, red Display range -19999 to 99999 switchable MIN/MAX value query Operating lock via 4-digit code 30 support points linearization of the measurement input Degree of protection: IP65 on the front Supply: 230VAC 50/60Hz Measuring input: 1mV; 2mV; 3.3mV free to 4mV/V Bridge supply: 10VDC/350 Ohm Digital input: <2.4 OFF, >10V ON, max 30VDC Switching output: 2 changeover relays 250VAC/5A,30VDC/5A Connection: plug-in screw terminal Operation: on the front via membrane keyboard including fasteners Operating instructions M2_1MD
Alternative to DV3.201.170C:	M2-1VR5B.0201.670CD 5-digit digital display, dimensions: neutral Housing size W96xH48xD89mm including plug-in terminal Digit height 14mm, red Display range from -19999 to 99999 switchable MIN/MAX value query Operating lock via 4-digit code 30 support points for linearization of the measurement input Degree of protection: IP65 on the front Supply: 10-30VDC galvanically isolated Measuring input: 0/4-20mA, 0-10VDC Measuring span: -22..+24mA, -12..+12VDC Sensor supply: 10VDC/20mA Digital input: <2.4 OFF, >10V ON, max 30VDC Connection: plug-in screw terminal Operation: on the front via membrane keyboard including fasteners Operating instructions M2_11E
Alternative to DV3.001.170C	M1-1VR4B.0001.770DD 4-digit digital display, dimension: neutral Housing size W96xH48xD40mm including plug-in terminal Digit height 14mm, red Display range from -1999 to 9999 switchable MIN/MAX value query Operating lock via 4-digit code 10 support points linearization of the measurement input Degree of protection: IP65 on the front Supply: 24VDC galvanically isolated Measuring input: 0/4-20mA, 0-10VDC Measuring span: -22..+24mA, -12..+12VDC Connection: plug-in screw terminal Operation: on the front via membrane keyboard including fastening material Operating Instructions M1_x1D
	5-digit digital display, dimension: neutral Housing size W96xH48xD89mm including plug-in terminal Digit height 14mm, red Display range -19999 to 99999 switchable MIN/MAX value query Operating lock via 4-digit code 30 support points linearization of the measurement input

M2-1VR5B.0001.670CD	Degree of protection: IP65 on the front Supply: 10-30VDC galvanically isolated Measuring input: 0/4-20mA, 0-10VDC Measuring span: -22..+24mA, -12..+12VDC Connection: plug-in screw terminal Operation: on the front via membrane keyboard including fasteners Operating instructions M2_11E
DV3.001.150C	Digital display 3 1/2 digits, dimensions: neutral Housing W96xH48xD134mm including screw terminal Digit height 14mm, red Display range from -1999 to +1999 Degree of protection: IP40 on the front Supply: 230VAC 50/60Hz Measuring input: 0-10-50-200VDC, 0/4-20,200mA Offset: -500 to +500, Measuring rate: 1s pluggable to 0.25s Connection: screw terminal Operation: behind the windscreen including fasteners User Manual DV315D
M2-1MR5B.020X.572CD	5-digit digital display, dimension: neutral Housing size W96xH48xD89mm including plug-in terminal Digit height 14mm, red Display range -19999 to 99999 switchable MIN/MAX value query Operating lock via 4-digit code 30 support points linearization of the measurement input Degree of protection: IP65 on the front Supply: 230VAC 50/60Hz Measuring input: 1mV; 2mV; 3.3mV free to 4mV/V Bridge supply: 10VDC/350 Ohm Digital input: <2.4 OFF, >10V ON, max 30VDC Switching output: 2 changeover relays 250VAC/5A,30VDC/5A Connection: plug-in screw terminal Operation: on the front via membrane keyboard including fasteners Operating instructions M2_1MD
DV3.001.150C	Digital display 3 1/2 digits, dimensions: neutral Housing W96xH48xD134mm including screw terminal Digit height 14mm, red Display range from -1999 to +1999 Degree of protection: IP40 on the front Supply: 230VAC 50/60Hz Measuring input: 0-10-50-200VDC, 0/4-20,200mA Offset: -500 to +500, Measuring rate: 1s pluggable to 0.25s Connection: screw terminal Operation: behind the windscreen including fasteners User Manual DV315D
M2-1TR5B.040X.572CD	5-digit digital display, dimension: neutral Housing size W96xH48xD89mm including plug-in terminal Digit height 14mm, red Display range -19999 to 99999 switchable MIN/MAX value query Operating lock via 4-digit code 30 support points linearization of the measurement input Degree of protection: IP65 on the front Supply: 230VAC 50/60Hz Measuring input: thermocouple type B,E,J,K,L,N,R,S,T Switching output: 2 changeover relays 250VAC/5A,30VDC/5A Connection: plug-in screw terminal Operation: on the front via membrane keyboard including fasteners Operating Instructions M2_1TD
M2-1tr5b.040x.572cd	
Dv3.001.170c	
M1-1vr4b.0001-770bd	
Dve3.001.776b (Obsolete - Replaced By M1-7vr4a.0001.770cd)	
M2-1mr5b.020x.572cd	

M1-7vr4a.0001.770cd
?2-1gr5b.00?0.570cd
Pb6.A000.3730b
Type:Pte.4.40x.1542b - Alternative M2-1tr5b.040x.572cd
Dv4.001.110c
M1-6vr4b.0001.770bd
M1-7vr4a.0001.770cd
M1-1vr4b.0001.770cd
Dv3.001.776b
Pme4.23x.1592b Obsolete, Replaced By M3-1mr5b.02xx.S72bd
M1-1vr4b.0001.770bd
M3-1mr5b.02yx.S72ad
M3-7vr5a.00x6.772ad
M1-7vr4a.0001.770dd
M2-1gr5b.00x0.570cd Indikator (Ps 4.030.112 B Nicht Mehr Produziert)
M1-7vr4a.0001.770cd Digitale Zeiger
Adapter-6-1
M2-1fr5b.0307.670cd
Dv 3.001.320b By M3-3vr5b.0001.W 70bd
Dv3.001.776b Controller
Pde4.003.8361e
M2-1gr5b.00x0.570cd
Pm-Tool-Musb6
Pfe 4.307.380b By M3-3fr5b.0307.W 70bd
Dv3.002.110c
Gh017-04
Dv3.006.110c
Pde4.003.8361e Dig. Anzeiger 4 Stellig

M1-1vr4b.0001.770bd Anzeige
M1-1vr4b.0001.570cd
Pme4.20x.1592b
Pde 4.003.8361e Manometer Mit Integriertem Sensor
Pme4.40x.1542b
Dv3.006.110c Digitalanzeige
M3-1mr5b.02xx.S72ad
Dv3.001.130c Display
96-047pve4/Pve4/Pve4 - By M3-3vr5b.0001.S72bd (3 Pcs) + Adapter-2-3
M1-7tr4a.020c.710dd
Type: Pde4.003.8361b (B Old Version), Replaced By E New Version
Obsolete Pf4.307.133.B Replaced By M2-1fr5b.0307.670cd
Dv3.001.110c
M1-1vr4b.0001.770dd
M1-7sr4a.0001.K70dd Digital Indicator
M1-1vr4b.0001.770cd Display Digital (Aktuelle Version Version C)
Dv3.001.130c Obsolete/Replaced By M1-1vr4b.0001.770cd
M3-1mr5b.02xx.S72bd
Pme.4.20x.1592b - Alternative M2-1mr5b.020x.572cd
Mg-Avr41.0001.S10bd1
S-Md11-350-2231-0
M1-7tr4a.020c.710cd (Obsolete - Replaced By M1-7tr4a.020c.710dd)
Adapter-2-3
M3-3vr5b.0001.S72bd
Pu5.030x.1s70d